



LED Linear Light Datasheet

Extruded aluminium linear bars with imported diffusers, designed to sit inside curtain wall mullions and outline architecture with even, low glare light.

Facade Lighting Technology Co., Ltd · Shenzhen China · Founded 2010

Email info@facadelighting.net · WhatsApp +86 186 0307 3320 · Tel +86-755 23733769

2nd Floor, Huahao High-tech Park, No.59 Gangzai Street, Xinqiao, Shajing, Baoan District, Shenzhen, China

Acrylic Cover LED Linear Light

Rating	IP67
Control	DMX512
Colour	RGB / RGBW / mono
Safety	Class III

Outdoor Linear Light RGB

Rating	IP67
Diffuser	Frosted or clear glass
Cascade	Up to 60 pcs
Safety	Class III

Outdoor Linear Light For Facade Lighting

Rating	IP67
Control	DMX512
Flame rating	V0
Safety	Class III

LED Light Bar With Wide Diffuser Area

Rating	IP67
Optics	Two side light guide
Colour	RGB / RGBW / mono
Control	DMX512

Outdoor Light Bar With Acrylic Diffuser

Thickness acrylic diffuser with much better smooth light outdoor lights application

Rating	IP67
Diffuser	Thick acrylic
Install	Embedded or flat
Safety	Class III

LED Light Bar For Facade Lighting Project

Rating	IP67
Protocol	TTL
Colour	RGB / RGBW / mono
Flame rating	V0

LED RGB Linear Light LL3618

Transmittance	80%
Grey scale	512 levels
Colours	16,777,216
Control	DMX512

LED Linear Light DMX512 RGB No Gap Connection

Rating	IP66
Transmittance	80%
Cascade	Up to 60 pcs
Load	Stands over 70 kg