



Specification Sheet

Published parameters for every model, grouped by range.

Facade Lighting Technology Co., Ltd · Shenzhen China · Founded 2010

Email info@facadelighting.net · WhatsApp +86 186 0307 3320 · Tel +86-755 23733769

2nd Floor, Huahao High-tech Park, No.59 Gangzai Street, Xinqiao, Shajing, Baoan District, Shenzhen, China

LED Pixel Light

Model	Key Parameters
High Power LED Dot Light 3W	Series M4 · Control DMX512 / dual channel backup · Mounting Aluminium profile or steel wire · Transmittance Up to 90%
V020 LED DMX Pixel Light	Light source 3535 · LED per point 3 / 4 / 6 pcs · Voltage DC12V / 15V / 24V · Protection IP66
D40 RGB LED Point Light	Series D40 · Control DMX512 + dual channel backup · Mounting Steel cable · Transmittance Up to 90%
RGB LED Point Light D40	Series D40 · Control Standard DMX512 · Housing Flame retardant PC · Transmittance Up to 90%
30mm DMX512 Pixel Light	Series D30 · Bit depth 16 Bit · Voltage DC12V · Protection IP66
LED Transparent Mesh Display	Series D018 · Light source 3535 / 5050 · Voltage DC5V / 12V · Weight 3 g per point
LED 3D Ball	Beam angle 360° · Voltage DC12V / 24V · Protection IP66 · Weight 50 g

LED Linear Light

Model	Key Parameters
Acrylic Cover LED Linear Light	Rating IP67 · Control DMX512 · Colour RGB / RGBW / mono · Safety Class III
Outdoor Linear Light RGB	Rating IP67 · Diffuser Frosted or clear glass · Cascade Up to 60 pcs · Safety Class III
Outdoor Linear Light For Facade Lighting	Rating IP67 · Control DMX512 · Flame rating V0 · Safety Class III
LED Light Bar With Wide Diffuser Area	Rating IP67 · Optics Two side light guide · Colour RGB / RGBW / mono · Control DMX512
Outdoor Light Bar With Acrylic Diffuser	Rating IP67 · Diffuser Thick acrylic · Install Embedded or flat · Safety Class III
LED Light Bar For Facade Lighting Project	Rating IP67 · Protocol TTL · Colour RGB / RGBW / mono · Flame rating V0
LED RGB Linear Light LL3618	Transmittance 80% · Grey scale 512 levels · Colours 16,777,216 · Control DMX512

LED Linear Light DMX512 RGB No Gap Connection	Rating IP66 · Transmittance 80% · Cascade Up to 60 pcs · Load Stands over 70 kg
---	---

LED Wall Washer

Model	Key Parameters
18-54W LED Wall Washer Lighting	Power 18 - 54 W · Housing 6063 extruded aluminium · Control DMX512 · Bracket Adjustable
12W Slim LED Wall Washer	Series WW025 · Power 12 - 15 W · Voltage DC24V · LED 48 pcs
18W 24W LED Wall Washer Lamps	Series WW035 · Power 18 - 24 W/m · Voltage DC24V · Protection IP66
18W 24W LED Wall Washer 3000K	Power 18 W / 24 W · Cover Toughened glass · Colour 3000K warm white · Optics No dark areas
DMX LED Wall Washer	Rating IP67 · Cover Tempered glass · Base Integrated precision aluminium · Cooling Air convection
DMX512 LED Wall Washer Lights	Rating IP67 · Waterproof Structural, glue free · Body UV and salt fog resistant · Lens Optical PC
Double Line LED Wall Washer	Rating IP67 · Rows Double line · Cover Tempered glass · Base Angle adjustable
Landscape Lighting Wall Washer	Rating IP67 · Body Thickened aluminium · Cover Tempered glass · Housing colour Customisable
Facade Lighting Wall Washer	Rating IP67 · Body Anti rust aluminium · Angle Adjustable base · Support Design service
Flexible Wall Washer	Rating IP65 · Flex Hand bendable on site · Resolution 16 bit · Safety Class III
4360 36W LED Wall Washer Light	Series 4360 · Power 36 W · Resolution 16 Bit · Optics Customisable lens

LED Spotlight And Flood Light

Model	Key Parameters
12W 30W 36W LED Flood Lights	Power 12 / 30 / 36 W · Rating IP65 · Colour RGB / warm / cool white · Bracket Adjustable
24W 48W LED Spike Light And Projector	Power 24 / 48 W · Rating IP65 · Mount Spike or bracket · Flame rating V0
Cube Series RDM LED Flood Light	Protocol RDM / DMX512 · Rating IP65 · Beam Narrow angle options · Resolution 16 Bit
Black Gold Steel Series LED RGB Spotlight	Rating IP65 · Control DMX512 · Colour RGB / warm / cool white · Body Extruded aluminium

LED Control System

Model	Key Parameters
LED Master Controller For Facade Lighting	Offline points 150,000 · Storage SD card up to 32G · Programs Up to 255 files · Transport Ethernet UDP 100 m
LED Slave Controller For Large Projects	Ports 8 output · Per port 512 channels · Frame rate Up to 120 fps · Network 1000M / 100M