

Product Catalogue 2026

Load cells, weighing indicators, industrial scales, balances, test weights and personal scales

- 68 catalogue models across 11 categories
- OIML R60, NTEP, CE and RoHS ranges depending on model
- Delivery normally under 15 days
- Exported to more than 30 countries and areas
- Components and finished scales on one order

Gromy Industry Co., Ltd. (formerly Gromy Scale Co., Ltd.) · 115 Binwen Road, Binjiang District, Hangzhou, Zhejiang, China · sales@gromyscale.cn · WhatsApp +86 153 9708 2308 · gromyscale.com

Weighing Accessories — Load Cells

Sixteen load cell families covering 2.5 kg to 50 t, in the four structures that cover almost every scale build: single point aluminium, shear beam, S type and column.

Model	Summary	Key specification
H8C Single Shear Beam Load Cell	Alloy steel single shear beam cell with OIML and NTEP approval, 0.5 t to 10 t.	Capacity: 0.5 / 1 / 1.5 / 2 / 2.5 / 3 / 5 / 10 t; 1 to 20 Klb; Accuracy classes: C2, C3, C4, A5M, B10M
B8D Stainless Steel Shear Beam Load Cell	Stainless steel single shear beam cell for corrosive and washdown positions, OIML R60 approved.	Capacity: 0.1 to 10 t; 250 lb to 20 Klb; Accuracy classes: C2, C3, A5M, B10M
SQB Shear Beam Load Cell	Shear beam cell specified for floor scales and low platform scales, IP67 and IP68 versions.	Capacity: 0.25 t to 10 t; Accuracy class: C2 to C5, OIML approved
UDA Aluminium Compression Load Cell	Aluminium compression cell for platform scales and compression testing, 50 kg to 800 kg.	Capacity: 50 to 800 kg; Accuracy class: C3
DEE And DEF S Type Load Cell	S type tension cell for crane scales, belt scales and blending systems, 100 kg to 5 t.	Capacity: 100 kg to 5 t; Accuracy class: C2 to C5
H3 S Type Load Cell	Wide range S type cell from 25 kg to 30 t with OIML R60 C3 and C4 approval.	Capacity: 0.025 t to 30 t; 100 lb to 20 Klb; Accuracy classes: C2, C3, C4, A5S, A5M, B10S, B10M
HM9B Double Shear Beam Load Cell	Hermetically welded double shear beam cell for truck and railway scales, 10 t to 50 t.	Capacity: 10 t to 50 t; Accuracy classes: C1, C2, C3, A5M, B10M
ZSF And ZSFY Column Load Cell	IP68 column cell for weighbridges and heavy platforms, 10 t to 50 t, two bridge resistance options.	Capacity: 10 t to 50 t; Protection: IP68
HM14C Column Load Cell	Hermetically welded alloy steel column cell, 10 t to 50 t, with anti reversal self aligning design.	Capacity: 10 t to 50 t; Accuracy classes: C2, C3, A5S, A5M
BM14C Stainless Steel Column Load Cell	Stainless steel column cell from 0.5 t to 50 t with OIML R60 C3 and C4 approval.	Capacity: 0.5 t to 50 t; Accuracy classes: C2, C3, C4, A5S, A5M
L6D Single Point Load Cell	Smallest single point cell in the range, 2.5 kg to 50 kg on a 250 x 350 mm platform.	Capacity: 2.5 kg to 50 kg; Accuracy classes: C3D, C3, C3G
L6N Single Point Load Cell	Single point cell aimed at electronic balances, 3 kg to 100 kg on a 400 x 400 mm platform.	Capacity: 3 kg to 100 kg; Accuracy class: C3
L6E Single Point Load Cell	Mid range single point cell, 50 kg to 300 kg on a 400 x 400 mm platform, OIML approved.	Capacity: 50 kg to 300 kg; Accuracy classes: C3D, C3, C3G
L6E3 Single Point Load Cell	Single point cell for decks up to 450 x 450 mm, 50 kg to 300 kg.	Capacity: 50 kg to 300 kg; Accuracy classes: C3D, C3, C3G
L6G Single Point Load Cell	Large deck single point cell, 50 kg to 600 kg on a 600 x 600 mm platform.	Capacity: 50 kg to 600 kg; Accuracy classes: C3D, C3, C3G
L6T Single Point Load Cell	Highest capacity single point cell in the range, up to 1000 kg on a 600 x 600 mm platform.	Capacity: 50 kg to 1000 kg; Accuracy classes: C3D, C3, C3G

Weighing Accessories — Weighing Indicators

Eleven indicator models covering the four jobs buyers actually ask for: legal weighing, price computing, ticket printing and process control.

Model	Summary	Key specification
XK315A1 Weighing Indicator	General purpose plastic housing indicator with red LED display, RS232 and 30 hour battery.	Housing: Plastic, 265 x 165 x 170 mm; Display: 6 digit 20.2 mm red LED
XK315A1GB-L Stainless Steel Weighing Indicator	Stainless steel indicator with 25.4 mm LCD and LO-OK-HI check weighing.	Housing: Stainless steel, 265 x 222 x 161 mm; Display: 6 digit 25.4 mm LCD
XK3190-A12 Weighing Indicator	High resolution indicator with anti-vibration software for platform and floor scales.	Models: A12, A12S, A12E, A12ES; Input signal range: -10 mV to 15 mV

Model	Summary	Key specification
XK3118T6-P Printing Weighing Indicator	Platform scale indicator with a built in 57 mm thermal printer and real time clock.	Display: 6 bit LCD with clock display; A/D conversion: Delta sigma technique, 20 bit
KW OIML Approved Weighing Indicator	OIML approved general purpose indicator with 600000 internal counts and 70 hour battery.	Display: 24 mm LCD with white LED backlight; Internal counts: 600000
KP Price Computing Weighing Indicator	Price computing head with a 20 key keypad for counter and market scales.	Display: 20 mm backlit LCD; Capacities supported: 30 kg to 600 kg
XK3119WM Stainless Steel IP67 Weighing Indicator	IP67 stainless steel indicator with a three colour high brightness LED display.	Housing: Stainless steel, module production; Protection: IP67
XK3119WL Stainless Steel IP67 Weighing Indicator	IP67 stainless indicator with LCD and an audible HI, LO and OK check weighing alert.	Housing: Stainless steel; Protection: IP67 waterproof, dustproof, anticorrosive, moisture proof
XK315A6GB Stainless Steel Truck Scale Indicator	Stainless steel weighbridge head storing 200 vehicle numbers and 1000 weighing records.	Housing: Stainless steel, 320 x 200 x 180 mm; Display: 6 digit 20 mm green LED
XK315A6P Printable Truck Scale Indicator	Printable weighbridge head with a large 30.5 mm red LED and built in micro printer.	Housing: Plastic, 320 x 200 x 180 mm; Display: 6 digit 30.5 mm red LED
XK3101 Weighing Control Indicator	Panel mount control indicator with fieldbus interfaces and batching outputs for control cabinets.	Display: 7 bit VFD vacuum fluorescent display; Housing: Aluminium, designed for control cabinet mounting

Weighing Accessories — Test Weights

Calibration weights in E2, F1, F2, M1 and M2 classes, from milligram laboratory sets to cast iron blocks for weighbridge testing.

Model	Summary	Key specification
Stainless Steel Cylindrical Test Weight Set	Cylindrical calibration weight sets in stainless steel and chrome plated finishes, E2 to M2.	Classes: E2, F1, F2, M1, M2; Materials: Stainless steel, chrome plated steel
Cast Iron Block Test Weights	Cast iron block weights with cut out handles for floor scale and weighbridge verification.	Classes: M1, M2; Material: Cast iron

Industrial Scale — Platform Scales

Ten bench and platform scales, from plastic housed shop scales to IP68 stainless steel models built for a washdown hose.

Model	Summary	Key specification
Super-SS IP68 Stainless Steel Platform Scale	The washdown model: IP68 stainless steel bench scale with fully sealed electronics, 0.6 kg to 30 kg.	Models: Super-0.6, 1.5, 3, 6, 15 and 30; Capacity: 0.6 / 1.5 / 3 / 6 / 15 / 30 kg
S29 OIML Stainless Steel Platform Scale	CE and OIML approved IP67 stainless bench scale with a 70 hour battery.	Capacities: 3 kg to 25 kg; Platform size: 230 x 190 mm
T28 OIML Waterproof Platform Scale	Waterproof bench scale with a stainless pan, CE and OIML approval and 15000d resolution.	Capacities: 3 / 6 / 15 / 25 kg; Display: 25 mm LCD with white LED backlight
ACS-SS Plastic Waterproof Platform Scale	Economical IP68 plastic bench scale with dual LED display, 600 g to 30 kg.	Capacity and division: 600 g x 0.05/0.1/0.2 g; 1500 g x 0.1/0.2/0.5 g; 3 kg x 0.2/0.5/1 g; 6 kg x 0.5/1/2 g; 15 kg x 1/2/5 g; 30 kg x 2/5/10 g; Display: LED, dual display
WP-ACS Waterproof Platform Scale	Waterproof bench scale with stainless pan, auto calibration and double LCD, 3 kg to 30 kg.	Models and capacity: WP-ACS 3K/3KB 3 kg, 6K/6KB 6 kg, 15K/15KB 15 kg, 30K/30KB 30 kg; Resolution: 0.1 g to 5 g depending on model; 1 in 2000 to 1 in 15000
TCS-JJ Corrosion Resistant Platform Scale	Rust free plastic steel platform scale for corrosive products, 15 kg to 600 kg.	Capacity: 15 kg to 600 kg; Divisions: 3000 / 6000 / 7500 / 15000, three options per capacity

Model	Summary	Key specification
TCS-A Bench And Platform Scale	Configurable platform scale, 60 kg to 1000 kg, with four structures and OEM manufacture.	Capacity: 60 kg to 1000 kg; Platform size: 300 x 300 mm to 800 x 1000 mm
TCS-H Platform Scale	Framework platform scale with pressure limit protection, 60 kg to 300 kg.	Capacity: 60 / 100 / 150 / 300 kg; Platform size: 30 x 40 cm, 40 x 50 cm
TTZ Platform Scale	Six model platform scale range, 50 kg to 500 kg, class III, with published packing sizes.	TTZ-50: 50 kg, 100 g division, 400 x 300 mm platform; TTZ-100: 100 kg, 200 g division, 400 x 300 mm platform
PF Platform Scale	Five model platform range to 1000 kg with finer divisions than the standard bench ranges.	PF-100: 100 kg, 20 g division, 400 x 300 mm platform, packing 69 x 48 x 16 cm; PF-300: 300 kg, 50 g division, 600 x 450 mm platform, packing 99 x 62 x 21 cm

Industrial Scale — Floor Scales

Pallet weighing platforms in painted carbon steel up to 10 t and full stainless steel 304 up to 3 t, in nine standard platform sizes.

Model	Summary	Key specification
GS-10 Industrial Floor Scale	Carbon steel pallet floor scale from 1 t to 10 t in nine platform sizes.	Capacity: 1 t to 10 t; Platform sizes: 0.8 x 0.8, 1 x 1, 1 x 1.2, 1.2 x 1.2, 1.2 x 1.5, 1.5 x 1.5, 1.5 x 2, 2 x 2, 2 x 3 m
Stainless Steel Floor Scale	Frameless all stainless 304 floor scale for washdown halls, 0.5 t to 3 t.	Capacity: 0.5 t to 3 t; Platform sizes: 0.8 x 0.8, 1.0 x 1.0, 1.0 x 1.2, 1.2 x 1.2, 1.5 x 1.5 m

Industrial Scale — Balances

Eight laboratory and workshop balances, from 0.1 mg analytical models with glass draft shields to economical bench balances for counting and formulation.

Model	Summary	Key specification
FA Analytical Balance	Four model analytical balance series reading to 0.1 mg with RS232C output.	Models: FA1004B, FA2004B, FA1004C, FA2004C; Capacity: 100 g and 200 g
LA High Precision Analytical Balance	Electromagnetic force compensation balance at 0.0001 g with eight weighing unit modes.	Models: LA114, LA164, LA204; Capacity: 110 g, 160 g, 200 g
LAC Internal Calibration Precision Balance	Precision balance with automatic internal calibration, 110 g to 210 g at 0.0001 g.	Models: LAC114, LAC164, LAC204, LAC214; Capacity: 110 g, 160 g, 200 g, 210 g
LDT Strain Load Cell Balance	Economical strain load cell balance, 200 g to 1200 g at 0.1 g, with counting.	Models: LDT201, LDT301, LDT501, LDT601, LDT1001, LDT1201; Capacity: 200, 300, 500, 600, 1000 and 1200 g
WT-K Precision Balance	Eight model 0.01 g precision balance series with CE certificate and metal housing.	Models: WT1002K, WT2002K, WT3002K, WT5002K, WT6002K, WT10002K, WT20002K, WT30002K; Capacity: 100, 200, 300, 500, 600, 1000, 2000 and 3000 g
WT-NF Precision Balance With RS232	Higher capacity 0.1 g balance series with RS232 port and a 160 mm pan.	Models: WT20001NF, WT30001NF, WT50001NF, WT60001NF, WT1000NF; Capacity: 2000, 3000, 5000 and 6000 g at 0.1 g; 1000 g at 1 g
GS-B1 Economical Balance	Economical bench balance with auto calibration and counting, 0.1 g and 0.01 g versions.	0.1 g models: 200, 500, 1000, 1200, 2000 and 3000 g; 0.01 g models: 100, 200, 300, 500, 600, 1000, 2000 and 3000 g
GS-B2 Economical Balance	Higher capacity economical balance, 5 kg to 20 kg, still at 0.1 g readability.	Capacity: 5000, 10000, 15000 and 20000 g; Readability: 0.1 g

Industrial Scale — Truck Scales

Steel deck weighbridges built to your site dimensions, from a 6 m single axle deck to a 24 m full length platform, with capacities up to 300 t for special use.

Model	Summary	Key specification
Steel Deck Truck Scale	Weighbridge deck built to site dimensions, 6 m to 24 m, with OIML R60 cells and a printable indicator.	Deck width: 3 m, 3.2 m, 3.4 m; Deck length: 6, 7, 8, 9, 10, 12, 14, 16, 17.4, 18, 21, 24 m

Industrial Scale — Commercial Scales

Five counter scales for selling by weight, from an economical price computing head up to a barcode label printing scale for a prepack room.

Model	Summary	Key specification
TM Series Barcode Label Printing Scale	Label printing retail scale with Ethernet, USB and 126 shortcut keys, 6 kg to 30 kg.	Models: TM-6A, TM-15A, TM-30A; Capacity: 6 kg, 15 kg, 30 kg
806 Printing Price Computing Scale	Counter printing scale with a 44 key keypad and 38 memory unit prices.	Capacity: 3 / 6 / 15 / 30 / 40 kg; Division: 1 g at 30 kg
803B Price Computing Scale	Counter price computing scale with a 26 key keypad and double side display.	Capacity: 3 / 6 / 15 / 30 kg; Division: 1 g at 30 kg
ACS-A Price Computing Scale	Green LED price computing counter scale, 3 kg to 35 kg, packed four per carton.	Capacity: 3 / 6 / 15 / 30 / 35 kg; Display: Green LED
ACS-A10 Price Computing Scale	Price computing counter scale with three display options, 3 kg to 35 kg.	Capacity: 3 / 6 / 15 / 30 / 35 kg; Display options: LED, LCD, LCD with light

Personal Scale — Body Scales

Five body scales for retail programmes and health rooms, from tempered glass bathroom scales to a combined height and weight measuring station.

Model	Summary	Key specification
2011A Tempered Glass Body Scale	200 kg glass bathroom scale with four sensors, CE and RoHS, built for own brand programmes.	Capacity: 200 kg / 440 lb; Division: 0.1 kg / 0.2 lb
2003A Body Scale	150 kg body scale on a larger 33 x 33 cm glass platform, CE and RoHS.	Capacity: 150 kg / 330 lb; Division: 0.1 kg / 0.2 lb
2008A Backlit Body Scale	Slim 180 kg bathroom scale with a blue backlit display and 8 mm tempered glass.	Capacity: 180 kg / 396 lb; Division: 0.1 kg / 0.2 lb
2004E Body Fat Scale	Body composition scale with foot electrodes, 150 kg, on a glass platform.	Capacity: 150 kg / 330 lb; Division: 0.1 kg / 0.2 lb
M301 Height And Weight Measuring Scale	Clinical column scale measuring height and weight with BMI, 250 kg at 100 g.	Capacity: 250 kg; Division: 100 g, maximum 2500e

Personal Scale — Kitchen Scales

Compact digital kitchen scales for household retail programmes, with tare, unit switching and customised printing.

Model	Summary	Key specification
SF-400 Digital Kitchen Scale	ABS bodied kitchen scale, 5 kg and 7 kg at 1 g, with four sensors and AAA power.	Capacity: 5 kg and 7 kg; Division: 1 g

Model	Summary	Key specification
5000A Glass Kitchen Scale	Glass topped kitchen scale, 5 kg at 1 g, with a slim lithium cell design.	Capacity: 5 kg; Division: 1 g

Personal Scale — Hanging And Crane Scales

Six hanging scales, from mini crane scales with stainless steel shackles and hooks to pocket sized luggage and market scales.

Model	Summary	Key specification
OCS-L Mini Crane Scale	Compact crane scale from 30 kg to 300 kg with stainless hook and 150 hour battery life.	Capacities: 30, 60, 120, 200 and 300 kg; Divisions: 0.01 kg at 30 kg up to 0.1 kg at 300 kg; n of 3000 on most capacities
OCS-C1 Crane Scale	Heavy crane scale from 1 t to 5 t with a swivel hook and remote operation to 10 m.	Capacities: 1000, 2000, 3000 and 5000 kg; Divisions: 0.5 kg at 1 t, 1 kg at 2 and 3 t, 2 kg at 5 t
GS-006 Mechanical Hanging Scale	Battery free mechanical dial hanging scale, 25 kg to 200 kg, with two hooks.	Capacity and division: 25 kg / 100 g; 50 kg / 200 g; 100 kg / 500 g; 150 kg / 500 g; 200 kg / 1000 g; Material: Metal body, transparent PS or PC mask, two hooks
GS-100 Portable Hanging Scale	Pocket sized hanging scale with a ring handle, 10 kg to 40 kg, in four colours.	Capacity and division: 40 kg / 10 g; 20 kg / 5 g; 10 kg / 5 g; Units: kg, lb, oz
GS-101 Portable Hanging Scale	Bar shaped hanging scale with a cord strap, 10 kg to 40 kg, in three colours.	Capacity and division: 40 kg / 10 g; 20 kg / 5 g; 10 kg / 5 g; Units: kg, lb, oz
GS-102 Luggage Hanging Scale	Luggage scale with a folding handle and webbing strap, 10 kg to 40 kg.	Capacity and division: 40 kg / 10 g; 20 kg / 5 g; 10 kg / 5 g; Units: kg, lb, oz