

LED Product Catalogue

135 models across 11 categories

Company	C&R Technology Co., Limited
Manufacturing	Shenzhen Chiclits Technology Co., Ltd.
Registered	Hong Kong, April 2010 (52075396-000-04-13-A)
Address	Floor 6, Bantian Business Building, Banxuegang Road, Bantian Street, Longgang District, Shenzhen, Guangdong Province 518129, China
Email	info@group-cr.com
Telephone	+86 755 81467599
Certification	CE (LVD) BST1703508020002Y-1SC-2 and RoHS BST1703508020001Y-1RC-4, issued by Shenzhen BST Technology Co., Ltd. for the LED bulb line

This catalogue lists every model in the standing range with the specification data published for it. Nothing in this document is a projection or an estimate.

Contents

Category	Models	What it covers
LED Bulbs	59	The retrofit range: everything that screws or bayonets into a socket somebody already owns.
LED Flood Lights	20	Outdoor and site lighting in mains-powered, sensor-triggered and battery-powered forms.
LED Panel Lights	15	Ceiling panels for offices, shops and public interiors in fixed white, tunable white and RGB.
LED Strip Lights	11	Flexible strip by the roll and retail-packed kits, in white and RGB, waterproof and dry.
LED Downlights	9	Recessed ceiling downlights, from fixed-output cans to app-controlled tunable white.
LED Tube Lights	7	T5 and T8 retrofit tubes in the four standard lengths, for fluorescent replacement.
LED Controllers And Remotes	7	The RF, WiFi and 433MHz control layer that drives our colour and tunable white products.
Solar LED Lamps	3	Self-powered garden and wall lamps with motion detection and a pest-repeller variant.
LED Flashlights And Bike Lights	2	Portable task and inspection lighting, including a 365nm UV torch and a rechargeable bike light.
LED Grow Lights	1	Adjustable multi-head grow lighting for propagation, indoor growing and plant display.
LED Desk Lamps	1	Touch-controlled dimmable desk lighting for study, work and bedside use.

LED Bulbs

The retrofit range: everything that screws or bayonets into a socket somebody already owns.

LED PIR Motion Sensor Bulb



Bulb Video	Motion sensor bulb (PS: https://youtu.be/uoGq8dh6bow)
Motion Sensor Bulb Instructions	1.Under the bright environment,the automatically is put out.

8W RGBWW Bluetooth Smart LED Bulb

Part number: **CRBU-BT-08**



P/N	CRBU-BT-08
Luminous Flux(lm)	0~500lm Cool White
CCT Adjustable	2700~6500K
Size	120 x 68.5mm
Input Voltage	AC85-264V
Power	8Watt
LED Type	SMD5050 4PCS + SMD2835 WW 10PCS + SMD2835 CW 10PCS
Max. Lumen	550lm
Material	Aluminum +PC
Option Base	E27
E26	B22
PF	>0.65
Lifespan	50,000Hours

GU10 6W COB LED Spotlight

Part number: **CRSP-GU-01**



P/N	CRSP-GU-01
Luminous Flux(lm)	620lm Cool White
Type	Dimmable Or Non-Dimmable
Size	50 x 58mm
Input Voltage	AC 180-265V 50/60Hz
Power	6 Watt
LED Type	COB
Beam Angle	60°
Material	Aluminum +PC
Option Base	GU10
Operating Temperature	0°C to 40°C
Lifespan	50,000Hours
Packing Information	One bulb per box
Inner Box Size	56 x 56 x 73mm, Gross Weight: 70G, Net Weight: 58G

MR16 6W COB LED Spotlight

Part number: **CRSP-MR-01**



P/N	CRSP-MR-01
Luminous Flux(lm)	620lm Cool White
Type	Dimmable Or Non-Dimmable
Size	50x51mm
Input Voltage	AC/DC 12V
Power	6 Watt
LED Type	COB
Beam Angle	60°
Material	Aluminum +PC
Option Base	MR16
Operating Temperature	0°C to 40°C
Lifespan	50,000Hours
Packing Information	One bulb per box
Inner Box Size	56x56x65mm, Gross Weight: 60G, Net Weight: 48G

3W Vintage Edison LED Bulb E26 Model CRBU-360E-03

Part number: **CRBU-360E-03**



P/N	CRBU-360E-03
Light Source	160pcs SMD3014
Luminous Flux	100~130Lm
Input Voltage	200-240VAC
Beam Angle	360°
Size	64*140mm
Color Temperature	2400K
Lamp Base	E26/ E27
Material	Iron+Glass
Lamp Cover	Clear
Life Span	50,000 Hours
Operating Temperature	-20°C to 45°C
Humidity	10~85%

3W Vintage Edison LED Bulb E26 Model CRBU-360E-04

Part number: CRBU-360E-04



P/N	CRBU-360E-04
Light Source	160pcs SMD3014
Luminous Flux	100~130Lm
Input Voltage	200-240VAC
Beam Angle	360°
Size	64x140mm
Color Temperature	2400K
Lamp Base	E26/ E27
Material	Iron+Glass
Lamp Cover	Clear
Life Span	50,000 Hours
Operating Temperature	-20°C to 45°C
Humidity	10~85%

4W WWCW Smart WiFi LED Bulb

Part number: CRBU-RF-06



P/N	CRBU-RF-06
Luminous Flux(lm)	0~220lm Cool White
CCT Adjustable	2700~6500K
Size	50x74mm
Input Voltage	AC85-264V
Power	4Watt
LED Type	SMD5730 0.5W
LED Quantity	12pcs
Max. Lumen	220lm
Material	Aluminum +PC
Option Base	GU10
PF	>0.65
Lifespan	50,000Hours
Packing Information	One bulb per color box
Inner Box Size	65x65x78mm, Gross Weight: 100G, Net Weight:80G

2W RGB Smart WiFi Glass LED Bulb

Part number: CRBU-RF-14

Mi-Light®



Power	2W
Color	RGB + warm white (2700k-3200k); RGB + cold white (6000k-6500k)
Lumen	120lm
Material	Acrylic
Weight	350g
Dimension	183 * 80mm
Capacity	3.7v/1400mA
Working Time	10 hours for RGB color, 5 hours for white color
Charge Time	3.5 hours
Charge Input	5v/500mA (package come with an USB cable)
Color Changeable	9 flashing modes
Brightness Adjustable	20 level
Wireless Control	by remote controller; by smart phone (need a Wifi controller)

3W Ceramic LED Bulb 45x80mm

Part number: CRBU-CE-01



P/N	CRBU-CE-01
Luminous Flux(lm)	300lm Cool White
Type	Non-Dimmable
Size	45x80mm
Input Voltage	180~264VAC
Power	3 Watt
LED Type	SMD5730 5PCS
Beam Angle	120°
Material	Glass +Ceramic
Color Rendering Index	Ra>80
Option Base	E27
Operating Temperature	-20°C to 45°C
Lifespan	50,000Hours

3W Vintage Edison LED Bulb E26 160-200lm

Part number: **CRBU-360E-01**



P/N	CRBU-360E-01
Light Source	47pcs D3 dip LED
Luminous Flux	160~200Lm
Input Voltage	200-240VAC
Beam Angle	360°
Size	64x140mm
Color Temperature	2400K
Lamp Base	E26/ E27
Material	Iron+Glass
Lamp Cover	Clear
Life Span	50,000 Hours
Operating Temperature	-20°C to 45°C
Humidity	10~85%

6W RGBW Smart WiFi LED Bulb 117x60mm

Part number: **CRBU-RF-09**



P/N	CRBU-RF-09
Luminous Flux(lm)	0~370lm Cool White
Color Adjustable	16million colors changing
Size	117x60mm
Input Voltage	AC85-264V
Power	6Watt
LED Type	SMD5630 0.5Watt SMD5050 1.5W
LED Quantity	11pcs
Max. Lumen	370lm
Material	Aluminum +PC
Option Base	E14
PF	>0.65
Lifespan	50,000Hours
Packing Information	One bulb per color box
Inner Box Size	65x65x130mm, Gross Weight: 120G

3.6W LED Filament Globe Bulb E26

Part number: **CRBU-360F-01**



P/N	CRBU-360F-01
Light Source	Filament COB 4PCS
Luminous Flux	350~400lm
Type	Non-dimmable or Dimmable
Input Voltage	AC:185~264VAC
Color Rendering Index	Ra>82
Beam Angle	360°
Size	60*108mm
Color Temperature	2700~3000K / 4000~4500K / 6000~6500K
Lamp Base	E26/ E27/B22
Material	Aluminum + Glass
Lamp Cover	Clear
Life Span	50,000 Hours
Operating Temperature	-20°C to 45°C
Humidity	10~85% / 1.
Application	Hotel, Conference Room, Exhibition Center etc.

3W LED Globe Bulb E14

Part number: **CRBU-360-01**



P/N	CRBU-360-01
Light Source	SMD3014 0.2W 12PCS
Luminous Flux	210~240lm
Type	Non-dimmable or Dimmable
Input Voltage	AC:85~264V
Color Rendering Index	Ra>85
Beam Angle	360°
Size	■ / 40*92mm/ / 45*95mm For E27
Color Temperature	2600~2850K / 2850~3000K / 4000~4500K / 6000~6500K
Lamp Base	E14/E26/ E27/B22
Life Span	50,000 Hours
Operating Temperature	0°C to 45°C
Humidity	10~85%

5W RGB LED Spotlight

Part number: **CRSP-RGB5A**



Item No	CRSP-RGB5A
Working Voltage	DC12/24V
LED Quantity	1pcs
Power	5w
Base Type	GU10,MR16,E27
Beam Angle	30°,45°,60° for option.
Color Rendering	≥75
Color Temperature	2700-7000K
Luminous	110-130lm
Material	Aluminum + PMMA
Lighting	RGB,Gradual changing
LED Lifespan	>50000hrs

AR111 7W COB LED Spotlight

Part number: **CRSP-010**



Item No	CRSP-010
Working Voltage	AC/DC24V
LED Quantity	7pcs
Power	7w
Beam Angle	30°(normal), 15°, 45°,60° for option.
Color Rendering	≥75
Color Temperature	2700-8000K
Luminous Flux	550lm±8%
Material	Aluminum alloy+ lens
LED Lifespan	>40000hrs

9W LED Globe Bulb E27

Part number: CRBU-030



Item No	CRBU-030
Lamp Base	E27/E26/B22
Working Voltage	AC100-240V 50/60Hz
Power	9W
Color Rendering	≥75
Color Temperature	2700-8000K
Luminous Flux	645lm±8%
Material	Aluminum alloy+ PC
LED Lifespan	>40000hrs

5W Ceramic LED Bulb

Part number: CRBU-CE-02



P/N	CRBU-CE-02
Luminous Flux(lm)	550lm Cool White
Type	Non-Dimmable
Size	57x105mm
Input Voltage	180~264VAC
Power	5 Watt
LED Type	SMD5730 10PCS
Beam Angle	120°
Material	Glass +Ceramic
Color Rendering Index	Ra>80
Option Base	E27
Operating Temperature	-20°C to 45°C
Lifespan	50,000Hours

2W Vintage Edison LED Bulb E26

Part number: CRBU-360E-02



P/N	CRBU-360E-02
Light Source	30pcs D3 dip LED
Luminous Flux	100~130Lm
Input Voltage	200-240VAC
Beam Angle	360°
Size	60*108mm
Color Temperature	2400K
Lamp Base	E26/ E27
Material	Iron+Glass
Lamp Cover	Clear
Life Span	50,000 Hours
Operating Temperature	-20°C to 45°C
Humidity	10~85%

6W LED Filament Globe Bulb E26 600-700lm

Part number: **CRBU-360F-02**



P/N	CRBU-360F-02
Light Source	Filament COB 4PCS
Luminous Flux	600~700lm
Type	Non-dimmable or Dimmable
Input Voltage	AC:85~264VAC
Color Rendering Index	Ra>82
Beam Angle	360°
Size	60*108mm
Color Temperature	2700~3000K / 4000~4500K / 6000~6500K
Lamp Base	E26/ E27/B22
Material	Aluminum + Glass
Lamp Cover	Clear
Life Span	50,000 Hours
Operating Temperature	-20°C to 45°C
Humidity	10~85% / 1.
Application	Hotel, Conference Room, Exhibition Center etc

4W LED Globe Bulb E14

Part number: **CRBU-360-02**



P/N	CRBU-360-02
Light Source	SMD3014 0.2W 18PCS
Luminous Flux	310~360lm
Type	Non-dimmable or Dimmable
Input Voltage	AC:85~264V
Color Rendering Index	Ra>85
Beam Angle	360°
Size	■45*95mm / ■50*102mm/■60*117mm For E27
Color Temperature	2600~2850K / 2850~3000K / 4000~4500K / 6000~6500K
Lamp Base	E14/E26/ E27/B22
Life Span	50,000 Hours
Operating Temperature	0°C to 45°C
Humidity	10~85%

AR111 9W COB LED Spotlight

Part number: **CRSP-010**



Item No	CRSP-010
Working Voltage	AC/DC24V
LED Quantity	9pcs
Power	9w
Beam Angle	30°(normal), 15°, 45°,60° for option.
Color Rendering	≥75
Color Temperature	2700-8000K
Luminous Flux	706lm±8%
Material	Aluminum alloy+ lens
LED Lifespan	>40000hrs

7W LED Globe Bulb E27

Part number: **CRBU-020**



Item No	CRBU-020
Lamp Base	E27/E26/B22
Working Voltage	AC100-240V 50/60Hz
Power	7W
Color Rendering	≥75
Color Temperature	2700-8000K
Luminous Flux	550lm±8%
Material	Aluminum alloy+ PC
LED Lifespan	>40000hrs

3W Ceramic LED Bulb 40x105mm

Part number: **CRBU-CE-03**



P/N	CRBU-CE-03
Luminous Flux(lm)	300lm Cool White
Type	Non-Dimmable
Size	40x105mm
Input Voltage	85~264VAC
Power	3 Watt
LED Type	SMD5730 5PCS
Beam Angle	120°
Material	Glass +Ceramic
Color Rendering Index	Ra>80
Option Base	E14/E27
Operating Temperature	-20°C to 45°C
Lifespan	50,000Hours

GU10 5W COB LED Spotlight 24-36 Degree Beam

Part number: **CRSP-GU-02**



P/N	CRSP-GU-02
Luminous Flux(lm)	520lm Cool White
Type	Dimmable Or Non-Dimmable
Size	50x56mm
Input Voltage	AC 180-265V 50/60Hz
Power	5 Watt
LED Type	COB 1PCS
Beam Angle	24° 36°
Material	Aluminum +PC
Option Base	GU10
Operating Temperature	0°C to 40°C
Lifespan	50,000Hours
Packing Information	One bulb per box
Inner Box Size	52x52x65mm, Gross Weight: 90G, Net Weight: 75G

1.8W LED Filament Candle Bulb E14 180-230lm

Part number: **CRBU-360F-03**



P/N	CRBU-360F-03
Light Source	Filament COB 2PCS
Luminous Flux	180~230lm
Type	Non-dimmable
Input Voltage	AC:85~264VAC
Color Rendering Index	Ra>82
Beam Angle	360°
Size	35*118mm
Color Temperature	2700~3000K / 4000~4500K / 6000~6500K
Lamp Base	E14
Material	Aluminum + Glass
Lamp Cover	Clear
Life Span	50,000 Hours
Operating Temperature	-20°C to 45°C
Humidity	10~85% / 1.
Application	Hotel, Conference Room, Exhibition Center etc.

6W LED Globe Bulb E14

Part number: **CRBU-360-03**



P/N	CRBU-360-03
Light Source	SMD3014 0.2W 30PCS
Luminous Flux	510~560lm
Type	Non-dimmable or Dimmable
Input Voltage	AC:85~264V
Color Rendering Index	Ra>85
Beam Angle	360°
Size	■ / 45*99mm / 50*106mm / 60*121mmFor E27
Color Temperature	2600~2850K / 2850~3000K / 4000~4500K / 6000~6500K
Lamp Base	E14/E26/ E27/B22
Life Span	50,000 Hours
Operating Temperature	0°C to 45°C
Humidity	10~85%

3W RGB LED Spotlight

Part number: CRSP-RGB3B



Item No	CRSP-RGB3B
Working Voltage	DC12/24V
LED Quantity	1pcs
Power	3w
Base Type	E27, GU10, MR16
Beam Angle	30°, 45°, 60° for option.
Color Rendering	≥75
Color Temperature	2700-7000K
Luminous	90-110lm
Material	Aluminum + PMMA
Lighting	RGB, Gradual changing
LED Lifespan	>50000hrs

5W LED Globe Bulb E27 450lm

Part number: CRBU-010



Item No	CRBU-010
Lamp Base	E27/E26/B22
Working Voltage	AC100-240V 50/60Hz
Power	5W
Color Rendering	≥75
Color Temperature	2700-8000K
Luminous Flux	450lm±8%
Material	Aluminum alloy+ PC
LED Lifespan	>40000hrs

GU10 5W COB LED Spotlight 60 Degree Beam

Part number: CRSP-GU-04



P/N	CRSP-GU-04
Luminous Flux(lm)	520lm Cool White
Type	Dimmable Or Non-Dimmable
Size	50x56mm
Input Voltage	AC 180-265V 50/60Hz
Power	5 Watt
LED Type	COB 1PCS
Beam Angle	60°
Material	Aluminum +PC
Option Base	GU10
Operating Temperature	0°C to 40°C
Lifespan	50,000Hours
Packing Information	One bulb per box
Inner Box Size	52x52x65mm, Gross Weight: 90G, Net Weight: 75G

3W LED Filament Candle Bulb E14

Part number: CRBU-360F-04



P/N	CRBU-360F-04
Light Source	Filament COB 2PCS
Luminous Flux	330~360lm
Type	Non-dimmable
Input Voltage	AC:85~264VAC
Color Rendering Index	Ra>82
Beam Angle	360°
Size	35*118mm
Color Temperature	2700~3000K / 4000~4500K / 6000~6500K
Lamp Base	E14
Material	Aluminum + Glass
Lamp Cover	Clear
Life Span	50,000 Hours
Operating Temperature	-20°C to 45°C
Humidity	10~85% / 1.
Application	Hotel, Conference Room, Exhibition Center etc.

9W LED Globe Bulb E26

Part number: CRBU-360-04



P/N	CRBU-360-04
Light Source	SMD3014 0.2W 48PCS
Luminous Flux	800~880lm
Type	Non-dimmable or Dimmable
Input Voltage	AC:85~264V
Color Rendering Index	Ra>85
Beam Angle	360°
Size	Φ60*133mm
Color Temperature	2600~2850K / 2850~3000K / 4000~4500K / 6000~6500K
Lamp Base	E26/E27/B22
Life Span	50,000 Hours
Operating Temperature	0°C to 45°C
Humidity	10~85% / 1.

6W RGBW Smart WiFi LED Bulb 100x57mm


Part number: **CRBU-RF-04**



P/N	CRBU-RF-04
Luminous Flux(lm)	0~470lm Cool White
Color Adjustable	16million colors changing
Size	100x57mm
Input Voltage	AC85-264V
Power	6Watt
LED Type	SMD5630 0.5Watt
LED Quantity	14pcs
Max. Lumen	470lm
Material	Aluminum +PC
Option Base	E27
E26	B22
PF	>0.65
Lifespan	50,000Hours
Packing Information	One bulb per color box
Inner Box Size	65x65x130mm, Gross Weight: 120G, Net Weight: 100G

3W LED Candle Bulb E27

Part number: **CRBU-001**



Item No	CRBU-001
Lamp Base	E27/E26/B22/E14
Working Voltage	AC100-240V 50/60Hz
Power	3W
Color Rendering	≥75
Color Temperature	2700-8000K
Luminous Flux	240lm±8%
Material	Aluminum alloy+ PC
LED Lifespan	>40000hrs

3W Ceramic LED Bulb G45

Part number: CRBU-CE-05



P/N	CRBU-CE-05
Luminous Flux(lm)	300lm Cool White
Type	Non-Dimmable
Size	45x80mm
Input Voltage	85~264VAC
Power	3 Watt
LED Type	SMD5730 5PCS
Beam Angle	120°
Material	Glass +Ceramic
Color Rendering Index	Ra>80
Option Base	E14/E27
Operating Temperature	-20°C to 45°C
Lifespan	50,000Hours

GU10 5W COB LED Spotlight 45 Degree Beam

Part number: CRSP-GU-03



P/N	CRSP-GU-03
Luminous Flux(lm)	520lm Cool White
Type	Dimmable Or Non-Dimmable
Size	50x56mm
Input Voltage	AC 180-265V 50/60Hz
Power	5 Watt
LED Type	COB 1PCS
Beam Angle	45°
Material	Aluminum +PC
Option Base	GU10
Operating Temperature	0°C to 40°C
Lifespan	50,000Hours
Packing Information	One bulb per box
Inner Box Size	52x52x65mm, Gross Weight: 90G, Net Weight: 75G

1.8W LED Filament Candle Bulb E14 190-210lm

Part number: **CRBU-360F-05**



P/N	CRBU-360F-05
Light Source	Filament COB 2PCS
Luminous Flux	190~210lm
Type	Non-dimmable
Input Voltage	AC:85~264VAC
Color Rendering Index	Ra>80
Beam Angle	360°
Size	35*118mm
Color Temperature	2700~3000K / 4000~4500K / 6000~6500K
Lamp Base	E14
Material	Aluminum+Glass
Lamp Cover	Clear
Life Span	50,000 Hours
Operating Temperature	-20°C to 45°C
Humidity	10~85% / 1.
Application	Hotel, Conference Room, Exhibition Center etc.

12W LED Globe Bulb E26

Part number: **CRBU-360-04**



P/N	CRBU-360-04
Light Source	SMD2835 0.5W 28PCS
Luminous Flux	1000~1100lm
Type	Non-dimmable
Input Voltage	AC:85-264V
Color Rendering Index	Ra>85
Beam Angle	360°
Size	Φ80*167mm
Color Temperature	2600~2850K / 2850~3000K / 4000~4500K / 6000~6500K
Lamp Base	E26/E27/B22
Life Span	50,000 Hours
Operating Temperature	0°C to 45°C
Humidity	10~85%

9W RGBW Smart WiFi LED Bulb



Input Voltage	AC85-264V
Power	9Watt
LED Type	SMD5050+SMD5630
LED Quantity	20pcs(including 5pcs5050, 15pcs 5630)
Lumen	760lm
Material	Plastic+ Aluminum +PC
Option Base	E27
E26	B22
Size	120 x 60mm
PF	>0.65
Lifespan	50.000Hours
Function	LED Lamp is dimming, color temperature adjustable, night mode, etc.
Packing Information	One bulb per color box
Inner Box Size	65 x 65 x 130mm, weight: 120G, net weight: 100G

11W LED Globe Bulb E27

Part number: CRBU-041



Item No	CRBU-041
Lamp Base	E27
Working Voltage	AC100-240V 50/60Hz
Power	11W
Color Rendering	≥75
Color Temperature	2700-8000K
Luminous Flux	896lm±8%
Material	Aluminum alloy+ PC
LED Lifespan	>40000hrs

7W Ceramic LED Bulb

Part number: CRBU-CE-06



P/N	CRBU-CE-06
Luminous Flux(lm)	650lm Cool White
Type	Non-Dimmable
Size	60x100mm
Input Voltage	85~264VAC
Power	7 Watt
LED Type	SMD5730 14PCS
Beam Angle	120°
Material	Glass +Ceramic
Color Rendering Index	Ra>80
Option Base	E14/E27
Operating Temperature	-20°C to 45°C
Lifespan	50,000Hours

6W LED Filament Globe Bulb E26 610-720lm

Part number: CRBU-360F-06



P/N	CRBU-360F-06
Light Source	Filament COB 6PCS
Luminous Flux	610~720lm
Type	Non-dimmable or Dimmable
Input Voltage	AC:85~264VAC
Color Rendering Index	Ra>80
Beam Angle	360°
Size	60*108mm
Color Temperature	2700~3000K / 4000~4500K / 6000~6500K
Lamp Base	E26/ E27/B22
Material	Aluminum+ Glass
Lamp Cover	Clear/ Milky White/ Frosted
Life Span	50,000 Hours
Operating Temperature	0°C to 45°C
Humidity	10~85% / 1.
Application	Hotel, Conference Room, Exhibition Center etc.

3W LED Candle Bulb E14 210-240lm


Part number: CRCD-360-01



P/N	CRCD-360-01
Light Source	SMD3014 0.2W 12PCS
Luminous Flux	210~240lm
Type	Non-dimmable or Dimmable
Input Voltage	AC:85~264V
Color Rendering Index	Ra>85
Beam Angle	360°
Size	37*120mm For E27
Color Temperature	2600~2850K / 2850~3000K / 4000~4500K / 6000~6500K
Lamp Base	E14/ E27
Life Span	50,000 Hours
Operating Temperature	0°C to 45°C
Humidity	10~85%

3W LED Candle Bulb E14 240lm

Part number: **CRBU-002**



Item No	CRBU-002
Lamp Base	E14
Working Voltage	AC100-240V 50/60Hz
Power	3W
Color Rendering	≥75
Color Temperature	2700-8000K
Luminous Flux	240lm±8%
Material	Aluminum alloy+ PC
LED Lifespan	>40000hrs

9W Ceramic LED Bulb

Part number: **CRBU-CE-07**



P/N	CRBU-CE-07
Luminous Flux(lm)	830lm Cool White
Type	Non-Dimmable
Size	70x127mm
Input Voltage	85~264VAC
Power	9 Watt
LED Type	SMD5730 18PCS
Beam Angle	120°
Material	Glass +Ceramic
Color Rendering Index	Ra>80
Option Base	E14/E27
Operating Temperature	-20°C to 45°C
Lifespan	50,000Hours

3W LED Flame Tip Bulb E14


Part number: CRCD-360-02



P/N	CRCD-360-02
Light Source	SMD3014 0.2W 12PCS
Luminous Flux	210~240lm
Type	Non-dimmable or Dimmable
Input Voltage	AC:85~264V
Color Rendering Index	Ra>85
Beam Angle	360°
Size	37*130mm For E27
Color Temperature	2600~2850K / 2850~3000K / 4000~4500K / 6000~6500K
Lamp Base	E14/ E27
Life Span	50,000 Hours
Operating Temperature	0°C to 45°C
Humidity	10~85%

5W LED Globe Bulb E27 425lm

Part number: CRBU-012



Item No	CRBU-012
Lamp Base	E27
Working Voltage	AC100-240V 50/60Hz
Power	5W
Color Rendering	≥75
Color Temperature	2700-8000K
Luminous Flux	425lm±8%
Material	Aluminum alloy+ PC
LED Lifespan	>40000hrs

5W WWCW Smart WiFi LED Bulb

Part number: CRBU-RF-08



P/N	CRBU-RF-08
Luminous Flux(lm)	0~370lm Cool White
CCT Adjustable	2700~6500K
Size	117x60mm
Input Voltage	AC85-264V
Power	5Watt
LED Type	SMD5630 0.5W
LED Quantity	16pcs
Max. Lumen	370lm
Material	Aluminum +PC
Option Base	E14
PF	>0.65
Lifespan	50,000Hours
Packing Information	One bulb per color box
Inner Box Size	65x65x130mm, Gross Weight: 120G, Net Weight: 100G

4W LED Candle Bulb E14

Part number: **CRCD-360-03**



P/N	CRCD-360-03
Light Source	SMD3014 0.2W 18PCS
Luminous Flux	310~360lm
Type	Non-dimmable or Dimmable
Input Voltage	AC:85~264V
Color Rendering Index	Ra>85
Beam Angle	360°
Size	37*120mm For E27
Color Temperature	2600~2850K / 2850~3000K / 4000~4500K / 6000~6500K
Lamp Base	E14/ E27
Life Span	50,000 Hours
Operating Temperature	0°C to 45°C
Humidity	10~85%

3W LED Globe Bulb E27

Part number: **CRBU-003**



Item No	CRBU-003
Lamp Base	E27/E26/B22
Working Voltage	AC100-240V 50/60Hz
Power	3W
Color Rendering	≥75
Color Temperature	2700-8000K
Luminous Flux	250lm±8%
Material	Aluminum alloy+ PC
LED Lifespan	>40000hrs

3W Ceramic LED Bulb 40x130mm

Part number: CRBU-CE-04



P/N	CRBU-CE-04
Luminous Flux(lm)	300lm Cool White
Type	Non-Dimmable
Size	40x130mm
Input Voltage	85~264VAC
Power	3 Watt
LED Type	SMD5730 5PCS
Beam Angle	120°
Material	Glass +Ceramic
Color Rendering Index	Ra>80
Option Base	E14
Operating Temperature	-20°C to 45°C
Lifespan	50,000Hours

4W RGBW Smart WiFi LED Bulb

Part number: CRBU-RF-07



P/N	CRBU-RF-07
Luminous Flux(lm)	0~220lm Cool White
Color Adjustable	16million colors changing
Size	74x50mm
Input Voltage	AC85-264V
Power	4Watt
LED Type	SMD5630 0.5Watt SMD5050 1.5W
LED Quantity	8pcs
Max. Lumen	220lm
Material	Aluminum +PC
Option Base	GU10
PF	>0.65
Lifespan	50,000Hours
Packing Information	One bulb per color box
Inner Box Size	65x65x78mm, Gross Weight: 100G, Net Weight:80G

4W LED Flame Tip Bulb E14

Part number: CRCD-360-04



P/N	CRCD-360-04
Light Source	SMD3014 0.2W 18PCS
Luminous Flux	310~360lm
Type	Non-dimmable or Dimmable
Input Voltage	AC:85~264V
Color Rendering Index	Ra>85
Beam Angle	360°
Size	37*130mm For E27
Color Temperature	2600~2850K / 2850~3000K / 4000~4500K / 6000~6500K
Lamp Base	E14/ E27
Life Span	50,000 Hours
Operating Temperature	0°C to 45°C
Humidity	10~85%

12W R95 WWCW Smart WiFi LED Bulb

Part number: CRBU-RF-12



P/N	CRBU-RF-12
Luminous Flux(lm)	0~1100lm Cool White
CCT Adjustable	2700~6500K
Size	132x95mm
Input Voltage	AC85-264V
Power	12Watt
LED Type	SMD5730 0.5W
LED Quantity	48pcs
Max. Lumen	1100lm
Material	Aluminum +PC
Option Base	E27,E26
PF	>0.65
Lifespan	50,000Hours

6W LED Candle Bulb E14

Part number: **CRCD-360-05**



P/N	CRCD-360-05
Light Source	SMD3014 0.2W 30PCS
Luminous Flux	510~560lm
Type	Non-dimmable or Dimmable
Input Voltage	AC:85~264V
Color Rendering Index	Ra>85
Beam Angle	360°
Size	■ / 37*124mm For E27
Color Temperature	2600~2850K / 2850~3000K / 4000~4500K / 6000~6500K
Lamp Base	E14/ E27
Life Span	50,000 Hours
Operating Temperature	0°C to 45°C
Humidity	10~85%

7W R63 WWCW Smart WiFi LED Bulb

Part number: **CRBU-RF-11**



P/N	CRBU-RF-11
Luminous Flux(lm)	0~650lm Cool White
CCT Adjustable	2700~6500K
Size	102x63mm
Input Voltage	AC85-264V
Power	7Watt
LED Type	SMD5730 0.5W
LED Quantity	28pcs
Max. Lumen	650lm
Material	Aluminum +PC
Option Base	E27,E26
PF	>0.65
Lifespan	50,000Hours

6W LED Flame Tip Bulb E14

Part number: **CRCD-360-06**



P/N	CRCD-360-06
Light Source	SMD3014 0.2W 30PCS
Luminous Flux	510~560lm
Type	Non-dimmable or Dimmable
Input Voltage	AC:85~264V
Color Rendering Index	Ra>85
Beam Angle	360°
Size	■ / 37*134mm For E27
Color Temperature	2600~2850K / 2850~3000K / 4000~4500K / 6000~6500K
Lamp Base	E14/ E27
Life Span	50,000 Hours
Operating Temperature	0°C to 45°C
Humidity	10~85%

7W WWCW Smart WiFi LED Bulb

Part number: **CRBU-RF-10**



P/N	CRBU-RF-10
Luminous Flux(lm)	0~650lm Cool White
CCT Adjustable	2700~6500K
Size	118x60mm
Input Voltage	AC85-264V
Power	7Watt
LED Type	SMD5730 0.5W
LED Quantity	28pcs
Max. Lumen	650lm
Material	Aluminum +PC
Option Base	E27,E26
PF	>0.65
Lifespan	50,000Hours

12W BR30 WWCW Smart WiFi LED Bulb

Part number: **CRBU-RF-13**



P/N	CRBU-RF-13
Luminous Flux(lm)	0~1100lm Cool White
CCT Adjustable	2700~6500K
Size	132x95mm
Input Voltage	AC85-264V
Power	12Watt
LED Type	SMD5730 0.5W
LED Quantity	48pcs
Max. Lumen	1100lm
Material	Aluminum +PC
Option Base	E27,E26
PF	>0.65
Lifespan	50,000Hours

2W RGBW Smart WiFi Glass LED Bulb

Part number: **CRBU-RF-15**



Power	2W
Color	RGB + warm white (2700k-3200k); RGB + cold white (6000k-6500k)
Lumen	120lm
Material	Acrylic
Weight	350g
Dimension	183 x 80mm
Capacity	3.7v/1400mA
Working Time	10 hours for RGB color, 5 hours for white color
Charge Time	3.5 hours
Charge Input	5v/500mA (package come with an USB cable)
Color Changeable	9 flashing modes
Brightness Adjustable	20 level
Wireless Control	by remote controller; by smart phone (need a Wifi controller)

LED Flood Lights

Outdoor and site lighting in mains-powered, sensor-triggered and battery-powered forms.

10W Rechargeable Emergency LED Flood Light

Part number: CRFL-RE-01



P/N	CRFL-RE-01
Light Source	High power integrated LED
Luminous Flux	800~900lm
Recharge Input Voltage	DC 12/24V
Charging Time	About 5 hours
Working Time	About 3 hours
Color Temperature	2700~3500K / 4000~4500K / 5500~6500K
Color Rendering Index	Ra>70
Beam Angle	120°
Life Span	50,000 Hours
Operating Temperature	-25°C to 50°C
Humidity	0~90%
Unit Dimension	145X160X240mm
Inner Box Size	178X178X171mm
Carton Size	360X370X560mm
Packing Quantity	12PCS/CTN
Warranty	2 Years or 500 Times Charging Cycle

10W PIR Motion Sensor LED Flood Light



Input Voltage	100-240V AC 50/60Hz
Power Factor	≥0.95
LED Power	30W
LED Luminous Flux	760-860lm
Average Illuminance	1m=289lux / 2M=72lux / 3M=32lu / Facula Area
CRI	>75
Beam Angle	100°,50 °
Color Temperature	Warm white WW 2800-3500K / Neutral white NW 4000-5000K / Pure white CW 5500-7000K
Operational Condition	Temperature:-30 / °C / -50
Humidity	10%-90%RH
Min	5sec Max:6min±2min
Height	2m-4.5m
Net Weight	0.65kg
Package	Color box,30pcs/ctn

10W LED Flood Light



Input Voltage	100-240V AC 50/60Hz /DC12-24V
Power Factor	≥0.95
LED Power	10W
LED Luminous Flux	760-860lm
Average lilluminance	1m=75lux / 2M=22lux / 3M=12ux / Facula Area
CRI	>75
Beam Angle	100°
Color Temperature	Warm white / WW 2800-3500K
Neutral White	NW 4000-5000K
Pure White	CW 5500-7000K
R/g/b/other Optional	Operational condition
Temperature	-30
Humidity	10%-90%RH
Net Weight	0.51kg
Package	Color box,30pcs/ctn
Mounting Height	Suitable for 8~10mheight
Certificate	.

20W Rechargeable Emergency LED Flood Light

Part number: CRFL-RE-02



P/N	CRFL-RE-02
Light Source	High power integrated LED
Luminous Flux	1600~1800lm
Recharge Input Voltage	DC 12/24V
Charging Time	About 5 hours
Working Time	About 3 hours
Color Temperature	2700~3500K / 4000~4500K / 5500~6500K
Color Rendering Index	Ra>70
Beam Angle	120°
Life Span	50,000 Hours
Operating Temperature	-25°C to 50°C
Humidity	0~90%
Unit Dimension	215X185X285mm
Inner Box Size	211X201X240mm
Carton Size	450X415X500mm
Packing Quantity	8PCS/CTN
Warranty	2 Years or 500 Times Charging Cycle

20W PIR Motion Sensor LED Flood Light



Input Voltage	100-240V AC 50/60Hz
Power Factor	≥0.95
LED Power	20W
LED Luminous Flux	1700-1900lm
Average lilluminance	2m=110lux / 3M=50lux / 4M=30lux / Facula Area
CRI	>75
Beam Angle	100°,50 °
Color Temperature	Warm white WW 2800-3500K / Neutral white NW 4000-5000K / Pure white CW 5500-7000K
Operational Condition	Temperature:-30 / °C / ~50
Humidity	10%-90%RH
Min	5sec Max:6min±2min
Height	2m-4.5m
Net Weight	2.13kg
Package	Color box,6pcs/ctn

20W LED Flood Light



Input Voltage	100-240V AC 50/60Hz / DC12-24V
Power Factor	≥0.95
LED Power	20W
LED Luminous Flux	1800-1900lm
Average lilluminance	4m=40lux / 5M=20lux / 6M=18ux / Facula Area
CRI	>75
Beam Angle	100°
Color Temperature	Warm white WW 2800-3500K / Neutral white NW 4000-5000K / Pure white CW 5500-7000K
Operational Condition	Temperature:-30 / °C
Humidity	10%-90%RH
Net Weight	2.5kg
Package	Color box,6pcs/ctn
Mounting Height	Suitable for 8~10mheight
Certificate	•

10W Dimmable Rechargeable LED Flood Light

Part number: CRFL-RE-03



P/N	CRFL-RE-03
Light Source	High power integrated LED
Luminous Flux	800~900lm
Charging Time	About 5 hours
Working Time	About 3~12 hours
Color Temperature	2700~3500K / 4000~4500K / 5500~6500K
Color Rendering Index	Ra>70
Beam Angle	120°
Life Span	40,000 Hours
Operating Temperature	-25°C to 50°C
Humidity	0~90%
Unit Dimension	145X160X240mm
Inner Box Size	178X178X171mm
Carton Size	360X370X560mm
Packing Quantity	12PCS/CTN
Warranty	2 Years or 500 Times Charging Cycle

30W PIR Motion Sensor LED Flood Light



Input Voltage	100-240V AC 50/60Hz
Power Factor	≥0.95
LED Power	30W
LED Luminous Flux	2550-2850lm
Average lilluminance	2m=155lux / 3M=75lux / 4M=45lux / Facula Area
CRI	>75
Beam Angle	100°,50 °
Color Temperature	Warm white WW 2800-3500K / Neutral white NW 4000-5000K / Pure white CW 5500-7000K
Operational Condition	Temperature:-30 / °C / ~50
Humidity	10%-90%RH
Min	5sec Max:6min±2min
Height	2m-4.5m
Net Weight	2.14kg
Package	Color box,6pcs/ctn

30W LED Flood Light



Input Voltage	100-240V AC 50/60Hz / DC12-24V
Power Factor	≥0.95
LED Power	30W
LED Luminous Flux	2550-2700lm
Average Illuminance	4m=121lux / 5M=71lux / 6M=41.5lux / Facula Area
CRI	>75
Beam Angle	100°
Color Temperature	Warm white WW 2800-3500K / Neutral white NW 4000-5000K / Pure white CW 5500-7000K
Operational Condition	Temperature:-30 / °C
Humidity	10%-90%RH
Net Weight	2.5kg
Package	Color box,6pcs/ctn
Mounting Height	Suitable for 8~10mheight
Certificate	·

20W Dimmable Rechargeable LED Flood Light

Part number: CRFL-RE-04



P/N	CRFL-RE-04
Light Source	High power integrated LED
Luminous Flux	1600~1800lm
Charging Time	About 5hours
Working Time	About 3~12 hours
Color Temperature	2700~3500K / 4000~4500K / 5500~6500K
Color Rendering Index	Ra>70
Beam Angle	120°
Life Span	50,000 Hours
Operating Temperature	-25°C to 50°C
Humidity	0~90%
Unit Dimension	215X185X285mm
Inner Box Size	211X201X240mm
Carton Size	450X415X500mm
Packing Quantity	8PCS/CTN
Warranty	2 Years or 500 Times Charging Cycle

50W PIR Motion Sensor LED Flood Light



Input Voltage	100-240V AC 50/60Hz
Power Factor	≥0.95
LED Power	50W
LED Luminous Flux	4250-4750lm
Average lilluminance	4m=80lux / 6M=35lux / 8M=18lux / Facula Area
CRI	>75
Beam Angle	100°,50 °
Color Temperature	Warm white WW 2800-3500K / Neutral white NW 4000-5000K / Pure white CW 5500-7000K
Operational Condition	Temperature:-30 / °C / ~50
Humidity	10%-90%RH
Min	5sec Max:6min±2min
Height	2m-4.5m
Net Weight	2.98kg
Package	Color box,4pcs/ctn

50W LED Flood Light



Input Voltage	100-240V AC 50/60Hz /DC12-24V
Power Factor	≥0.95
LED Power	50W
LED Luminous Flux	4350-4500lm
Average lilluminance	4m=174ux / 5M=102lux / 8M=30lux / Facula Area
CRI	>75
Beam Angle	100°
Color Temperature	Warm white WW 2800-3500K / Neutral white NW 4000-5000K / Pure white CW 5500-7000K
Operational Condition	Temperature:-30 / °C
Humidity	10%-90%RH
Net Weight	4.5kg
Package	Color box,4pcs/ctn
Mounting Height	Suitable for 8~10mheight
Certificate	•

20W Dimmable 24-Hour Rechargeable LED Flood Light

Part number: CRFL-RE-05



P/N	CRFL-RE-05
Light Source	High power integrated LED
Luminous Flux	1600~1800lm
Charging Time	About 10hours
Working Time	About 8~24 hours
Color Temperature	2700~3500K / 4000~4500K / 5500~6500K
Color Rendering Index	Ra>70
Beam Angle	120°
Life Span	50,000 Hours
Operating Temperature	-25°C to 50°C
Humidity	0~90%
Unit Dimension	215X185X285mm
Inner Box Size	211X201X240mm
Carton Size	450X415X500mm
Packing Quantity	8PCS/CTN
Warranty	2 Years or 500 Times Charging Cycle

10W Rechargeable LED Flood Light With Replaceable Battery

Part number: CRFL-RE-06



P/N	CRFL-RE-06
Light Source	High power integrated LED
Luminous Flux	800~900lm
Recharge Input Voltage	DC 12/24V
Charging Time	About 5 hours (4.4Ah Battery) / About 6 hours (5.2Ah Battery)
Working Time	About 3 hours (4.4Ah Battery) / About 6 hours (5.2Ah Battery)
Color Temperature	2700~3500K / 4000~4500K / 5500~6500K
Color Rendering Index	Ra>70
Beam Angle	120°
Life Span	50,000 Hours
Operating Temperature	-25°C to 50°C
Humidity	0~90%
Unit Dimension	145X175X240mm
Inner Box Size	210X153X160mm
Carton Size	480X440X340mm
Packing Quantity	12PCS/CTN
Warranty	2 Years or 500 Times Charging Cycle

5W Rechargeable LED Flood Light With Replaceable Battery

Part number: CRFL-RE-07



P/N	CRFL-RE-07
Light Source	High power integrated LED
Luminous Flux	400~450lm
Recharge Input Voltage	DC 12/24V
Charging Time	About 5 hours (2.2Ah Battery) / About 6 hours (4.4Ah Battery)
Working Time	About 3 hours (2.2Ah Battery) / About 6 hours (4.4Ah Battery)
Color Temperature	2700~3500K / 4000~4500K / 5500~6500K
Color Rendering Index	Ra>70
Beam Angle	120°
Life Span	50,000 Hours
Operating Temperature	-25°C to 50°C
Humidity	0~90%
Unit Dimension	145X175X240mm
Inner Box Size	210X153X160mm
Carton Size	480X440X340mm
Packing Quantity	12PCS/CTN
Warranty	2 Years or 500 Times Charging Cycle

20W Portable Rechargeable LED Flood Light

Part number: **CRFL-RE-08**



P/N	CRFL-RE-08
Light Source	High power integrated LED
Luminous Flux	1600~1800lm
Recharge Input Voltage	DC 12/24V
Charging Time	About 5 Hours (8.8Ah Battery) / About 10 Hours (12Ah Battery)
Working Time	About 3 Hours (8.8Ah Battery) / About 8 Hours (12Ah Battery)
Color Temperature	2700~3500K / 4000~4500K / 5500~6500K
Color Rendering Index	Ra>70
Beam Angle	120°
Life Span	40,000 Hours
Operating Temperature	-25°C to 50°C
Humidity	0~90%
Unit Dimension	215X185X285mm
Inner Box Size	211X201X240mm
Carton Size	450X415X500mm
Packing Quantity	8PCS/CTN
Warranty	2 Years or 500 Times Charging Cycle

20W RGB Rechargeable LED Flood Light

Part number: CRFL-RE-09



P/N	CRFL-RE-09
Light Source	High power integrated LED
Luminous Flux	1600~1800lm
Recharge Input Voltage	DC 12/24V
Charging Time	About 5 Hours
Working Time	About 3 Hours
Color Temperature	2700~3500K / 4000~4500K / 5500~6500K
Color Rendering Index	Ra>70
Beam Angle	120°
Life Span	50,000 Hours
Operating Temperature	-25°C to 50°C
Humidity	0~90%
Unit Dimension	215X185X285mm
Inner Box Size	211X201X240mm
Carton Size	450X415X500mm
Packing Quantity	8PCS/CTN
Warranty	2 Years or 500 Times Charging Cycle

10W RGB Rechargeable LED Flood Light

Part number: CRFL-RE-10



P/N	CRFL-RE-10
Light Source	High power integrated LED
Luminous Flux	800~900lm
Recharge Input Voltage	DC 12/24V
Charging Time	About 5 hours
Working Time	About 3 hours
Color Temperature	2700~3500K / 4000~4500K / 5500~6500K
Color Rendering Index	Ra>70
Beam Angle	120°
Life Span	50,000 Hours
Operating Temperature	-25°C to 50°C
Humidity	0~90%
Unit Dimension	145X175X240mm
Inner Box Size	210X153X160mm
Carton Size	480X440X340mm
Packing Quantity	12PCS/CTN
Warranty	2 Years or 500 Times Charging Cycle

10W PIR Rechargeable LED Flood Light

Part number: CRFL-RE-11



P/N	CRFL-RE-11
Light Source	High power integrated LED
Luminous Flux	800~900lm
Working Mode	PIR
Recharge Input Voltage	DC 12/24V
Charging Time	About 5 hours
Working Time	About 3 hours
Color Temperature	2700~3500K / 4000~4500K / 5500~6500K
Color Rendering Index	Ra>70
Beam Angle	120°
Life Span	50,000 Hours
Operating Temperature	-25°C to 50°C
Humidity	0~90%
Unit Dimension	145X175X240mm
Inner Box Size	210X153X160mm
Carton Size	480X440X340mm
Packing Quantity	12PCS/CTN
Warranty	2 Years or 500 Times Charging Cycle

20W PIR Rechargeable LED Flood Light

Part number: CRFL-RE-12



P/N	CRFL-RE-12
Light Source	High power integrated LED
Luminous Flux	1600~1800lm
Working Mode	PIR
Recharge Input Voltage	DC 12/24V
Charging Time	About 5 Hours
Working Time	About 3 Hours
Color Temperature	2700~3500K / 4000~4500K / 5500~6500K
Color Rendering Index	Ra>70
Beam Angle	120°
Life Span	50,000 Hours
Operating Temperature	-25°C to 50°C
Humidity	0~90%
Unit Dimension	215X185X285mm
Inner Box Size	211X201X240mm
Carton Size	450X415X500mm
Packing Quantity	8PCS/CTN
Warranty	2 Years or 500 Times Charging Cycle

LED Panel Lights

Ceiling panels for offices, shops and public interiors in fixed white, tunable white and RGB.

Round LED Panel Light Series 6W To 22W


Part number: **CRPL-DH-XX**



P/N	CRPL-DH-XX
CRI	>85
CCT	CW:5500-6500K NW:3900-4500K WW:2700-3200K

RGB LED Panel Light 295x295mm


Part number: **CRPL-RGB-01**



P/N	CRPL-RGB-01
Size	295 x 295 x 12mm
Working Voltage	24Vdc
Power	18Watt
LED Type	SMD5050 48PCS
Material	Aluminum
Beam Angle	120°
CRI	>85
Control Frequency	2.4GHZ Compatible Wifi
Working Temperature	-20~40 °C
Lifespan	50,000Hours

CCT Adjustable LED Panel Light 295x295mm

Part number: **CRPL-CCT-01**



P/N	CRPL-CCT-01
Luminous Flux(lm)	0~1200lm Cool White
Color Temperature Adjustable	2700K~6500K
Size	295 x 295 x 12mm
Working Voltage	24Vdc
Power	18Watt
LED Type	SMD3014 336PCS
Material	Aluminum
CRI	>85
Beam Angle	120°
Control Frequency	2.4GHZ Compatible Wifi
Working Temperature	-
Lifespan	50,000Hours

Square LED Panel Light Series 6W To 18W

Part number: CRPL-DH-XX



P/N	CRPL-DH-XX
CRI	>85
CCT	CW:5500-6500K NW:3900-4500K WW:2700-3200K

598x598mm LED Panel Light 38W

Part number: CRTB-015



Item No	CRTB-015
Input	AC100-240V, or AC220V, AC110V
Size	598x598x13mm
Frame Material	AL6063 aluminium material
LED Type	SMD 3528
Lumen	2000LM
CRI (color Rendering Index)	74-78 Ra
Heat Dissipation	two sides and back plate
Color	white/blue/red/orange/green/RGB
Installation	recessed, mounted, suspended
Power Consumption	38w

Super Brightness Square LED Panel Light Series

Part number: CRPL-PS-XX



P/N	CRPL-PS-XX
CRI	>85
CCT	CW:5500-6500K NW:3900-4500K WW:2700-3200K

RGB LED Panel Light 295x595mm

Part number: CRPL-RGB-02



P/N	CRPL-RGB-02
Size	295*595*12mm
Working Voltage	24Vdc
Power	40Watt
LED Type	SMD5050 120PCS
Material	Aluminum
Beam Angle	120°
CRI	>85
Control Frequency	2.4GHZ Compatible Wifi
Working Temperature	-20~40 °C
Lifespan	50,000Hours

CCT Adjustable LED Panel Light 295x595mm

Part number: CRPL-CCT-02



P/N	CRPL-CCT-02
Color Temperature Adjustable	2700K~6500K
Size	295*595*12mm
Working Voltage	24Vdc
Power	40Watt
LED Type	SMD3014 720PCS
Material	Aluminum
CRI	>85
Beam Angle	120°
Control Frequency	2.4GHZ Compatible Wifi
Working Temperature	-20~40 °C
Lifespan	50,000Hours

Round LED Panel Light 180mm 550lm


Part number: CRPN-002



Item No	CRPN-002
Input	AC100-240V, or AC220V, AC110V
Size	Φ180x19mm
Frame Material	AL6063 aluminium material
LED Type	SMD 3528
Lumen	550LM
CRI (color Rendering Index)	74-78 Ra
Heat Dissipation	two sides and back plate
Power Consumption	10w

RGB LED Panel Light 595x595mm


Part number: CRPL-RGB-03



P/N	CRPL-RGB-03
Size	595*595*12mm
Working Voltage	24Vdc
Power	40Watt
LED Type	SMD5050 120PCS
Material	Aluminum
Beam Angle	120°
CRI	>85
Control Frequency	2.4GHZ Compatible Wifi
Working Temperature	-20~40 °C
Lifespan	50,000Hours

CCT Adjustable LED Panel Light 595x595mm

Part number: CRPL-CCT-03



P/N	CRPL-CCT-03
Color Temperature Adjustable	2700K~6500K
Size	595*595*12mm
Working Voltage	24Vdc
Power	40Watt
LED Type	SMD3014 720PCS
Material	Aluminum
CRI	>85
Beam Angle	120°
Control Frequency	2.4GHZ Compatible Wifi
Working Temperature	-20~40 °C
Lifespan	50,000Hours

180x180mm Square LED Panel Light 550lm

Part number: CRPN-003



Item No	CRPN-003
Input	AC100-240V, or AC220V, AC110V
Size	180x180x19mm
Frame Material	AL6063 aluminium material
LED Type	SMD 3528
Lumen	550LM
CRI (color Rendering Index)	74-78 Ra
Heat Dissipation	two sides and back plate
Power Consumption	10w

RGB LED Panel Light 295x1195mm

Part number: CRPL-RGB-04



P/N	CRPL-RGB-04
Size	295*1195*12mm
Working Voltage	24Vdc
Power	40Watt
LED Type	SMD5050 120PCS
Material	Aluminum
Beam Angle	120°
CRI	>85
Control Frequency	2.4GHZ Compatible Wifi
Working Temperature	-20~40 °C
Lifespan	50,000Hours

CCT Adjustable LED Panel Light 295x1195mm

Part number: CRPL-CCT-04



P/N	CRPL-CCT-04
Color Temperature Adjustable	2700K~6500K
Size	295*1195*12mm
Working Voltage	24Vdc
Power	40Watt
LED Type	SMD3014 818PCS
Material	Aluminum
CRI	>85
Beam Angle	120°
Control Frequency	2.4GHZ Compatible Wifi
Working Temperature	-20~40 °C
Lifespan	50,000Hours

CCT Adjustable LED Panel Light 595x1195mm

Part number: CRPL-CCT-05



P/N	CRPL-CCT-05
Color Temperature Adjustable	2700K~6500K
Size	595*1195*12mm
Working Voltage	24Vdc
Power	54Watt
LED Type	SMD3014 1120PCS
Material	Aluminum
CRI	>85
Beam Angle	120°
Control Frequency	2.4GHZ Compatible Wifi
Working Temperature	-20~40 °C
Lifespan	50,000Hours

LED Strip Lights

Flexible strip by the roll and retail-packed kits, in white and RGB, waterproof and dry.

Colour Box Packed RGB LED Strip Light Kit



LED Type	RGB
LED Chips	5050 / 3528
LED Quantity	30Pcs/M / 60Pcs/M
IR Controller	24KEY / 44KEY
PCB Size	5000 x 10mm / 5000 x 8mm
Power	36W/Roll / 72W/Roll
Voltage	12Vdc
Beam Angle	120°

SMD3528 USB LED Strip Light Kit



Tips	0.5m, 1m, and 2m
Voltage	DC 5V (USB Power Supply)
Waterproof	NON-Waterproof
LED Type	SMD 3528
Strip Length	50cm,1m,2m,3m,4m,5m
Light Color	White / Warm white
Beam Angle	120 degrees
Storage Temp	-40~80 Celsius
Operating Temp	-25~60 Celsius
Package	1X USB LED strip light

Colour Box Packed White LED Strip Light Kit



LED Type	White
LED Chips	5050 / 3528
LED Quantity	30Pcs/M / 60Pcs/M / 120Pcs/M
IR Controller	14KEY
PCB Size	5000*10mm / 5000*8mm
Power	36W/Roll / 72W/Roll / 24W/Roll / 48W/Roll
Voltage	12Vdc
Beam Angle	120°

Portable Waterproof Camping LED Strip Light 1.5m



Voltage	DC5V
Power Consumption	3.5W
Color Temperature	Cool White,Warm White
LED Bulbs	45 x SMD3528
Lumens	300 LM
Waterproof	IP67
Package Includes	Outdoor Waterproof LED Strip x 1

Blister Packed RGB LED Strip Light Kit



LED Type	RGB
LED Chips	5050 / 3528
LED Quantity	30Pcs/M / 60Pcs/M
IR Controller	24KEY / 44KEY
PCB Size	5000x10mm / 5000x8mm
Power	36W/Roll / 72W/Roll
Voltage	12Vdc
Beam Angle	120°

Blister Packed White LED Strip Light Kit



LED Type	White
LED Chips	5050 / 3528
LED Quantity	30Pcs/M / 60Pcs/M / 120Pcs/M
IR Controller	14KEY
PCB Size	5000*10mm / 5000*8mm
Power	36W/Roll / 72W/Roll / 24W/Roll / 48W/Roll
Voltage	12Vdc
Beam Angle	120°

Solar Powered LED Strip Light

	Solar led strip light	CRST-3028-20-10V	Warm white	8V / 20V	18401020 20,40x45 10000xRoll Under panel: 3.7V/1.25V Li-ion battery: 3.7V/500MAH Cable: 2meters Charge time: 6 hours for solar panel. 8hours for charge. Lighting time: 6 hours for constant lighting Mode: constant light, flash, flashing green	IP65
	Solar led strip light	CRST-3028-20-CV	Cold white	8V / 20V	18401020 20,40x45 10000xRoll Under panel: 3.7V/1.25V Li-ion battery: 3.7V/500MAH Cable: 2meters Charge time: 6 hours for solar panel. 8hours for charge. Lighting time: 6 hours for constant lighting Mode: constant light, flash, flashing green	IP65
	Solar led strip light	CRST-3028-16-ROB	RGB	8V / 20V	18401020 16,40x45 10000xRoll Under panel: 3.7V/1.25V Li-ion battery: 3.7V/500MAH Cable: 2meters Charge time: 6 hours for solar panel. 8hours for charge. Lighting time: 6 hours for constant lighting Mode: constant light, flash, flashing green	IP65

SMD5060 60 LEDs/m IP68 LED Strip Light

Part number: CRWS-101-60S



Item No	CRWS-101-60S
PCB Color	white or yellow board.
Beam Angle	120 degree.
Lift Span	50000 ~ 80000 hours.
IP68	Solid silicon waterproof (with silicon cover on the back and silicon gel filled from the top).
Available Color	White, Warm White, Red, Green, Blue, Yellow, RGB

SMD5060 60 LEDs/m IP67 LED Strip Light

Part number: CRDW-101-60S



Item No	CRDW-101-60S
PCB Color	white or yellow board.
Beam Angle	120 degree.
Lift Span	50000 ~ 80000 hours.
Available Color	White, Warm White, Red, Green, Blue, Yellow, RGB

SMD5060 30 LEDs/m IP68 LED Strip Light

Part number: CRWS-101-30S



Item No	CRWS-101-30S
PCB Color	white or yellow board.
Beam Angle	120 degree.
Lift Span	50000 ~ 80000 hours.
Available Color	White, Warm White, Red, Green, Blue, Yellow, RGB

SMD5060 30 LEDs/m IP67 LED Strip Light

Part number: CRDW-101-30S



Item No	CRDW-101-30S
PCB Color	white or yellow board.
Beam Angle	120 degree.
Lift Span	50000 ~ 80000 hours.
Available Color	White, Warm White, Red, Green, Blue, Yellow, RGB

LED Downlights

Recessed ceiling downlights, from fixed-output cans to app-controlled tunable white.

12W WWCW Smart WiFi LED Downlight

Part number: CRDL-WF-01



P/N	CRDL-WF-01
LED Power	12W
LED Quantity	5630 48PCS
Luminous Flux	1100lm Max
Color Temperature	2700~6500K Adjustable
Brightness	100lm~1100lm Adjustable
Color Rendering Index	Ra>85
Power Factor	>0.9
Material Of Case	Aluminum
Life Span	40,000 Hours
Operating Temperature	-25°C to 50°C
Humidity	0~90%
Telecontrol Distance	20-30meters
Radio Frequency	2.4GHz
Hole Size	125~140mm
Unit Dimension	145x78mm
Inner Box Size	190x190x120mm
Packing Quantity	48PCS/CTN
Warranty	2 Years

1W Recessed LED Downlight

Part number: CRDL-1W; CRDL-3W



Item No	CRDL-1W; CRDL-3W
Input Voltage	12VAC/DC; 100-240VAC 50-60Hz
Output Current	350-700mA
Light Source	LED
Power	1x1W/1x3W
Color	WW/CW/Y/R/B/G/RGB
Beam Angle	30°, 45°
Operation Temperature	-20°-+50°
Fixture Material	Aluminium
Life Span	50000Hours
Surface Color	Silver/Brass/Shining White/Matt White

6W WWCW Smart WiFi LED Downlight

Part number: CRDL-WF-02



P/N	CRDL-WF-02
LED Power	6W
LED Quantity	5630 24PCS
Luminous Flux	560lm Max
Color Temperature	2700~6500K Adjustable
Brightness	60lm~560lm Adjustable
Color Rendering Index	Ra>85
Power Factor	>0.9
Material Of Case	Aluminum
Life Span	40,000 Hours
Operating Temperature	-25°C to 50°C
Humidity	0~90%
Telecontrol Distance	20-30meters
Radio Frequency	2.4GHz
Hole Size	78~95mm
Unit Dimension	100X65mm
Inner Box Size	140X140X110mm
Packing Quantity	60PCS/CTN
Warranty	2 Years

3W Recessed LED Downlight

Part number: CRDL-3W; CRDL-9W



Item No	CRDL-3W; CRDL-9W
Input Voltage	12VAC/DC 100-240VAC 50-60Hz
Output Current	350-700mA
Light Source	LED
Power	3x1W/3x3W
Color	WW/CW/Y/R/B/G/RGB
Beam Angle	8° 15° 30° 45° 60°
Operation Temperature	-20°~+50°
Fixture Material	Aluminium
Life Span	50000Hours
Surface Color	Silver/Brass/Shining White/Matt White

12W RGBW Smart WiFi LED Downlight

Part number: CRDL-WF-03



P/N	CRDL-WF-03
LED Power	12W
LED Quantity	5630 48PCS
Luminous Flux	1100lm Max
Working Mode	RGBW
Color Adjustable	16million colors changing
Brightness	100lm~1100lm Adjustable
Color Rendering Index	Ra>85
Power Factor	>0.9
Material Of Case	Aluminum
Life Span	40,000 Hours
Operating Temperature	-25°C to 50°C
Humidity	0~90%
Telecontrol Distance	20-30meters
Radio Frequency	2.4GHz
Hole Size	125~140mm
Unit Dimension	145X78mm
Inner Box Size	190X190X120mm
Packing Quantity	48PCS/CTN
Warranty	2 Years

5W Recessed LED Downlight

Part number: **CRDL-5w; CRDL-15W**



Item No	CRDL-5w; CRDL-15W
Input Voltage	24VAC/DC 100-240VAC 50-60Hz
Output Current	350-700mA
Light Source	LED
Power	5x1W/5x3W
Color	WW/CW/Y/R/B/G
Beam Angle	8° 15° 30° 45° 60°
Operation Temperature	-20°-+50°
Fixture Material	Aluminium
Life Span	50000Hours
Surface Color	Silver/Brass/Shining White/Matt White

6W Recessed LED Downlight

Part number: **CRDL-6W; CRDL-18W**



Item No	CRDL-6W; CRDL-18W
Input Voltage	24VAC/DC 100-240VAC 50-60Hz
Output Current	350-700mA
Light Source	LED
Power	6x1W/6x3W
Color	WW/CW/Y/R/B/G/RGB
Beam Angle	8° 15° 30° 45° 60°
Operation Temperature	-20°-+50°
Fixture Material	Aluminium
Life Span	50000Hours
Surface Color	Silver/Brass/Shining White/Matt White

7W Recessed LED Downlight

Part number: CRDL-7W; CRDL-21W



Item No	CRDL-7W; CRDL-21W
Input Voltage	100-240VAC 50-60Hz
Output Current	350-700mA
Light Source	LED
Power	7x1W/7x3W
Color	WW/CW/Y/R/B/G
Beam Angle	8° 15° 30° 45° 60°
Operation Temperature	-20°-+50°
Fixture Material	Aluminium
Life Span	50000Hours
Surface Color	Silver/Brass/Shining White/Matt White

8W Recessed LED Downlight

Part number: CRDL-8W; CRDL-24W




Item No	CRDL-8W; CRDL-24W
Input Voltage	100-240VAC 50-60Hz
Output Current	350-700mA
Light Source	LED
Power	8x1W/8x3W
Color	WW/CW/Y/R/B/G
Beam Angle	8° 15° 30° 45° 60°
Operation Temperature	-20°-+50°
Fixture Material	Aluminium
Life Span	50000Hours
Surface Color	Silver/Brass/Shining White/Matt White

LED Tube Lights

T5 and T8 retrofit tubes in the four standard lengths, for fluorescent replacement.

600mm T5 LED Tube Light


Part number: **CRTB-506**



Item No	CRTB-506
Input	AC85-265V
Length	600mm
LED Diodes Location In Tube	1 rows
Cover	Aluminum cover
LED Current	57.5 mA
Power Factor	0.9
CRI (color Rendering Index)	74-90 Ra
Power Consumption	7w for 600mm

600mm T8 LED Tube Light

Part number: **CRTB-006**



Item No	CRTB-006
Input	AC100-240V, or AC220V, AC110V
Length	600mm
Cover	Aluminum cover
LED Current	15-18mA
Power Factor	0.85~0.95
CRI (color Rendering Index)	74-90 Ra
Power Consumption	8w for 600mm

900mm T5 LED Tube Light


Part number: **CRTB-509**



Item No	CRTB-509
Input	AC85-265V
Length	900mm
Cover	Aluminum cover
LED Current	57.5 mA
Power Factor	0.9
CRI (color Rendering Index)	74-90 Ra
Power Consumption	10w for 900mm

1200mm T8 LED Tube Light

Part number: **CRTB-012**



Item No	CRTB-012
Input	AC100-240V, or AC220V, AC110V
Length	1200mm
LED Diodes Location In Tube	2 rows
Cover	Aluminum cover
LED Current	15-18mA
Power Factor	0.85~0.95
CRI (color Rendering Index)	74-90 Ra
Power Consumption	16w for 1200mm

1200mm T5 LED Tube Light

Part number: **CRTB-512**



Item No	CRTB-512
Input	AC85-265V
Length	1200mm
Cover	Aluminum cover
LED Current	57.5 mA
Power Factor	0.9
CRI (color Rendering Index)	74-90 Ra
Power Consumption	14w for 1200mm

1500mm T8 LED Tube Light

Part number: **CRTB-015**



Item No	CRTB-015
Input	AC100-240V, or AC220V, AC110V
Length	1500mm
Cover	Aluminum cover
LED Current	15-18mA
Power Factor	0.85~0.95
CRI (color Rendering Index)	74-90 Ra
Power Consumption	18w for 1500mm

1500mm T5 LED Tube Light

Part number: **CRTB-515**



Item No	CRTB-515
Input	AC85-265V
Length	1500mm
Cover	Aluminum cover
LED Current	57.5 mA
Power Factor	0.9
CRI (color Rendering Index)	74-90 Ra
Power Consumption	18w for 1500mm

LED Controllers And Remotes

The RF, WiFi and 433MHz control layer that drives our colour and tunable white products.

WiFi LED Controller For Strip Lights

Part number: **CRCT-WF-01**

Mi·Light®



P/N	CRCT-WF-01
Input	DC5V, 500mA
Telecontrol Distance	20-30meters
Dimension	90mmx65mmx12mm
Inner Color Box	L110mm x W84mm x H32mm

4-Zone RGBW RF LED Remote Control

Part number: **CRRC-RF-02**

Mi·Light®




P/N	CRRC-RF-02
Power Supply	AAA batteryx2pcs
Cover Material	ABS
Dimension	L109xW53xH22mm
Receiving Range	30meters
Power Consumption	5uA
Transmitting Power	6DB
Operation Frequency	2.4GHZ
Working Temperature	0~45 degrees

WWCW RF LED Controller

Part number: **CRCT-RF-06**

Mi·Light®



P/N	CRCT-RF-06
Power Supply	AAA batteryx2pcs
Cover Material	ABS
Working Voltage	DC12V-24V
Output Control	2circuits
Control Current	6A/circuit
Connection Method	common anode
Dimension	L85xW45xH22mm
Receiving Range	30meters

4-Zone WWCW RF LED Remote Control

Part number: **CRRC-RF-01**



P/N	CRRC-RF-01
Cover Material	ABS
Dimension	L109xW53xH22mm
Receiving Range	30meters
Power Consumption	5uA
Transmitting Power	6DB
Operation Frequency	2.4GHZ
Working Temperature	0~45 degrees

RGBW RF LED Controller

Part number: **CRCT-RF-02**



P/N	CRCT-RF-02
Power Supply	AAA batteryx2pcs
Cover Material	ABS
Technical Parameters(controller)	1. Working voltage: DC12V-24V
Output Control	4 circuit
Control Current	6A/circuit
Dimension	L85xW45xH22mm
Receiving Range	30meters
Working Temperature	-20~60 degrees

RGB RF LED Controller


Part number: **CRCT-RF-05**



P/N	CRCT-RF-05
Power Supply	AAA batteryx2pcs
Cover Material	ABS
Working Voltage	DC12V-24V
Output Control	3circuits
Control Current	6A/circuit
Connection Method	common anode
Dimension	L85xW45xH22mm
Receiving Range	30meters

433MHz RF LED Dimmer Controller

Part number: **CRCT-RF-04**



P/N	CRCT-RF-04
Power Supply	AAA batteryx2pcs
Cover Material	ABS
Working Voltage	DC12V-24V
Output Control	2 circuits
Control Current	6A/circuit
Dimension	L85xW45xH22mm
Receiving Range	30meters

Solar LED Lamps

Self-powered garden and wall lamps with motion detection and a pest-repeller variant.

150 LED Solar Motion Sensor Wall Light



Solar Panel	6V, 3W
Battery	3.7V, 4000mAh 18650 Li-ion battery
Charging Time	6-8h
Waterproof	IP65
Cable Length	5m
Solar Panel Size	180*155*15mm
Light Size	178*138*110mm
Material	Polysilicon solar panel + Copper wire + Plastic
Light Source	150pcs 2835 LED
Light Color	Pure white/ Warm white
Package Included	1 x Solar Panel
Function Introduction	Switching mode: manual switch + light control sensor + microwave radar body sensing
Radar Body Sensing Function	1. Installation height 3-5 meters. In the open environment, the human sensing distance is 5-7 meters.
Prev	end Next

Waterproof Solar Garden Lamp



Li-ion Battery	3.7V/ 2000mAh
Material	ABS
Lamp Colors	White
LED	48pcs SMD LED
Lumens	960LM
Lighting Time	≥ 5 hours(it is different from the operation modes)
Charging Time	≥ 8 hours
Lighting Mode	lights off during the day, lights automatically turn on at night
Outdoor Solar Lamp Advantage	1. Higher efficiency and lower consumption
Function	Day/Night Sensor
Package List	1 * Outdoor spotlight with solar panel

Solar Rodent Repeller Garden Lamp



Battery	NI-MH 1.2V 300mAh
Charging Time	8h
Working Time	120hr
Buzzer Frequency	400Hz +/- 50Hz
Protection Range	400■
Interval Time	30s
Repelling Animal	Rodent
Water Resistance	IP55
Material	ABS
Solar Panel Size	6.5 * 5cm / 2.6 * 2in (L * W)
Item Size	9.3 * 8 * 38cm / 3.7 * 3.1 * 15in (L * W * H)
Single Repeller Weight	131g / 4.6oz
Package Size	42.5 * 10 * 8.5cm / 16.7 * 3.9 * 3.3in (L * W * H)
Package Weight	328g / 11.6oz

LED Flashlights And Bike Lights

Portable task and inspection lighting, including a 365nm UV torch and a rechargeable bike light.

Mini 365nm UV LED Flashlight



Life	100,000 hours
Lamp Beads Brightness	3W
Switch Design	high-quality rubber switch
Charging Method	USB charging
Battery	Built-in high-capacity lithium battery
Material	Aircraft aluminum
Waterproof Performance	life waterproof
Size	16mm x 22mm x 120mm
Weight	70g
Package Included	1 x UV Lamp

1800lm Waterproof Rechargeable LED Bike Light



Lumen	1800LM
-------	--------

LED Grow Lights

Adjustable multi-head grow lighting for propagation, indoor growing and plant display.

Three Head LED Grow Light With Timer



Input Voltage	AC100-240V
Working Environment	-20 degree - 50 degree
Working Current	300MA
Service Life	50,000 hours
Operating Frequency	50/60 Hz
Light Color	red / blue
Gross Weight	about 700g
Energy Efficient	1 kWh/1,000 hours
Healthy Light	the light does not contain ultraviolet and infrared,no radiation
Green	The light does not contain mercury and lead and other harmful elements, which is conducive to recycling and use
Eye Protection	DC drive, no flicker
Polished Aluminum Shell	fin design keeps the unit cool and features high luminous efficiency; It is easy for light to run for a long time under this environment.
Wide Applications	indoor garden, potted plants, planting, farming, farmland, spray plants, greenhouse plants, pipe planting, flowering and so on.
Packing List	1*Led Grow Light

LED Desk Lamps

Touch-controlled dimmable desk lighting for study, work and bedside use.

Touch Control Dimmable LED Desk Lamp

Part number: CRDEL-03



P/N	CRDEL-03
Luminous Flux(lm)	100lm/W
Material	ABS+PC
Color	White and Black
Voltage	AC100-240V, DC12V, 1500mA
LED	27pcs
Power	11~14W
Color Temp	2500~7000K
CRI	Ra>90
Working Temperature	-20 - 40°C
Working Lifetime	40000 Hours
Function	4 mode, 5 steps brightness , 60mins timer
Color Temperature	5 Steps Brightness / 1 / 2 / 3 / 4 / 5
Reading	4300-5300K
Packing Information	One table lamp per color box
Product Size	L18xW17xH46cm
Inner Box Size	L45.8xW19.2xH8.2cm
Packing Size	49.5x40x43.5(cm), 8PCS/CTN, N.W:15.88KG; G.W:17KG