

Lifting Eye Bolts Eye Nuts and Wood Screw Eye Hooks

Eye bolts and eye nuts create a threaded lifting or anchoring point on a machine, a mould or a structure. Screw eyes and hook screws do the same job in timber. Honke covers both in stainless steel and carbon steel.

- 6 items in this range
- DIN 580 lifting eye bolts and DIN 582 eye nuts in the M6 to M24 range
- Stainless steel and carbon steel on the same part codes
- Open and closed wood hook screws plus lag eye screws with a captive ring
- Polished, hot dip galvanised and zinc plated finishes

Contact

WhatsApp +86 181 4895 2022 Email denny@honkehardware.com.cn

201, Building 2, Headquarters Center, Panyu Energy Saving Technology Park, No.555 Panyu Avenue North, Panyu District, Guangzhou, China

Plant: Longyan City, Fujian Province, China | 4,500 sq m floor area | 100 staff

Eye Bolts and Screw Eye Hooks Specifications



S306

LIFTING EYE BOLT DIN580

Lifting Eye Bolt DIN580

MATERIAL	Stainless steel, carbon steel
SIZE	M6-M24
FINISH	Polishing, Hot Dipped Galvanized, Zinc-plated etc
DESIGN	OEM & ODM



S3061

LIFTING EYE NUT

Lifting Eye Nut DIN582

MATERIAL	Stainless steel, carbon steel
SIZE	M6-M24
FINISH	Polishing, Hot Dipped Galvanized, Zinc-plated etc
DESIGN	OEM & ODM



S3191A

EYE BOLT WITH NUT

High Quality fasteners Stainless steel screw Eye Bolt with wing Nut

MATERIAL	Stainless steel, carbon steel
SIZE	Custom size on request
FINISH	Polishing, Zinc-plated etc
DESIGN	OEM & ODM



S7220

OPEN EYE WOOD HOOK SCREW

Customized Metal Self Tapping Open Eye Wood Hook Screw

MATERIAL	Stainless steel, steel Iron
SIZE	Custom size on request
FINISH	Polishing, Zinc-plated etc
DESIGN	OEM & ODM



S7228

WOOD EYE HOOK SCREW

Customized Metal Self Tapping Wood Hook Eye Screw Bolt Lag Screw

MATERIAL	Stainless steel, steel Iron
SIZE	Custom size on request
FINISH	Polishing, Zinc-plated etc
DESIGN	OEM & ODM



S7235

LAG EYE SCREW WITH RING

Hot Sale OEM Zinc-plated Stainless Steel Lag Eye Screw with Ring

MATERIAL	Stainless steel, steel Iron
SIZE	Custom size on request
FINISH	Polishing, Zinc-plated etc
DESIGN	OEM & ODM

Frequently Asked Questions

What is DIN 580 and DIN 582

DIN 580 is the standard forged lifting eye bolt with a machined shoulder and metric thread. DIN 582 is the matching lifting eye nut. Both are used to create a temporary lifting point on machinery and tooling.

Can an eye bolt be loaded sideways

A standard DIN 580 eye bolt is designed for vertical pull. Angled loading reduces capacity sharply and needs a swivel lifting point instead. Ask your lifting engineer before using one off axis.

What thread sizes do you make

M6 through M24 on the DIN 580 eye bolt and the DIN 582 eye nut. Other sizes are made to order.

What is the difference between a screw eye and a hook screw

A screw eye has a closed loop, a hook screw has an open one. The open hook lets a line be lifted off without unthreading, the closed eye cannot release by accident.

Do you supply eye bolts with a nut

Yes. The S306 body is listed as an eye bolt with nut and the S3061 is the matching eye nut.