

Stainless Steel Spring Snap Hooks

Spring snap hooks are the fastest way to make a rope, chain or webbing connection that a person can open and close by hand. Honke forms them in 304 and 316 stainless steel from 4 mm to 20 mm and finishes them by polishing.

- 5 items in this range
- 304 for general use and 316 for salt water so you can quote both grades from one supplier
- Polished finish that does not chip or flake like plating
- Eight standard diameters from 6 mm to 20 mm on the S2430 body alone
- Screw lock and eyelet variants for applications where the gate must stay shut

Contact

WhatsApp +86 181 4895 2022 Email denny@honkehardware.com.cn

201, Building 2, Headquarters Center, Panyu Energy Saving Technology Park, No.555 Panyu Avenue North, Panyu District, Guangzhou, China

Plant: Longyan City, Fujian Province, China | 4,500 sq m floor area | 100 staff

Spring Hooks Specifications



S2430

SPRING SNAP HOOK

304/316 Stainless Steel Spring Carabiner Snap Keychain Hook 6mm-20mm

MATERIAL	stainless steel 304/316
SIZE	6mm/8mm/10mm/12mm/14mm/16mm/18mm/20mm
FINISH	Polishing
DESIGN	OEM & ODM



S2450

SPRING HOOK

Stainless steel carabiner spring snap hook 4mm-14mm

MATERIAL	stainless steel, Steel Iron
SIZE	4mm-14mm
FINISH	Polishing, plating, etc
DESIGN	OEM & ODM



S2450N

SPRING HOOK

High Quality Stainless Steel Screw Lock Snap Hooks with Nut Carabiner 4mm-14mm

MATERIAL	stainless steel, Steel Iron
SIZE	4mm-14mm
FINISH	Polishing, plating, etc
DESIGN	OEM & ODM




S2450X

SPRING HOOK

High Quality Stainless Steel Spring Hook With Eyelet 4mm-14mm

MATERIAL	stainless steel, Steel Iron
SIZE	4mm-14mm
FINISH	Polishing, plating, etc
DESIGN	OEM & ODM

**S2470****SPRING SNAP HOOK**

Stainless steel spring hook clasps stainless steel oval egg snap hook 40mm/50mm/70mm/100mm

MATERIAL	stainless steel 304/316
SIZE	40mm/50mm/70mm/100mm
FINISH	Polishing
DESIGN	OEM & ODM

Frequently Asked Questions

What is the difference between 304 and 316 spring hooks

Both are austenitic stainless steels. 316 contains molybdenum, which makes it noticeably more resistant to chloride pitting, so it is the normal choice for sea water, coastal air and swimming pool areas. 304 is used for general indoor and inland outdoor work. Honke supplies both grades on the same part numbers.

Can you supply a spring hook with a locking gate

Yes. The S2450N carries a screw lock nut over the gate and the S2450X adds an eyelet so a lanyard or split ring can be attached. Both are listed in this category.

Are spring snap hooks load rated

The hooks in this range are connecting and holding hardware. Tell us the working load your market expects and we will confirm what we can supply and what documentation is possible for that item before you order.

What sizes do you keep

The S2430 runs 6, 8, 10, 12, 14, 16, 18 and 20 mm. The S2450 family runs 4 mm to 14 mm and the S2470 oval hook runs 40, 50, 70 and 100 mm overall length.

Can we get our own logo on the hook

Colour, marking and packaging are handled as OEM and ODM work. Send us the artwork and the part you want it applied to and we will come back on what the forming process allows.