

Wire Rope Clips and Rope Thimbles

A clip and a thimble together form the standard field made eye in a wire rope. The thimble protects the rope from crushing in the eye and the clips hold the tail. Honke makes both in stainless steel and carbon steel.

- 4 items in this range
- DIN 741 and JIS patterns from size 3 to size 12 so both markets are covered
- Light duty and standard thimbles in 3 mm to 12 mm
- Stainless steel for cable railing and marine work, carbon steel where price leads
- Polished, hot dip galvanised and zinc plated finishes

Contact

WhatsApp +86 181 4895 2022 Email denny@honkehardware.com.cn

201, Building 2, Headquarters Center, Panyu Energy Saving Technology Park, No.555 Panyu Avenue North, Panyu District, Guangzhou, China

Plant: Longyan City, Fujian Province, China | 4,500 sq m floor area | 100 staff

Wire Rope Clips and Thimbles Specifications



S234

ROPE THIMBLE

Stainless Steel Light Duty Wire Rope Thimble

MATERIAL	Stainless steel, carbon steel
SIZE	3mm-12mm
FINISH	Polishing, Zinc-plated etc
DESIGN	OEM & ODM



S2350

ROPE THIMBLE

High quality stainless steel wire rope clip and wire rope thimble and round thimble and wire rope clamp steel

MATERIAL	Stainless steel, carbon steel
SIZE	3mm-12mm
FINISH	Polishing, Zinc-plated etc
DESIGN	OEM & ODM



S260

WIRE ROPE CLIP JIS TYPE

Stainless Steel JIS Type Wire Rope Clip (Cable Clip)

MATERIAL	Stainless steel, carbon steel
SIZE	3#-12#
FINISH	Polishing, Hot Dipped Galvanized, Zinc-plated etc
DESIGN	OEM & ODM



S261

WIRE ROPE CLIP DIN741

Stainless Steel DIN741 Wire Rope Clip (Cable Clip)

MATERIAL	Stainless steel, carbon steel
SIZE	3#-12#
FINISH	Polishing, Hot Dipped Galvanized, Zinc-plated etc
DESIGN	OEM & ODM

Frequently Asked Questions

What is the difference between DIN 741 and JIS type clips

They are two national patterns for the same job. DIN 741 uses a forged saddle with a U bolt, the JIS type uses a different saddle profile and is common in Asian markets. Saddle sizes are not interchangeable, so pick one pattern per assembly.

How many clips does an eye need

The number depends on rope diameter and the standard your market follows. As a rule the saddle always sits on the live part of the rope and the U bolt on the dead tail. Check the rope maker instruction for the exact count and spacing.

Why fit a thimble

The thimble keeps the eye round so the rope is not crushed or bent tighter than its minimum radius. Without one the eye deforms and the rope loses strength at the loop.

What sizes do you supply

Clips run from size 3 to size 12 in both DIN 741 and JIS patterns. Thimbles run 3 mm to 12 mm.

Can I use stainless clips on galvanised rope

It is done, but the two metals can react in wet conditions. Where the assembly stays wet or salty, match the clip material to the rope.