



No	描述 Description	材质 Material
1	玻璃件 Glass Body	钢化玻璃 Toughened Glass
2	钢帽 Cap	铸铁, 热镀锌 Cast Iron, HDG
3	钢脚 Pin	锻钢, 热镀锌 Forged Steel, HDG
4	胶合剂 Binding Material	硅酸盐水泥 Aluminous Cement
5	垫片 Gasket	沥青油毡 Asphalt Felt
6	销紧销 Split Pin	不锈钢R销 Stainless Steel R Clip

- | | |
|---|------------|
| a) 地对地试验电压 Test Voltage RMS to Ground: | 10kV |
| b) 在1000 kHz最大值 Maximum RIV at 1000 kHz: | 50μV |
| c) 电晕熄灭电压 Corona extinction voltage, 脚pin/帽Cap: | 18/22kV |
| d) 工频电弧实验 Power frequency arc test: | 0.12s/20kA |

GLASS INSULATOR UNITS FOR A.C. SYSTEMS - DEFINITIONS, TEST METHODS AND ACCEPTANCE CRITERIA ACCORDING TO IEC 60383-1:2022

型号 Model	U70BP148D	类型 Type	双伞型 Double Shed	设计 Designed	Xiao Ke
颜色 Colour	浅绿色 Light Green	比例 Scale	1:1	核对 Checked	Chen Liang
重量 Weight	5.3 KGS	日期 Date	2024/03/25	批准 Approved	Nie Ke

江西华耀电气有限公司
Jiangxi Huayao Electric Co., Ltd.

交流盘形悬式玻璃绝缘子
AC Disc Suspension Glass Insulator