



Roller And Curtain Coating Machines

Roller coaters, curtain coaters, stain, putty and back coating machines.

Qingdao INCRI Machinery Co., Ltd has built flexible intelligent finishing lines since 1999. All machines are customised to the buyer's requirement, so the figures below are the published data for each model series and are confirmed against your panel size, coating system and line speed before production.

Address: Jinling Industrial Park, Chengyang District, Qingdao City, Shandong Province, China
Email: info@incrimachine.com | WhatsApp and mobile: +86 150 0542 7255

Coating Machine

Everything that puts liquid coating on a flat panel: roller coaters, curtain coaters, putty filling, staining and back coating.

Back Coating Machine For solid wood floor Back Coating Equipment

A back coating machine designed for painting the back of solid wood flooring. Correctly applied, the back seal blocks more than 80 percent of the water that would otherwise enter the board from below, so the floor does not deform. The standard build pairs a single roller coater with a double lamp UV dryer. Coating widths are 600, 1000 and 1300 mm.

Parameter	ICBQ600	ICBQ1000	ICBQ1300
Max.Coating Width	600mm	1000mm	1300mm
Processing Thickness	2-90mm	2-90mm	2-90mm
Feeding Speed Frequency Alternator Frequency Alternator Frequency Alternator Lamp Power 0,75kw Fan Power	5.6kw*2	11kw*2	1.1kw*2
Absorption Power (optional)	0.75kw	1.1kw	1.1kw
TTotal Power	24.6kw	24.6kw	24.6kw
Dimension(L x W x H) mm	1600*1200*1750	1785*2300*1640	2100*1950*1780mm
Net Weight	1700kg	1500kg	1900kg

Back Coating Machine For MDF UV Back Coating Equipment

A back coating machine designed for painting the back of solid wood flooring. Correctly applied, the back seal blocks more than 80 percent of the water that would otherwise enter the board from below, so the floor does not deform. The standard build pairs a single roller coater with a double lamp UV dryer. Coating widths are 600, 1000 and 1300 mm.

Parameter	ICBQ600	ICBQ1000	ICBQ1300
Max.Coating Width	600mm	1000mm	1300mm
Processing Thickness	2-90mm	2-90mm	2-90mm
Feeding Speed Frequency Alternator Frequency Alternator Frequency Alternator Lamp Power 0,75kw Fan Power	5.6kw*2	11kw*2	1.1kw*2

Parameter	ICBQ600	ICBQ1000	ICBQ1300
Absorption Power (optional)	0.75kw	1.1kw	1.1kw
TTotal Power	24.6kw	24.6kw	24.6kw
Dimension(L x W x H) mm	1600*1200*1750	1785*2300*1640	2100*1950*1780mm
Net Weight	1700kg	1500kg	1900kg

Carpentry Tools Back Coating Machine For Cabinet/Floor Wood precise back coating

A back coating machine designed for painting the back of solid wood flooring. Correctly applied, the back seal blocks more than 80 percent of the water that would otherwise enter the board from below, so the floor does not deform. The standard build pairs a single roller coater with a double lamp UV dryer. Coating widths are 600, 1000 and 1300 mm.

Parameter	ICBQ600	ICBQ1000	ICBQ1300
Max.Coating Width	600mm	1000mm	1300mm
Processing Thickness	2-90mm	2-90mm	2-90mm
Feeding Speed Frequency Alternator Frequency Alternator Frequency Alternator Lamp Power o,75kw Fan Power	5.6kw*2	11kw*2	1.1kw*2
Absorption Power (optional)	0.75kw	1.1kw	1.1kw
TTotal Power	24.6kw	24.6kw	24.6kw
Dimension(L x W x H) mm	1600*1200*1750	1785*2300*1640	2100*1950*1780mm
Net Weight	1700kg	1500kg	1900kg

Precise Stain Machine Furniture Wood Flooring woodworking stain machine 600mm

A precise stain machine for flat line furniture and solid wood flooring. Brush rollers push stain into the pore holes and grain of the wood surface rather than laying colour only on the top, so the grain reads clearly after coating. Coating widths are 600, 1000 and 1300 mm at a feed of 0-20 m per minute.

Parameter	ICZS600	ICZS1000	ICZS1300
Max.Coating Width	600mm	1000mm	1300mm
Processing Thickness	2-90mm	2-90mm	2-90mm
Feeding Speed	0-20m/min	0-20m/min	0-20m/min
Feeding Power	0.75kw	1.5kw	1.5kw
Brush Roller Power	0.75kw*2	1.5kw*2	1.5kw*2
Absorption Power (optional)	3kw	4kw	4kw
TTotal Power	3.75kw	8.2kw	8.2kw
Dimension(L x W x H) mm	1785*1920*1640	1785*2300*1640	1785*2600*1640
Net Weight	720kg	950kg	1150kg

Wood Flooring Precise Stain Machine Furniture Wood Flooring woodworking stain machine

A precise stain machine for flat line furniture and solid wood flooring. Brush rollers push stain into the pore holes and grain of the wood surface rather than laying colour only on the top, so the grain reads clearly after coating. Coating widths are 600, 1000 and 1300 mm at a feed of 0-20 m per minute.

Parameter	ICZS600	ICZS1000	ICZS1300
Max.Coating Width	600mm	1000mm	1300mm
Processing Thickness	2-90mm	2-90mm	2-90mm

Parameter	ICZS600	ICZS1000	ICZS1300
Feeding Speed	0-20m/min	0-20m/min	0-20m/min
Feeding Power	0.75kw	1.5kw	1.5kw
Brush Roller Power	0.75kw*2	1.5kw*2	1.5kw*2
Absorption Power (optional)	3kw	4kw	4kw
TTotal Power	3.75kw	8.2kw	8.2kw
Dimension(L x W x H) mm	1785*1920*1640	1785*2300*1640	1785*2600*1640
Net Weight	720kg	950kg	1150kg

Wood Flooring Precise Stain Machine Furniture Wood Flooring

A precise stain machine for flat line furniture and solid wood flooring. Brush rollers push stain into the pore holes and grain of the wood surface rather than laying colour only on the top, so the grain reads clearly after coating. Coating widths are 600, 1000 and 1300 mm at a feed of 0-20 m per minute.

Parameter	ICZS600	ICZS1000	ICZS1300
Max.Coating Width	600mm	1000mm	1300mm
Processing Thickness	2-90mm	2-90mm	2-90mm
Feeding Speed	0-20m/min	0-20m/min	0-20m/min
Feeding Power	0.75kw	1.5kw	1.5kw
Brush Roller Power	0.75kw*2	1.5kw*2	1.5kw*2
Absorption Power (optional)	3kw	4kw	4kw
TTotal Power	3.75kw	8.2kw	8.2kw
Dimension(L x W x H) mm	1785*1920*1640	1785*2300*1640	1785*2600*1640
Net Weight	720kg	950kg	1150kg

Wood Flooring Precise Stain Machine Furniture Wood Flooring Precise Stain Machine

A precise stain machine for flat line furniture and solid wood flooring. Brush rollers push stain into the pore holes and grain of the wood surface rather than laying colour only on the top, so the grain reads clearly after coating. Coating widths are 600, 1000 and 1300 mm at a feed of 0-20 m per minute.

Parameter	ICZS600	ICZS1000	ICZS1300
Max.Coating Width	600mm	1000mm	1300mm
Processing Thickness	2-90mm	2-90mm	2-90mm
Feeding Speed	0-20m/min	0-20m/min	0-20m/min
Feeding Power	0.75kw	1.5kw	1.5kw
Brush Roller Power	0.75kw*2	1.5kw*2	1.5kw*2
Absorption Power (optional)	3kw	4kw	4kw
TTotal Power	3.75kw	8.2kw	8.2kw
Dimension(L x W x H) mm	1785*1920*1640	1785*2300*1640	1785*2600*1640
Net Weight	720kg	950kg	1150kg

Automatic Curtain Coating Machine for Woodworking Painting

A curtain coater passes the panel through a falling sheet of paint, so nothing touches the surface and there are no roller marks to sand out. Film thickness can be taken down to 0.05 mm, feed runs up to 80 m per minute, and the circulation

system recycles the paint that does not land on the panel. Coating widths are 600, 1000 and 1300 mm.

Parameter	ICLM600	ICLM1000	ICLM1300
Valid Coating Width	600mm	1000mm	1300mm
Feeding Speed	0-80m/min	0-80m/min	0-80m/min
Working Thickness	2-60mm	2-60mm	2-60mm
Min.Length	300mm	300mm	300mm
Feeding Power	1.5kw	3.7kw	3.7kw
Heating Power	3kw*2	5kw*2	5kw*2
TTotal Power	7.5kw	13.7kw	13.7kw
Dimension(L x W x H)	3000*1400*1300mm	4120*1850*1400mm	4120*2100*1400mm
Net Weight	1500kg	1800kg	2300kg

Woodworking UV Painting Curtain Coating Machine

A curtain coater passes the panel through a falling sheet of paint, so nothing touches the surface and there are no roller marks to sand out. Film thickness can be taken down to 0.05 mm, feed runs up to 80 m per minute, and the circulation system recycles the paint that does not land on the panel. Coating widths are 600, 1000 and 1300 mm.

Parameter	ICLM600	ICLM1000	ICLM1300
Valid Coating Width	600mm	1000mm	1300mm
Feeding Speed	0-80m/min	0-80m/min	0-80m/min
Working Thickness	2-60mm	2-60mm	2-60mm
Min.Length	300mm	300mm	300mm
Feeding Power	1.5kw	3.7kw	3.7kw
Heating Power	3kw*2	5kw*2	5kw*2
TTotal Power	7.5kw	13.7kw	13.7kw
Dimension(L x W x H)	3000*1400*1300mm	4120*1850*1400mm	4120*2100*1400mm
Net Weight	1500kg	1800kg	2300kg

UV Curtain Coater Machine For High Glossy Effect Curtain Coating Machine

A curtain coater passes the panel through a falling sheet of paint, so nothing touches the surface and there are no roller marks to sand out. Film thickness can be taken down to 0.05 mm, feed runs up to 80 m per minute, and the circulation system recycles the paint that does not land on the panel. Coating widths are 600, 1000 and 1300 mm.

Parameter	ICLM600	ICLM1000	ICLM1300
Valid Coating Width	600mm	1000mm	1300mm
Feeding Speed	0-80m/min	0-80m/min	0-80m/min
Working Thickness	2-60mm	2-60mm	2-60mm
Min.Length	300mm	300mm	300mm
Feeding Power	1.5kw	3.7kw	3.7kw
Heating Power	3kw*2	5kw*2	5kw*2
TTotal Power	7.5kw	13.7kw	13.7kw
Dimension(L x W x H)	3000*1400*1300mm	4120*1850*1400mm	4120*2100*1400mm
Net Weight	1500kg	1800kg	2300kg

UV Varnish Curtain Coating Machine For Wood Curtain coater machine 1000mm

A curtain coater passes the panel through a falling sheet of paint, so nothing touches the surface and there are no roller marks to sand out. Film thickness can be taken down to 0.05 mm, feed runs up to 80 m per minute, and the circulation system recycles the paint that does not land on the panel. Coating widths are 600, 1000 and 1300 mm.

Parameter	ICLM600	ICLM1000	ICLM1300
Valid Coating Width	600mm	1000mm	1300mm
Feeding Speed	0-80m/min	0-80m/min	0-80m/min
Working Thickness	2-60mm	2-60mm	2-60mm
Min.Length	300mm	300mm	300mm
Feeding Power	1.5kw	3.7kw	3.7kw
Heating Power	3kw*2	5kw*2	5kw*2
TTTotal Power	7.5kw	13.7kw	13.7kw
Dimension(L x W x H)	3000*1400*1300mm	4120*1850*1400mm	4120*2100*1400mm
Net Weight	1500kg	1800kg	2300kg

High Gloss UV Curtain Coating Machine Curtain Coater Machine

A curtain coater passes the panel through a falling sheet of paint, so nothing touches the surface and there are no roller marks to sand out. Film thickness can be taken down to 0.05 mm, feed runs up to 80 m per minute, and the circulation system recycles the paint that does not land on the panel. Coating widths are 600, 1000 and 1300 mm.

Parameter	ICLM600	ICLM1000	ICLM1300
Valid Coating Width	600mm	1000mm	1300mm
Feeding Speed	0-80m/min	0-80m/min	0-80m/min
Working Thickness	2-60mm	2-60mm	2-60mm
Min.Length	300mm	300mm	300mm
Feeding Power	1.5kw	3.7kw	3.7kw
Heating Power	3kw*2	5kw*2	5kw*2
TTTotal Power	7.5kw	13.7kw	13.7kw
Dimension(L x W x H)	3000*1400*1300mm	4120*1850*1400mm	4120*2100*1400mm
Net Weight	1500kg	1800kg	2300kg

Wood Putty MachinePutty Patching Machine for Solid Wood heavy putty machine

A putty filling and coating machine for flat wood, plastic and metal surfaces. It replaces manual filling: the constant pressure structure keeps the film even on pieces that vary slightly in thickness, and an independent inverter and motor hold the applied weight between 10 and 30 g per square metre. Working widths are 600, 1000 and 1300 mm.

Parameter	ICDT600	ICDT1000	ICDT1300
Max.Coating Width	600mm	1000mm	1300mm
Processing Thickness	2-90mm	2-90mm	2-90mm
Feeding Speed	0-20m/min	0-20m/min	0-20m/min
Feeding Power	1.5kw	1.5kw	1.5kw
Coating Roller Power	1.5kw	1.5kw	1.5kw
Doctor Roller Power	0.55kw	0.55kw	0.55kw
Filling Roller Power	1.5kw	1.5kw	1.5kw

Parameter	ICDT600	ICDT1000	ICDT1300
Heater Power	2kw*1	2kw*1	2kw*1
TTotal Power	7.05kw	7.05kw	7.05kw
Dimension(L x W x H) mm	1450*1920*1640	1450*2315*1640	1450*2615*1640
Net Weight	1050kg	1250kg	1370kg

Putty Patching Machine for Solid Wood heavy putty machine UV paint

A putty filling and coating machine for flat wood, plastic and metal surfaces. It replaces manual filling: the constant pressure structure keeps the film even on pieces that vary slightly in thickness, and an independent inverter and motor hold the applied weight between 10 and 30 g per square metre. Working widths are 600, 1000 and 1300 mm.

Parameter	ICDT600	ICDT1000	ICDT1300
Max.Coating Width	600mm	1000mm	1300mm
Processing Thickness	2-90mm	2-90mm	2-90mm
Feeding Speed	0-20m/min	0-20m/min	0-20m/min
Feeding Power	1.5kw	1.5kw	1.5kw
Coating Roller Power	1.5kw	1.5kw	1.5kw
Doctor Roller Power	0.55kw	0.55kw	0.55kw
Filling Roller Power	1.5kw	1.5kw	1.5kw
Heater Power	2kw*1	2kw*1	2kw*1
TTotal Power	7.05kw	7.05kw	7.05kw
Dimension(L x W x H) mm	1450*1920*1640	1450*2315*1640	1450*2615*1640
Net Weight	1050kg	1250kg	1370kg

Automatic Flat Line Furniture Uv Putty Filler Machine Putty Machine

A putty filling and coating machine for flat wood, plastic and metal surfaces. It replaces manual filling: the constant pressure structure keeps the film even on pieces that vary slightly in thickness, and an independent inverter and motor hold the applied weight between 10 and 30 g per square metre. Working widths are 600, 1000 and 1300 mm.

Parameter	ICDT600	ICDT1000	ICDT1300
Max.Processing Width	600mm	1000mm	1300mm
Processing Thickness	2-90mm	2-90mm	2-90mm
Min. Processing Length	300mm	300mm	300mm
Feeding Speed	0-20m/min	0-20m/min	0-20m/min
Feeding Power	1.5kw	1.5kw	2.2kw
Coating Roller Power	1.5kw*2	1.5kw*2	1.5KW*2
Doctor Roller Power	0.55kw*2	0.55kw*2	0.55kw*2
Filling Roller Power	1.5kw	1.5kw	1.5kw
Heater Power	2kw*2	2kw*2	2kw*2
TTotal Power	11.1kw	11.1kw	11.8kw
Dimension(L x W x H)mm	2145*1920*1640	2145*2300*1640	2145*2600*1640
Net Weight	1400kg	1750kg	2000kg

Floor Putty Filling Machine Putty Machine

A putty filling and coating machine for flat wood, plastic and metal surfaces. It replaces manual filling: the constant pressure structure keeps the film even on pieces that vary slightly in thickness, and an independent inverter and motor hold the applied weight between 10 and 30 g per square metre. Working widths are 600, 1000 and 1300 mm.

Parameter	ICDT600	ICDT1000	ICDT1300
Max.Processing Width	600mm	1000mm	1300mm
Processing Thickness	2-90mm	2-90mm	2-90mm
Min. Processing Length	300mm	300mm	300mm
Feeding Speed	0-20m/min	0-20m/min	0-20m/min
Feeding Power	1.5kw	1.5kw	2.2kw
Coating Roller Power	1.5kw*2	1.5kw*2	1.5KW*2
Doctor Roller Power	0.55kw*2	0.55kw*2	0.55kw*2
Filling Roller Power	1.5kw	1.5kw	1.5kw
Heater Power	2kw*2	2kw*2	2kw*2
TTotal Power	11.1kw	11.1kw	11.8kw
Dimension(L x W x H)mm	2145*1920*1640	2145*2300*1640	2145*2600*1640
Net Weight	1400kg	1750kg	2000kg

Uv Putty Filler Machine Putty Machine

A putty filling and coating machine for flat wood, plastic and metal surfaces. It replaces manual filling: the constant pressure structure keeps the film even on pieces that vary slightly in thickness, and an independent inverter and motor hold the applied weight between 10 and 30 g per square metre. Working widths are 600, 1000 and 1300 mm.

Parameter	ICDT600	ICDT1000	ICDT1300
Max.Processing Width	600mm	1000mm	1300mm
Processing Thickness	2-90mm	2-90mm	2-90mm
Min. Processing Length	300mm	300mm	300mm
Feeding Speed	0-20m/min	0-20m/min	0-20m/min
Feeding Power	1.5kw	1.5kw	2.2kw
Coating Roller Power	1.5kw*2	1.5kw*2	1.5KW*2
Doctor Roller Power	0.55kw*2	0.55kw*2	0.55kw*2
Filling Roller Power	1.5kw	1.5kw	1.5kw
Heater Power	2kw*2	2kw*2	2kw*2
TTotal Power	11.1kw	11.1kw	11.8kw
Dimension(L x W x H)mm	2145*1920*1640	2145*2300*1640	2145*2600*1640
Net Weight	1400kg	1750kg	2000kg

3 head roller coater machine for UV panel woodworking panel Roller

A three head roller coater for board type furniture, flooring, flush doors, ceramic and handicraft surfaces. Three frequency converter groups run independently, and each can be used on its own, so filler, primer and top coat can all be applied in one pass. Total power is 11.1 kW at 600 and 1000 mm and 11.8 kW at 1300 mm.

Parameter	ICDT600	ICDT1000	ICDT1300
Max.Processing Width	600mm	1000mm	1300mm
Processing Thickness	2-90mm	2-90mm	2-90mm

Parameter	ICDT600	ICDT1000	ICDT1300
Min. Processing Length	300mm	300mm	300mm
Feeding Speed	0-20m/min	0-20m/min	0-20m/min
Feeding Power	1.5kw	1.5kw	2.2kw
Coating Roller Power	1.5kw*2	1.5kw*2	1.5KW*2
Doctor Roller Power	0.55kw*2	0.55kw*2	0.55kw*2
Filling Roller Power	1.5kw	1.5kw	1.5kw
Heater Power	2kw*2	2kw*2	2kw*2
TTotal Power	11.1kw	11.1kw	11.8kw
Dimension(L x W x H)mm	2145*1920*1640	2145*2300*1640	2145*2600*1640
Net Weight	1400kg	1750kg	2000kg

Three Heads Paint Roller Coater Machine roller coating machine for wood

A three head roller coater for board type furniture, flooring, flush doors, ceramic and handicraft surfaces. Three frequency converter groups run independently, and each can be used on its own, so filler, primer and top coat can all be applied in one pass. Total power is 11.1 kW at 600 and 1000 mm and 11.8 kW at 1300 mm.

Parameter	ICDT600	ICDT1000	ICDT1300
Max.Processing Width	600mm	1000mm	1300mm
Processing Thickness	2-90mm	2-90mm	2-90mm
Min. Processing Length	300mm	300mm	300mm
Feeding Speed	0-20m/min	0-20m/min	0-20m/min
Feeding Power	1.5kw	1.5kw	2.2kw
Coating Roller Power	1.5kw*2	1.5kw*2	1.5KW*2
Doctor Roller Power	0.55kw*2	0.55kw*2	0.55kw*2
Filling Roller Power	1.5kw	1.5kw	1.5kw
Heater Power	2kw*2	2kw*2	2kw*2
TTotal Power	11.1kw	11.1kw	11.8kw
Dimension(L x W x H)mm	2145*1920*1640	2145*2300*1640	2145*2600*1640
Net Weight	1400kg	1750kg	2000kg

Prime Single Roller Coating Machine Roller Coater machine

A one head roller coating machine for board type furniture, flooring, flush doors, ceramic and handicraft surfaces. One applicator roller and one doctor roller lay primer or top coat and the paint that does not transfer is recycled. It runs UV, PU, PE, NC and water borne coatings at a feed of 0-20 m per minute and 5.75 kW total power.

Parameter	ICGT-1-600	ICGT-1-1000	ICGT-1-1300
Max.Processing Width	600mm	1000mm	1300mm
Processing Thickness	2-90mm	2-90mm	2-90mm
Min. Processing Length	300mm	300mm	300mm
Feeding Speed	0-20m/min	0-20m/min	0-20m/min
Feeding Power	1.5kw	1.5kw	1.5kw
Coating Roller Power	1.5kw	1.5kw	1.5kw
Doctor Roller Power	0.75kw	0.75kw	0.75kw

Parameter	ICGT-1-600	ICGT-1-1000	ICGT-1-1300
Heater Power	2kw	2kw	2kw
TTotal Power	5.75kw	5.75kw	5.75kw
Dimension(L x W x H)	1130*1920*1640	1130*2315*1640	1130*2615*1640
Net Weight	820kg	900kg	980kg

Prime UV One Head roller coater machine Roller Coating Machine

A one head roller coating machine for board type furniture, flooring, flush doors, ceramic and handicraft surfaces. One applicator roller and one doctor roller lay primer or top coat and the paint that does not transfer is recycled. It runs UV, PU, PE, NC and water borne coatings at a feed of 0-20 m per minute and 5.75 kW total power.

Parameter	ICGT-1-600	ICGT-1-1000	ICGT-1-1300
Max.Processing Width	600mm	1000mm	1300mm
Processing Thickness	2-90mm	2-90mm	2-90mm
Min. Processing Length	300mm	300mm	300mm
Feeding Speed	0-20m/min	0-20m/min	0-20m/min
Feeding Power	1.5kw	1.5kw	1.5kw
Coating Roller Power	1.5kw	1.5kw	1.5kw
Doctor Roller Power	0.75kw	0.75kw	0.75kw
Heater Power	2kw	2kw	2kw
TTotal Power	5.75kw	5.75kw	5.75kw
Dimension(L x W x H)	1130*1920*1640	1130*2315*1640	1130*2615*1640
Net Weight	820kg	900kg	980kg

Roller Coater Machine For Uv Line Automatic Flat Line Furniture

A two head roller coating machine for flat line furniture, flooring and door panels. Two applicator and doctor roller pairs let you put down two layers, or a filler and a primer, in one pass through the machine at 9.6 kW total power. It handles UV, PU, PE, NC and water borne coatings and recycles the paint.

Parameter	Value
Max processing width	600 mm / 1000 mm / 1300 mm
Processing thickness	2-90 mm
Min processing length	300 mm
Feeding speed	0-20 m/min
Feeding power	1.5 kW
Coating roller power	1.5 kW x2
Doctor roller power	0.55 kW x2
Total power	9.6 kW
Paint film	5-10 g/m2

Furniture Automatic Intelligent Precise Roller coater Machine Double Roller UV Coating

A two head roller coating machine for flat line furniture, flooring and door panels. Two applicator and doctor roller pairs let you put down two layers, or a filler and a primer, in one pass through the machine at 9.6 kW total power. It handles UV, PU, PE, NC and water borne coatings and recycles the paint.

Parameter	Value
Max processing width	600 mm / 1000 mm / 1300 mm
Processing thickness	2-90 mm
Min processing length	300 mm
Feeding speed	0-20 m/min
Feeding power	1.5 kW
Coating roller power	1.5 kW x2
Doctor roller power	0.55 kW x2
Total power	9.6 kW
Paint film	5-10 g/m2

Automatic Flat Line Furniture roller coater machine Two Head Roller Coating

A two head roller coating machine for flat line furniture, flooring and door panels. Two applicator and doctor roller pairs let you put down two layers, or a filler and a primer, in one pass through the machine at 9.6 kW total power. It handles UV, PU, PE, NC and water borne coatings and recycles the paint.

Parameter	Value
Max processing width	600 mm / 1000 mm / 1300 mm
Processing thickness	2-90 mm
Min processing length	300 mm
Feeding speed	0-20 m/min
Feeding power	1.5 kW
Coating roller power	1.5 kW x2
Doctor roller power	0.55 kW x2
Total power	9.6 kW
Paint film	5-10 g/m2

Roller Coater Machine

One, two and three head roller coaters that hold 5 to 10 grams per square metre and recycle the paint that does not transfer.

Curtain Coating Machine

A falling curtain of varnish that lays a film down to 0.05 mm with nothing touching the wet surface, which is why it is used for high gloss.

Precise Stain Machine

Brush roller stain machines that work colour into the pore of the wood so the grain reads clearly instead of looking washed out.

Putty Machine

Putty filling machines that close open pores and pinholes at 10 to 30 grams per square metre, at constant pressure across varying panel thickness.

Back Coating Machine

Sealing the underside of flooring and panel so moisture from the subfloor cannot enter and cup the board.

How To Order

Do you offer installation?

Machines are almost fully assembled before they are loaded into the container, so installation in your workshop is straightforward. Video guidance and an English manual are provided free. An engineer can be sent to site on request, with all costs in the buyer's account: two way transport between China and your factory, visa and insurance, hotel and meals in your country, plus USD 200 per day labour.

Where can we get replacement parts?

Most spare parts are held in stock and are sent to the buyer directly from our warehouse at original prices.

How long does it take to get replacement parts?

Common spare parts can be delivered by express within one week. Some parts can be purchased locally.

What technical support do you offer?

Technical support by phone, email or WhatsApp and Skype around the clock, an English version manual with operation video, and an engineer available to service machinery overseas.

Do you have machines in our country?

Machines have been sold to more than 20 countries, including Russia, Singapore, Uzbekistan, the USA, Malaysia, Peru, Colombia, Vietnam and Slovakia.

Can the machine be customised?

Yes. Machines are customised to the buyer's requirement, which is how almost every order is built.

What other machines do you offer?

A one-stop range of woodworking machines: sanding machines, UV dryers, roller coating machines, painting machines and conveyors.