



Separate Slip Rings — Specification Sheet

A separate slip ring supplies the ring stack and the brush block as two independent parts, so the machine builder mounts each one directly on the structure instead of fitting a packaged unit.

Models in this sheet	4
Manufacturer	JiuJiang Ingiant Technology Co., Ltd
Established	2014
Quality system	ISO 9001, GJB9001C, GB/T 19001-2008 / ISO 9001:2008
Standard lead time	7–15 days
Customised lead time	10–20 days simple, 15–40 days complex
Delivery port	Jiujiang, China Mainland
Warranty	12 months from date of sale
Enquiries	sales@ingiant.com · WhatsApp +86 138 7929 7499

What this family solves

Very large diameters, very thin axial space or a rotor that is already part of the machine make a packaged slip ring impossible to install.

INGIANT supplies the rotor ring assembly and the brush holder separately with the mounting interfaces you specify, so the bearing function stays in the machine and the slip ring only carries current.

Model list with published parameters

Model / product	Circuits	Voltage	Current	Speed	IP
DHK035-5 Ingiant through hole slip ring without housing hole diameter 35mm...	—	0–240 VAC/VDC	2A.5A.10A.15A.20A	0–600rpm	IP54
DHK060-10-002 Ingiant seperate slip rings with through hole 60mm and 10...	10	0–240 VAC/VDC	2A.5A.10A.15A.20A	0–600rpm	IP54
Customization through hole slip ring 130mm 6 channels 10A	—	0–240 VAC/VDC	2A.5A.10A.15A.20A	0–600rpm	IP54
Separate slip rings	—	0–240 VAC/VDC	2A.5A.10A.15A.20A	0–600rpm	IP54

How to order

Send these eight inputs and INGIANT returns a design and a drawing: Operating speed in rpm; Type of installation and mounting interface; Installation envelope and bore size; Number of circuits, counted as single wires beside the cable; Rated voltage and current for the power rings and the signal rings; Signal type and its parameters — this is the parameter that decides the design; Operating temperature range; IP sealing requirement.

Dashes in the table mean the value is not published for that model because the build is set against the customer drawing. It is issued with the quotation.