

Ventedilated Stretch Film JMSH02 and JMSH03

Already prestretched perforated pallet wrap – machine and manual rolls



Ventedilated stretch film is perfect for product distribution and the film is designed to maximise the aeration of the product wrapped. Because of its perforated film structure it allows quicker cooling and drying of palletised goods. It is easy to apply by hand or machine, and available in prestretched and conventional grades. It is perfect for solving problems when there is a build up of condensation or moisture, such as breweries, soft drinks, pasteurised goods, canned foods, pharmacies, dairy, fruit and vegetable, plants, meat, fish and frozen snacks.

Technical Data Sheet

Technical feature	Machine rolls	Manual rolls	Tolerance
Length	3500 m	440 m	—
Width	430 mm	430 mm	+/-5%
Average thickness	8 µm	8 µm	+/-2 µm
Prestretch	50%	50%	—
Elongation at break	55%	55%	+/-5%
Tensile stress at break	15 kg	15 kg	+/-5%
Number of holes	13	13	—
Weight per metre	3.1 g	3.1 g	+/-5%
Weight per roll	11 kg	1.37 kg	—

Ventedilated stretch film can be customised to your request.

Why This Grade

- 3.1 g per metre, roughly a third of the plastic per pallet of the 25 micron prestretchable grade
- Already stretched in production, so results do not depend on a machine prestretch setting
- 3500 m machine rolls reduce roll changes on a high volume line
- 440 m manual rolls weigh 1.37 kg, light enough for hand wrapping through a shift
- Thirteen perforations per row, the same as the heavier grade

Notes On Application

- Elongation at break is 55% against a prestretch of 50%. Apply with light even tension rather than pulling further.

- If the load will not hold at that tension it needs the 25 micron grade or pallet netting.
- Machine and manual rolls carry the same film specification.

Request a quotation. Send your pallet size, load weight, wrapper model and the temperature at which goods are wrapped. WhatsApp +63 917 685 5050 or lizzy@jiameiplast.com