



Rigging And Cargo Control Catalogue

The complete Kailipu range: 517 catalogued items across eight product families, supplied from Qingdao China on one purchase order.

Rigging Hardware — 272 items

Chains — 61 items

Webbing Slings — 60 items

Ratchet Straps — 67 items

Trailer Winches — 8 items

Wire Rope — 20 items

Pulley Blocks — 29 items

All figures in this document are the specification lines published in the Kailipu catalogue. Where a value is not stated it is available on request. Send a drawing or a bill of materials on WhatsApp +86-18660236941 or to sales@qd-kailipu.com and we will confirm sizes, finish and lead time.

Rigging Hardware

272 catalogued items. Full page: qd-kailipu.com/categories/rigging-hardware.html

D-Rings

No	Product	Published Specification Lines
1	Weld-on Lifting Point Grade 80 Alloy Steel Forged D-Ring with Pivoting Link	Size: From 1.12T to 20T Material: Alloy Steel Processing: Forged Finish: Painted Packing: Cartons + Pallets
2	Bend Lashing Ring Weld-on, Heavy Duty 45 Degree Bent Forged with Weld-On Mounting Bracket	Size: From 1/2"x12000lbs to 1"x47000lbs Material: Carbon / Alloy Steel Processing: Forged Finish: Self-colored, Painted,
3	Weld-On Forged D Ring Heavy Duty Mounting Ring Lashing Ring	Size: From 3/8"x5000lbs to 1"x47000lbs Material: Carbon / Alloy Steel Processing: Forged Finish: Self-colored, Painted,
4	Forged Container Lashing D Ring Weldable Heavy Duty D Points with Clamp	Size: From 20T to 67T WLL: From 5T to 16.75T Material: Carbon / Alloy Steel Processing: Forged Finish: Self-colored, Pai

Eye Bolts and Eye Nuts

No	Product	Published Specification Lines
1	G-400 Threaded Eye Nut	Material: Forged Steel Processing: Drop Forged, Quenched and Tempered Finish: Hot Dipped Galvanized Size: from 1/4 " to 2
2	S279 Shoulder Type Machinery Eye Bolt	Material: Forged Steel Processing: Drop Forged, Quenched and Tempered Finish: Hot Dipped Galvanized Size: from 1/4 " to 1
3	Regular Nut Eye Bolts G-291	Material: Forged Steel Processing: Drop Forged, Quenched and Tempered Finish: Hot Dipped Galvanized Size: from 1/4 x 2" t
4	G277 Shoulder Nut Eye Bolt Lifting Eye Bolts and Eye Nuts	Material: Forged Steel Processing: Drop Forged, Quenched and Tempered Finish: Hot Dipped Galvanized Size: from 1/4 x 2" t
5	DIN 582 EYE NUT	Material: Super carbon steel. Size: M6-M64 Safety factor: 4:1. Marking: WLL, CE-marking Finish: Zinc Plated. Self-Colore
6	DIN 580 Eye Bolt	Material: Super carbon steel. Size: M6-M64 Safety factor: 4:1. Marking: WLL, CE-marking Finish: Zinc Plated. Self-Colore

G43 and G70 Hooks

No	Product	Published Specification Lines
1	Bolt-On Tow Hook with Safety Latch	Material: Drop-Forged Heat-Treated Carbon Steel / Alloy Steel Size: WLL 10,000 lbs (4.5T) Surface Finish: Weather-Resist
2	Grade 70 Bolt-On Grab Hook with Backer Plate	Material: Heat-Treated Alloy Steel Size: 5/16" , 3/8" Grade: Grade 70 / G70 Hook Type: Grab Hook Mounting Type: Bolt-On
3	5/16 G70 Mini J Hook Compact Frame J Hook	Size: 5/16 inch Grade: Grade 70 Material: Alloy Steel Manufacturing Process: Forged Heat Treatment Quenched and Tempered
4	Triangle Snap Hook, Triangle Ring Safety Hook For Lashing Strap	Material: Carbon Steel Finish: Zinc-plated or powder-coated Size: Various sizes available Load Capacity: Customized on r
5	Clevis Grab Hook with Safety Latch A330N Grade 70	Size: From 5/16" to 5/8" Ultimate Load is 4 times Working Load Limit. Material: Alloy Steel Processing: Forged Finish: S
6	Weld On Grab Hook Grade 70 Forged Steel Chain Hooks	Size: From 5/16" to 5/8" Ultimate Load is 4 times Working Load Limit. Material: Alloy Steel Processing: Forged Finish: S
7	Eye J Hook 8" Tow J Hook Short Type, G70 WLL 4700LBS	Size: 8" WLL: 4700LBS Breaking Strength (lbs): 18800 LBS Material: Alloy Steel Processing: Forged Finish: Yellow chroma
8	Eye J Hook 15" Towing Long Shank Hook, Grade 70 Forged Steel WLL 4700LBS	Size: 15" WLL: 4700LBS Breaking Strength (lbs): 18800 LBS Material: Alloy Steel Processing: Forged Finish: Yellow chroma

No	Product	Published Specification Lines
9	8 Inch Clevis Short J Tow Hook Grade 70 Forged Steel WLL 5400LBS	Size: 8" WLL: 5400LBS Breaking Strength (lbs): 18800 LBS Material: Alloy Steel Processing: Forged Finish: Yellow chromate
10	15 Inch Clevis J Tow Hook Grade 70 Forged Steel WLL 5400LBS	Size: 15" WLL: 5400LBS Breaking Strength (lbs): 18800 LBS Material: Alloy Steel Processing: Forged Finish: Yellow chroma
11	RTJ Cluster Hooks Grade 70 Forged Steel WLL 4800 LBS	WLL: 4800LBS Breaking Strength (lbs): 18800 LBS Material: Alloy Steel Processing: Forged Finish: Yellow chromate finish
12	Mini J Hook Grade 70 Forged Steel 5/16"-3/8" /7-8mm, WLL 5400LBS	Size: 5/16"-3/8" /7-8mm WLL: 5400LBS Breaking Strength (lbs): 19000 LBS Material: Alloy Steel Processing: Forged Finish:
13	Twisted T/J Combo Hook Grade 70 Forged Steel 5/16"/8mm, Safe Working Load 4700LBS	Size: 5/16"/8mm WLL: 4700LBS Safety Factor: 4:1 Material: Alloy Steel/Carbon Steel Processing: Forged Finish: Electric Y
14	T Hook For Towing 5/16"/8mm, WLL 4700LBS	Size: 5/16"/8mm WLL: 4700LBS Safety Factor: 4:1 Material: Alloy Steel/Carbon Steel Processing: Forged Finish: Electric Y
15	R Hook Grade 70 Towing Hook 5/16"/8mm, WLL 4700LBS.	Size: 5/16"/8mm WLL: 4700LBS Safety Factor: 4:1 Material: Alloy Steel/Carbon Steel Processing: Forged Finish: Electric Y
16	Swivel Lifting Hook, Eye Hoist Hook Grade 70 322A	Material : Alloy steel Safety Factor: 5 : 1 Size: From 0.5T to 30T Processing: Drop Forged / Quenched and Tempered Finis
17	Eye Slip Hook with Latch Grade 70 A324	Material: Alloy Steel Safety Factor: 4:1 Processing: Forged / Quenched and Tempered Finish: Powder Coated / Electric Gal
18	Eye Hoist Hook With Latch 320C	Material: Carbon Steel Safety Factor: 5:1 Processing: Forged / Quenched and Tempered Finish: Powder Coated / Electric Ga
19	Eye Grab Hook Grade G43 H323	Material: Carbon Steel Safety Factor: 4:1 Processing: Forged / Quenched and Tempered Finish: Powder Coated / Electric Ga
20	Clevis Slip Hook Grade 70 Yellow Zinc-Plated A331	Material: Alloy Steel Safety Factor: 4:1 Processing: Forged / Quenched and Tempered Finish: Yellow Zinc-Plated Size: Fro
21	Clevis Grab Hook Grade 70 Yellow Zinc-Plated A330	Material: Drop-Forged Alloy Steel Safety Factor: 4:1 Processing: Forged / Quenched and Tempered Finish: Yellow Zinc-Plat
22	322C Swivel Eye Hoist Hook Grade 43	Material : Carbon steel Safety Factor: 5 : 1 Size: From 0.5T to 20T Processing: Drop Forged / Quenched and Tempered Fini
23	Eye Slip Hook with Latch Grade 43 H324	Material: Carbon Steel Safety Factor: 4:1 Processing: Forged / Quenched and Tempered Finish: Powder Coated / Electric Ga
24	Eye Hoist Hook With Latch 320A	Material: Alloy Steel Safety Factor: 5:1 Processing: Forged / Quenched and Tempered Finish: Powder Coated / Electric Gal
25	Eye Grab Hook Grade 70 A323	Material: Alloy Steel Safety Factor: 4:1 Processing: Forged / Quenched and Tempered Finish: Powder Coated / Electric Gal
26	DIN 689 Eye Load Hook With Latch	Material: Carbon steel. Safety Factor: 4:1 Size: 250kg-3000kg Finish: Self-Colored , Eletric Galvanized Process: Drop Fo
27	Clevis Slip Hook Grade 43 Zinc-Plated H331	Material: Carbon Steel Safety Factor: 4:1 Processing: Forged / Quenched and Tempered Finish: Powder Coated / Electric Ga
28	Clevis Grab Hook Grade 43 Zinc-Plated H330	Material: Carbon Steel Safety Factor: 4:1 Processing: Forged / Quenched and Tempered Finish: Powder Coated / Electric Ga

Grade 80 Hooks

No	Product	Published Specification Lines
1	G80 Eurpean Type Eye Self-locking Safety Hook	Material : Alloy steel Safety Factor: 4 : 1 Size: From 6-8 to 32-8 Processing: Drop Forged / Quenched and Tempered Finis
2	G80 Eye Shorterning Grab Hook	Material : Alloy steel Safety Factor: 4 : 1 Size: From 6-8 to 22-8 Processing: Drop Forged / Quenched and Tempered Finis
3	G80 Eye Grab Hook U.S Type A328	Material: Alloy Steel Size: From 1/4" to 7/8" Surface :Powder Coated,Painted Process:Froged,Quenched and Tempered Packi

No	Product	Published Specification Lines
4	G80 Clevis Sling Hook With Latch A339	Material : Alloy steel Safety Factor: 4 : 1 Size: From 6-8 to 32-8 Processing: Drop Forged / Quenched and Tempered Finis
5	G80 Sling Hook With Connecting Link	Material: Alloy Steel Size: From 7/8-8 to 18/20-8 Surface :Powder Coated,Painted Process:Froged,Qunenched and Tempered P
6	G80 Weld On Lifting Hooks	Material : Alloy steel. Size: From 1T to 10T Surface :Powder Coated,Painted Safety Factor: 5 : 1 Packing: Cartons then p
7	G80 Swivel Self Locking Hook European Type	Material : Alloy steel Safety Factor: 4 : 1 Size: From 6-8 to 32-8 Processing: Drop Forged / Quenched and Tempered Finis
8	G80 Sliding Choke Hook	Material : Alloy steel. Size: From 3/8"-1/2" to 1" Surface :Powder Coated,Painted Packing: Cartons then pack on pallets
9	G80 High Tensile C Hook Lashing Chain Type Marine Towing Hook	Material : Alloy steel Safety Factor: 4 : 1 Size: From 9-8 to 13-8 Processing: Drop Forged / Quenched and Tempered Finis
10	G80 Shank Self-locking Hook US Type	Material : Alloy steel. Size: From 5/16 to 3/8 Surface :Powder Coated,Painted Packing: Cartons then pack on pallets
11	G80 Eye Foundry Hook	Material : Alloy steel Safety Factor: 4 : 1 Size: From 6 to 32 Processing: Drop Forged / Quenched and Tempered Finish :P
12	G80 Viking G Hook	Material : Alloy steel Safety Factor: 4 : 1 Size: From 5T to 20T Processing: Drop Forged / Quenched and Tempered Finish
13	G80 Eye Sling Hook With Latch	Material : Alloy steel Safety Factor: 4 : 1 Size: From 6-8 to 32-8 Processing: Drop Forged / Quenched and Tempered Finis
14	G80 Clevis Shortening Grab Hook	Material : Alloy steel Safety Factor: 4 : 1 Size: From 6-8 to 22-8 Processing: Drop Forged / Quenched and Tempered Finis
15	G80 Eurpean Type Clevis Self-locking Safety Hook	Material : Alloy steel Safety Factor: 4 : 1 Size: From 6-8 to 32-8 Processing: Drop Forged / Quenched and Tempered Finis
16	G80 Clevis Grab Hook U.S Type	Material: Alloy Steel Size: From 1/4" to 7/8" Surface :Powder Coated,Painted Process:Froged,Qunenched and Tempered Packi
17	G80 Clevis Forest Hook	Material: Alloy Steel Size: From 6-8,to 13-8 Surface :Powder Coated,Painted Process:Froged,Qunenched and Tempered Packin
18	G80 Clevis Bend Hook	Material: Alloy Steel Safety Factor: 4 : 1 Processing: Drop Forged / Quenched and Tempered Finish: Powder Coated/Yellow
19	G80 Forged Barrel Hook	Material: Alloy Steel Safety Factor: 4 : 1 Processing: Drop Forged / Quenched and Tempered Finish: Powder Coated Size: 1
20	Forged Mild Steel Agricultural Hook	Size From 50mm to 120mm Yellow painted, other color is available as per request. Working load limit permanently shown on

Grade 80 Links

No	Product	Published Specification Lines
1	G80 Weldless Round Ring Forged Alloy Steel Ring - S-643	Forged alloy steel, quenched and tempered Forged-Quenched and Tempered. Ultimate Load at 6 times the Working Load Limit.
2	Pear Shaped Link Forged Weldless Pear links A-341, G-341	Available with Carbon Steel and Alloy Steel. Forged-Quenched and Tempered. Ultimate Load at 5 times the Working Load Lim
3	Weld-on pivoting link / Grade 80 Weld on Lifting Point	S-265 Pivot Link Approved for overhead lifting Design Factor 4:1 Forged Steel- Quenched and Tempered Painted finish.
4	Swivel Hoist Ring/G80 Universal Swivel Eyebolt with Ring	Colour - Red or yellow Grade 80 alloy steel, quenched and tempered. Painted finish. Minimum breaking load is 4 times the
5	GRADE 80 EYEBOLT/Alloy Steel Eye Bolt	Grade 80, high strength alloy steel. Red Painted finish. Sizes based generally on Din 580 Eyebolts. Minimum breaking loa
6	G80 Welded Master Link Assembly A347	Material: High tensile Alloy steel. Processing: Forged, Quenched & Tempered. Proof Loading: 2 times Working Load Limit.

No	Product	Published Specification Lines
7	G80 Web Sling Connector	Materials: Alloy steel Surface: Powder plastified Size: 6-32mm B. L= 4 times*WLL commonly used to connect webbing slings
8	G80 European Type Coupling Link	Materials: Alloy steel Surface: Powder plastified Size: From 6mm to 32mm B. L= 4 times*WLL Application: Overhead Lifting
9	G80 US Type Connect link	Materials: Alloy steel Surface: Powder plastified Size: From 1/4" to 1 1/4" Working Load Limit: 1.12T-31.5T B. L= 4 time
10	G80 Omega Link	Materials: Alloy steel Surface: Powder plastified Size: From 6mm to 20mm Working Load Limit: 1.12T-12.5T B. L= 4 times*W
11	G80 Oblong Link US Type Welded Master Link A344	Material: Forged Super Alloy Steel -Quenched and Tempered Surface: Powder plastified Size: From 7/16" to 1 1/4" Ultimate
12	A346 Master Link Assembly Grade 80 European Type	Material: Forged Super Alloy Steel Suitable for EN818-2 CHAIN Individually proof test at 2.5 times Working Load Limited.
13	G80 Master Link Assembly A345 US Type	Material: Forged Super Alloy Steel Suitable for EN818-2 CHAIN Individually proof test at 2.5 times Working Load Limited.
14	G80 European Type Master Link A343(no flat Din 5688)	.Forged Super Alloy Steel-Quenched and Tempered .Suitable for EN818-2 CHAIN .Individually proof test at 2.5 times Workin
15	G80 US Type Forged Oblong Master Link A342	Material: Alloy Steel Size: From 1/2" to 4" Surface :Powder Coated,Painted Process:Froged,Qunenched and Tempered Packing

Hardware Kits

No	Product	Published Specification Lines
1	Outdoor Light Hanging Kit, Hanging Light Hardware Kit	For Outdoor String Lights Suspension. Hanging Light Hardware Kit includes: 1 Black coated wire rope 7x7 STRAND, Dia 2.5m

Links and Rings

No	Product	Published Specification Lines
1	G-401 Regular Chain Swivel Eye and Eye	Material : Carbon Steel Size: From 1/4" to 1 1/2" Processing: Drop Forged,Welded, Heat Treated Finish : Hot Dip Galvaniz
2	Twin Clevis Link S249 H Link	Material : Pin is alloy steel, Body is forged carbon steel Size: From 1/4" to 7/16" Surface : Galvanized, Self-color, Po
3	Lag Hitching Ring Tie/Hitching Ring Hook Srew	Material : Carbon Steel Size: 6.7mm, 7mm,7.6mm Processing: Forged Finish: Zinc Plated Use with Rope Package: Cartons the
4	Hitching Ring with Plate 2 in Zinc Plated	Material : Carbon Steel Size: 2" Processing: Forged Finish: Zinc Plated Used for animal tie-downs and other home and far
5	G-403 Jaw End Swivel	Material : Carbon Steel Size: From 1/4" to 1 1/2" Processing: Drop Forged,Welded, Heat Treated Finish : Hot Dip Galvaniz
6	G-402 Regular Chain Swivel Eye and Eye	Material : Carbon Steel Size: From 1/4" to 1 1/2" Processing: Drop Forged,Welded, Heat Treated Finish : Hot Dip Galvaniz
7	Chain Missing Link Replacement Links G-335	Material : Carbon Steel Integral rivets join the two halves Size: From 3/16" to 1" Processing: Forged,Quenched and Tempe
8	Double Clevis Link S247	Material : Pin is alloy steel, Body is forged carbon steel Size: From 1/4" to 5/8" Surface : Galvanized, Self-color, Pow

Load Binders

No	Product	Published Specification Lines
1	Ratchet Binders W/O Hooks	Material : Carbon steel Size: From 5/16"-3/8" to 1/2"-5/8" Processing: Drop Forged and Casting Finish : Powder Coated or

No	Product	Published Specification Lines
2	Australia Standard Ratchet Chain Load Binder With Winged Grab Hook	Material : Carbon steel Size: From 6mm to 13mm Processing: Drop Forged and Casting Finish : Powder Coated or Electronic
3	Tension Lever Load Binder	Material : Carbon steel Size: From 9mm to 13mm Processing: Drop Forged and Casting Finish : Powder Coated or Electronic
4	EN12195-3 Ratchet Load Binder With Shortening Grab Hook and Safety Pin	Material : Carbon steel Size: From 6mm to 16mm Processing: Drop Forged and Casting Finish : Powder Coated or Electronic
5	Ratchet Load Binders 140 Chain Binder	Drop Forged Steel. Heat Treated, Quenched and Tempered. Finishing: Powder Coated Fitted with grab hooks for easy connect
6	Lever Chain Binder 150 Load Binders	Material : Carbon steel Size: From 5/16"-3/8" to 1/2"-5/8" Processing: Drop Forged and Casting Finish : Powder Coated or

Precast Concrete Lifting Systems

No	Product	Published Specification Lines
1	Double-Headed U-Shape Lifting Anchor	Material: High-Strength Forged Steel Design: U-Shape with Double-Headed Ends Load Capacities: Available in multiple grad
2	Spherical Head Anchor with Collar for Precast Concrete	Application: Lifting and handling precast concrete elements Material: High-Strength Forged Steel Anchor Type: Cast-In Li
3	Utility Lift Anchor for Precast Concrete	Material: High-Strength Steel Surface Treatment: Galvanized / Untreated (customizable) Load Capacities: Available in mul
4	Rubber Recess Former for Spread Anchor (Split Type)	Material: High-Quality Rubber Design Type: Split Type (Two-Piece Construction) Compatible Anchor Type: Spread Anchor App
5	Rubber Recess Former with Threaded Rod & Wing Nut for Lifting Anchors	Material: High-Quality Rubber Fixing Method: Threaded Rod and Wing Nut Recess Shape: Hemispherical Application: Securing
6	Magnetic Recess Former for Swift Lift / Pin Anchors, Magnetic Void Former	Product Name: Magnetic Recess Former for Swift Lift / Pin Anchors Application: Fixing lifting anchors onto steel formwor
7	Spherical Head Lifting Anchor	Material: High-quality forged steel CM490, 20Mn2 Safety Factor: 3:1 Size Range: Available in load capacities from 1.3T t
8	Lifting Eye Anchor / Dogbone for Precast Concrete	Material: High-quality forged steel CM490 Safety Factor: 3:1 Size Range: Available in load capacities from 1.3T to 20T F
9	Lifting Clutch for Precast Concrete	Material: High-quality alloy steel. Safety Factor: 5:1 Size Range: Available in load capacities from 1.3T to 32T Finish:
10	Erection Anchor for Precast Concrete Panels	Material: High-strength steel Q345D. Safety Factor: 3:1 Size Range: Available in load capacities from 1.3T to 20T Finish
11	Sandwich Panel Connector Butterfly Plate	Material: High-quality forged alloy steel Safety Factor: 3:1 Size Range: Available in load capacities from 6T to 12T Fin
12	Forged Erection Anchor w/ Shear Plate	Material: High-quality forged alloy steel Safety Factor: 3:1 Size Range: Available in load capacities from 3T to 12T Fin

Shackles

No	Product	Published Specification Lines
1	Drop Forged Roller Shackle with Hexagon Bolt Pin and Nut, Sheave / Pulley D Shackle	Size: 3T-85T Material: Alloy Steel Manufacturing Process: Drop Forged Heat Treatment Quenched and Tempered Pin Type: Hex
2	Crosby Wide Body Shackles	Forged Alloy Steel Quenched and Tempered Size from 7Ton to 300Ton Proof tested is 2 times the Work Load Limit Hot Dip Ga
3	G2160 Shackle Crosby Wide Body Shackles	Forged Alloy Steel Quenched and Tempered Size from 7Ton to 300Ton Proof tested is 2 times the Work Load Limit Hot Dip Ga
4	Wide Body Shackle Crosby G-2160	Forged Alloy Steel Quenched and Tempered Size from 7Ton to 300Ton Proof tested is 2 times the Work Load Limit Hot Dip Ga

No	Product	Published Specification Lines
5	Screw Pin Chain Shackle D Type	Material: Carbon Steel or Stainless Steel Process: Free Forging Surface: Electric galvanized Safety factor: 3:1 Size: M5
6	Stainless Steel Shackles Bow Type	Material: Carbon Steel or Stainless Steel Process: Free Forging Surface: Electric galvanized Safety factor: 3:1 Size: M5
7	Screw Pin Bow Shackle	Material: Carbon Steel or Stainless Steel Process: Free Forging Surface: Electric galvanized Safety factor: 3:1 Size: M5
8	Screw Pin Shackle Large Bow Shackle with Collar Pin	Material: Carbon Steel or Stainless Steel Process: Free Forging Surface: Electric galvanized Safety factor: 3:1 Size: M5
9	Stainless Steel D Shackle	Material: Carbon Steel or Stainless Steel Process: Free Forging Surface: Electric galvanized Safety factor: 3:1 Size: M5
10	D Type Shackle European Large Dee	Material: Carbon Steel or Stainless Steel Process: Free Forging Surface: Electric galvanized Safety factor: 3:1 Size: M5
11	3 4 D Ring Shackle, Off Road Towing Shackles	Material: High tensile steel, body carbon steel, pin alloy steel Standard: EN and US Standard Size: 3/16" - 2-1/2" /Diff
12	Off Road Shackle With Isolator, D Ring Towing Shackles	Material: High tensile steel, body carbon steel, pin alloy steel Standard: EN and US Standard Size: 3/16" - 2-1/2" /Diff
13	Safety Chain Shackle, Bolt Pin, Lifting D Shackles	Material: Body-Super Carbon Steel. Screw Pin-Alloy Steel Safety Factor: 4:1, 6:1. Processing: Drop Forged, quenched and
14	Bolt Type Shackle, Safety Pin Chain Shackle, Lifting D Shackles	Material: Body-Super Carbon Steel. Screw Pin-Alloy Steel Safety Factor: 4:1, 6:1. Processing: Drop Forged, quenched and
15	Bolt Type Anchor Shackle Bow Shackles	Material: Body-Super Carbon Steel. Screw Pin-Alloy Steel Safety Factor: 4:1, 6:1. Processing: Drop Forged, quenched and
16	Heavy Duty Shackle Bolt Type Anchor / Bow Shackles	Material: Body-Super Carbon Steel. Screw Pin-Alloy Steel Safety Factor: 4:1, 6:1. Processing: Drop Forged, quenched and
17	Chain Shackle, US Type Screw Pin D / Dee Shackle	Material: Body-Super Carbon Steel. Screw Pin-Alloy Steel Safety Factor: 4:1, 6:1. Processing: Drop Forged, quenched and
18	Lifting D Shackles, US Type Screw Pin Chain Shackle G210	Material: Body-Super Carbon Steel. Screw Pin-Alloy Steel Safety Factor: 4:1, 6:1. Processing: Drop Forged, quenched and
19	Rigging Shackle Grade S(6) Bow Shackle	Processing: Body-Drop Forged / Quenched and Tempered Screw Pin-hot/cold forging / Drop Forged / Quenched and Tempered Fi
20	Dee shackle European Type Large D	Material: Carbon Steel or Stainless Steel Process: Free Forging Surface: Electric galvanized Safety factor: 3:1 Size: M5
21	D-Ring Shackle With Isolator, D Ring Towing Shackles	Material: High tensile steel, body carbon steel, pin alloy steel Standard: EN and US Standard Size: 3/16" - 2-1/2" /Diff
22	Safety Pin Shackle, Bolt Type Lifting Chain Shackles	Material: Body-Super Carbon Steel. Screw Pin-Alloy Steel Safety Factor: 4:1, 6:1. Processing: Drop Forged, quenched and
23	Anchor Shackle Bolt Type G2130 Lifting Rigging Shackles	Material: Body-Super Carbon Steel. Screw Pin-Alloy Steel Safety Factor: 4:1, 6:1. Processing: Drop Forged, quenched and
24	D Shackle, Screw Pin Chain Shackles G210	Material: Body-Super Carbon Steel. Screw Pin-Alloy Steel Safety Factor: 4:1, 6:1. Processing: Drop Forged, quenched and
25	Shackles for Lifting Screw Pin Bow Shackle	Technical Notes: U.S. Federal Specification(ASME B30.26) Material: Body-Super Carbon Steel. Screw Pin-Alloy Steel Safety
26	Bow Shackle/ Screw Pin Anchor Shackle	Technical Notes: U.S. Federal Specification(ASME B30.26) Material: Body-Super Carbon Steel. Screw Pin-Alloy Steel Safety
27	Twisted Shackle Stainless Steel	Size: From 4mm to 12mm. Ultimate Load is 4 times Working Load Limit. Material: Stainless steel 304/316 Processing: Forge
28	Stainless Steel Long D Shackle	Stainless Steel Long D Shackle marine hardware STAINLESS STEEL Long Shackle Marine Grade This is for one quality marine
29	JIS Standard Screw Pin Chain Type Shackles For Rigging	Material: Carbon steel. Safety Factor: 4:1 Size: 5mm-50mm Surface: electro galvanize or on special requirement. Process:

No	Product	Published Specification Lines
30	Stainless Steel Bow Shackle JIS Standard Screw Pin Anchor Shackle	Material: Carbon steel. Safety Factor: 4:1 Size: 5mm-50mm Surface: electro galvanize or on special requirement. Process:
31	European Large D Shackle with Screw Collar Pin	Material: Carbon Steel or Stainless Steel Process: Free Forging Surface: Electric galvanized Safety factor: 3:1 Size: M5
32	European Large Bow Shackle with Screw Collar Pin	Material: Carbon Steel or Stainless Steel Process: Free Forging Surface: Electric galvanized Safety factor: 3:1 Size: M5
33	G2150 Shackle US Fed. Spec Safety Bolt Chain / D Shackle	Material: Body-Super Carbon Steel. Screw Pin-Alloy Steel Safety Factor: 4:1, 6:1. Processing: Drop Forged, quenched and
34	G2130 Shackle US Bolt Type Anchor Bow Shackle	Material: Body-Super Carbon Steel. Screw Pin-Alloy Steel Safety Factor: 4:1, 6:1. Processing: Drop Forged, quenched and
35	G210 Shackle US Type Screw Pin Chain / D Shackles	Material: Body-Super Carbon Steel. Screw Pin-Alloy Steel Safety Factor: 4:1, 6:1. Processing: Drop Forged, quenched and
36	G209 US Type Screw Pin Anchor Shackle	Technical Notes: U.S. Federal Specification(ASME B30.26) Material: Body-Super Carbon Steel. Screw Pin-Alloy Steel Safety

Marine Chains

No	Product	Published Specification Lines
1	Lugless Joining Shackle - Kenter Link - End Shackle -Swivel Set	Grade: U2 or U3 Size: From 12.5mm to 162mm Color: Silver,Black,Steel color Process: Welded Surface: Hot dip galvanized,G
2	Kenter Link - Joining / End Shackle -Swivel Set	Grade: U2 or U3 Size: From 12.5mm to 162mm Color: Silver,Black,Steel color Process: Welded Surface: Hot dip galvanized,G
3	Kenter Shackle - Anchor Chain Fittings	Grade: U2 or U3 Size: From 12.5mm to 162mm Color: Silver,Black,Steel color Process: Welded Surface: Hot dip galvanized,G

Spring Snap Hooks and Quick Links

No	Product	Published Specification Lines
1	Solid Brass Snap Hook	Material: 100% Solid Brass (No Plating) Surface Finish: Polished Natural Brass Sizes: 3/4", 1", 1-1/4", 1-1/2", etc.
2	Swivel Eye Bull Snap Zinc Alloy Diecast Series-Pet Hardware	Material: Zinc Die Casting Surface Finish: Polished / Nickel Plated / Chrome Plated Sizes: Available in multiple sizes t
3	Trigger Snap Hook Zinc Alloy Diecast Series-Pet Hardware	Material: Zinc Die Casting Surface Finish: Polished / Nickel Plated / Chrome Plated Sizes: Available in multiple sizes t
4	Panic Snap - Heavy Duty Quick Release Hook	Panic Snap - Heavy Duty Quick Release Hook Pet Hardware -Designed for safety and quick release, our panic snaps are idea
5	Snap Hook Zinc Alloy Diecast Series-Pet Hardware Bolt Snaps	Material: Zinc Alloy (Die Cast) Surface Finish: Polished / Nickel Plated / Chrome Plated Sizes: Available in multiple si
6	D Type Mountaineering Buckle 8CM Aluminum Alloy	Outdoor Spring Hook Quick release buckle mountaineering buckle water bottle buckle
7	Sponge Mountaineering Clasp Aluminum Steel/Large D Shape Outdoor	Size: 160x100x12mm Net weight: 115g Material: Aluminum alloy Surface: Colorful
8	Aluminum D Carabiner, Climbing Hook for Home, Rv, Camping, Fishing, Hiking	Size: 77x40mm Net weight: 23g Material: Aluminum alloy Surface: Colorful Type A,B,C,D,E Colorful
9	Rigid Panic Snap Hook Zinc Alloy	SWIVELING STRAP EYE PANIC SNAP RIGID ROUND EYE PANIC SNAP
10	Egg Shaped Snap Hook	Material: SS 316 / 304 / Aluminium Alloy steel Packing: clean poly bags plus cartons plus pallets
11	Pear Shaped Quick Link	Stainless Steel AISI304 or 316 Size : 6-12mm

No	Product	Published Specification Lines
12	Oblique Angle Snap Hook With Eyelet	Size: From 6x60 to 12x120. Material: Carbon steel/Stainless steel 316/304
13	Oblique Angle Snap Hook	Stainless Steel, AISI304 or 316
14	Delta Shaped Quick Link	Stainless Steel AISI304&316 From 3.5mm to 14mm
15	Quick Link, Rapid Links Zinc Plated/Stainless Steel 316/304	SS304-OR-SS316-Steel-Electric-Galvanized Size: 3.5-16
16	S Hook	S Hook, Galvanized or Stainless Steel Specifications Size B C D L N.W. mm mm mm mm mm kgs/100pcs 2.5 6 3 2.5 20 0.17 3 7
17	Welded Round Ring	SS304 OR SS316, Steel Electric Galvanized
18	Aluminium Snap Hook/Carabiner Multi Colors	Type A,B,C,D,E Colorful
19	Cold Shut Chain Link Zinc Plated	Size: From dia 3/16"-1/2". Material: Carbon Steel Surface: Zinc Plated. Packing: Cartons + Pallets
20	Repair Link Chain Lap Zinc Plated	Size: From 3mm-8mm. Material: Carbon Steel/SS304/SS316 Surface: Zinc Plated Packing: Cartons + Pallets
21	Oval Carabiner W/Eyelet Spring Hook With Eyelet	Size: From dia 5mm-12mm. Material: Carbon Steel/SS304/SS316 Surface: Galvanized/Oxide/Spray paint Packing: Cartons + Pal
22	Straight Snap Hook W/Screw	Size: From dia 5mm-11mm. Material: Carbon Steel/SS304/SS316 Surface: Galvanized/Oxide/Spray paint Packing: Cartons + Pal
23	Straight Spring Hook Zinc Plated Oval Snap Hook Carabiner	Straight Spring Hook Supplier in China. Zinc Plated / Stainless Steel Oval Snap Hook Carabiner. Size Dimension(mm) W.L.L
24	Snap Hook With Screw DIN 5299D	Size: From dia 4mm-14mm. Material: Carbon Steel/SS304/SS316 Surface: Galvanized/Oxide/Spray paint Packing: Cartons + Pal
25	Snap Hook With Eyelet DIN 5299A	Snap Hook With Eyelet China Manufacturer and Supplier Detailed introduction: SIZE mm φA B C D F W.L.L LBS 4x40 4 20 40 7
26	Spring Hook with Screw Nut and Eyelet Carabiner	Size: From dia 5mm-14mm. Material: Carbon Steel/SS304/SS316 Surface: Galvanized/Oxide/Spray paint Packing: Cartons + Pal
27	Snap Hook DIN 5299C Carabiner Spring Hooks	Size: From dia 4mm-14mm. Material: Carbon Steel/SS304/SS316 Surface: Galvanized/Oxide/Spray paint Packing: Cartons + Pall
28	EGG Type Snap Hook DIN 5299 B Pear Shaped Spring Hook Carabiners	Size : 5x50 to 12x140

Turnbuckles

No	Product	Published Specification Lines
1	HD Turnbuckle Jaw Jaw, Heavy Duty Turnbuckles	Material: High tensile steel Safety Factor: 5 times Finish: Painted RAL 5013 Temperature Range: -20°C upto +180°C Standar
2	Stainless Steel Turnbuckle H/E, H/H, E/E	Material: Stainless Steel 304/316 Type: Hook & Eye, Hook & Hook, Eye & Eye Process: Forging Size: 4mm-48mm Packing: Cart
3	Aluminum Body Turnbuckle Hook and Eye Alu Closed Body	Material: Aluminum Steel Type: Hook & Eye, Hook & Hook, Eye & Eye Process: Forging Surface: Self Color Size: From 1/4" t
4	Aluminum Turnbuckles Eye and Eye Alu Closed Body	Material: Aluminum Steel Type: Hook & Eye, Hook & Hook, Eye & Eye Process: Forging Surface: Self Color Size: From 1/4" t
5	Aluminum Turnbuckle Hook and Hook Alu Closed Body	Material: Aluminum Steel Type: Hook & Eye, Hook & Hook, Eye & Eye Process: Forging Surface: Self Color Size: From 1/4" t
6	Wire Rope Turnbuckle Commercial Type Malleable Steel	Material: Malleable Iron Type: Hook & Eye, Hook & Hook, Eye & Eye Process: Casting Surface: Electric Galvanized Size: M1
7	Turnbuckles hook and hook Commercial Type Malleable Steel	Material: Malleable Iron Type: Hook & Eye, Hook & Hook, Eye & Eye Process: Casting Surface: Electric Galvanized Size: M1
8	Galvanized Turnbuckle Eye/Eye Commercial Type Malleable Steel	Material: Malleable Iron Type: Hook & Eye, Hook & Hook, Eye & Eye Process: Casting Surface: Electric Galvanized Size: M1

No	Product	Published Specification Lines
9	Turnbuckle Eye to Eye Commercial Type Malleable Steel	Material: Malleable Iron Type: Hook & Eye, Hook & Hook, Eye & Eye Process: Casting Surface: Electric Galvanized Size: M1
10	Turnbuckle M16 Commercial Type Malleable Steel	Material: Malleable Iron Type: Hook & Eye, Hook & Hook, Eye & Eye Process: Casting Surface: Electric Galvanized Size: M1
11	Lifting Turnbuckle DIN 1478 Hook and Hook Pipe Body	Material: Cold-drawn Seamless Steel Tube Type: Jaw End, Eye End, Hook End Process: Drop Forged Surface: Hot Dipped Galva
12	Closed Turnbuckle DIN 1478 Hook and Eye Pipe Body	Material: Cold-drawn Seamless Steel Tube Type: Jaw End, Eye End, Hook End Process: Drop Forged Surface: Hot Dipped Galva
13	Pipe Turnbuckle DIN 1478 Eye and Eye Closed Body	Material: Cold-drawn Seamless Steel Tube Type: Jaw End, Eye End, Hook End Process: Drop Forged Surface: Hot Dipped Galva
14	DIN 1478 Jaw and Jaw Turnbuckle With Closed Pipe Body	Material: Cold-drawn Seamless Steel Tube Type: Jaw End, Eye End, Hook End Process: Drop Forged Surface: Hot Dipped Galva
15	Turnbuckle 12mm JIS Frame Type Open Body Hook Hook	Material: Carbon Steel Type: JIS Frame Process: Drop Forged Surface: Electric Galvanized Size: 6mm-50mm Packing: Cartons
16	Eye Eye Turnbuckle JIS Frame Type Open Body	Material: Carbon Steel Type: JIS Frame Process: Drop Forged Surface: Electric Galvanized Size: 6mm-50mm Packing: Cartons
17	Tension Turnbuckle JIS Frame Type Hook / Eye	Material: Carbon Steel Type: JIS Frame Process: Drop Forged Surface: Electric Galvanized Size: 6mm-50mm Packing: Cartons
18	Turnbuckle Hardware Eye and Eye DIN 1480	Material: Malleable / Carbon / Stainless Steel Type: Eye / Hook / Jaw Size: M6-M48 Surface: Galvanized Process: Forged /
19	Eye and Eye Turnbuckle Malleable Steel DIN 1480	Material: Malleable Steel Type: Eye / Eye Size: M6-M48 Surface: Galvanized Process: Casting Packing: Cartons or Gunny Ba
20	Turnbuckle M20 Hook/Eye/Jaw	Material: Carbon / Malleable / Stainless Steel Type: Hook / Eye / Jaw Size: M6-M48 Surface: Galvanized Process: Forged /
21	Industrial Turnbuckles Hook & Eye	Material: Carbon / Malleable / Stainless Steel Size: M6-M48 Surface: Galvanized Process: Forged / Casting Packing: Carto
22	Hook Hook Turnbuckles Malleable Steel	Material: Malleable Steel Type: Hook / Hook Size: M6-M48 Surface: Galvanized Process: Casting Packing: Cartons or Gunny
23	Turn buckle 16mm DIN1480 Hook & Eye Malleable Type	Material: Malleable Steel Type: DIN 1480 Hook / Eye / Jaw / Stub end Size: M6-M48 Surface: Galvanized Process: Casting P
24	Turn buckle Hardware DIN1480 Hook & Eye Malleable Type	Material: Malleable Steel Type: DIN 1480 Hook / Eye / Jaw / Stub end Size: M6-M48 Surface: Galvanized Process: Casting P
25	China Turnbuckles Leading Manufacturer Eye/ Hook /Jaw	Material: Carbon Steel Q235 Type: Hook / Eye / Jaw / Stub end Size: M6-M48 Surface: Galvanized Process: Forged Packing:
26	Eye Turnbuckle DIN 1480 Forged	Material: Carbon Steel Q235 Type: DIN 1480 Size: M6-M48 Surface: Galvanized Process: Forged Packing: Cartons or Gunny Ba
27	Steel Cable Turnbuckle DIN 1480 Forged Hook and Hook with Locknut	Material: Carbon Steel Q235 Type: DIN 1480 Hook / Eye / Jaw / Stub end Size: M6-M48 Surface: Galvanized Process: Forged
28	DIN1480 Turnbuckle Forged Hook and Hook	Material: Carbon Steel Q235 Type: DIN 1480 Hook / Eye / Jaw / Stub end Size: M6-M48 Surface: Galvanized Process: Forged
29	Hook Hook Turnbuckle DIN1480 Forged	Material: Carbon Steel Q235 Type: DIN 1480 Hook / Eye Size: M6-M48 Surface: Galvanized Process: Forged Packing: Cartons
30	Hook Eye Turnbuckle DIN1480 Forged	Material: Carbon Steel Q235 Type: DIN 1480 Hook / Eye Size: M6-M48 Surface: Galvanized Process: Forged Packing: Cartons
31	Turnbuckle DIN 1480 Forged Hook and Eye	Material: Carbon Steel Q235 Type: DIN 1480 Hook / Eye / Jaw / Stub end Size: M6-M48 Surface: Galvanized Process: Forged
32	Turnbuckle Stub end HG-251 U.S. Federal Specification	Material: Carbon Steel / Stainless Steel Surface: Hot Dipped Galvanized W.L.L: From 400 lbs Tons to 34000 lbs Size: From
33	Eye To Clevis Turnbuckle US Type Drop Forged HG-227	Material: Carbon Steel / Stainless Steel Surface: Hot Dipped Galvanized W.L.L: From 400 lbs Tons to 34000 lbs Size: From

No	Product	Published Specification Lines
34	Jaw Turnbuckle US Type Drop Forged HG-228	Material: Carbon Steel / Stainless Steel Surface: Hot Dipped Galvanized W.L.L: From 400 lbs Tons to 34000 lbs Size: From
35	Crosby HG 228 Jaw Jaw Turnbuckle US Drop Forged	Material: Carbon Steel / Stainless Steel Surface: Hot Dipped Galvanized W.L.L: From 400 lbs Tons to 34000 lbs Size: From
36	Heavy Duty Turnbuckle US Type Jaw to Jaw HG-228	Material: Carbon Steel / Stainless Steel Surface: Hot Dipped Galvanized W.L.L: From 400 lbs Tons to 34000 lbs Size: From
37	Chain Turnbuckle US Type Drop Forged	Material: Carbon Steel/Stainless Steel Surface: Hot Dipped Galvanized Standard: US Type Safety Factor: 5:1 Application:
38	1 2 Turnbuckle US Type Drop Forged Eye to Eye 1/2"	Material: Carbon Steel/Stainless Steel Surface: Hot Dipped Galvanized W.L.L: 2200 lbs Size: 1/2"x 6" / 9"/ 12" Standard:
39	3 8 Turnbuckle US Type Forged Hook/Eye/Jaw	Material: Carbon Steel/Stainless Steel Surface: Hot Dipped Galvanized/SS304/316 W.L.L: 1000 lbs Size: 3/8"x 6 Safety Fact
40	Turnbuckle Hook and Eye Crosby Type HG-225	Material: Carbon Steel (C1045) Surface: Hot Dipped Galvanized W.L.L: From 400 lbs Tons to 34000 lbs Size: From 1/4"x4" t
41	Hook and Hook Turnbuckle Drop Forged HG223	Professional Turnbuckle Supplier in China Material: Carbon Steel Process: Drop Forged Surface: Hot Dipped Galvanized/Gal
42	US Type Drop Forged Turnbuckle Stub end HG-251	Material: Carbon Steel / Stainless Steel Surface: Hot Dipped Galvanized W.L.L: From 400 lbs Tons to 34000 lbs Size: From
43	Jaw And Eye Turnbuckle US Type Drop Forged HG-227	Material: Carbon Steel / Stainless Steel Surface: Hot Dipped Galvanized W.L.L: From 400 lbs Tons to 34000 lbs Size: From
44	Jaw Jaw Turnbuckle US Type Drop Forged HG-228	Material: Carbon Steel / Stainless Steel Surface: Hot Dipped Galvanized W.L.L: From 400 lbs Tons to 34000 lbs Size: From
45	Eye to Eye Turnbuckle US Type Drop Forged HG-226	Material: Carbon Steel/Stainless Steel Surface: Hot Dipped Galvanized W.L.L: From 400 lbs Tons to 34000 lbs Size: From 1
46	Turnbuckle Hook and Hook Drop Forged HG-223	Material: Carbon Steel Process: Drop Forged Surface: Hot Dipped Galvanized, Electric galvanized Safety factor: 5:1 Size:
47	Turnbuckle Hook and Eye US Type HG-225	Material: Carbon Steel (C1045) Surface: Hot Dipped Galvanized W.L.L: From 400 lbs Tons to 34000 lbs Size: From 1/4"x4" t
48	Die Cast Turnbuckle Hook & Eye Zinc Plated	Material: Carbon steel Surface: Electro-Galvanized(Zinc Plated) Size: From 5/32" to 3/8" Processing: Die Casting Applic
49	DIN 1480 Forged Turnbuckle Hook and Eye	Material: Carbon Steel Q235 Type: DIN 1480 Hook / Eye / Jaw / Stub end Size: M6-M48 Surface: Galvanized Process: Forged
50	Hamburger Turnbuckle D-D Turnbuckles	Material: Carbon steel Surface: Hot Dipped Galvanized, Electro Galvanized, Self Color Process: Drop forged, Precision Ca
51	Open Body Turnbuckle JIS Frame Type Forged Steel	Material: Carbon Steel Type: JIS Frame Process: Drop Forged Surface: Electric Galvanized Size: 6mm-50mm Packing: Cartons
52	Korean Type Malleable Turnbuckle m12	Material: Malleable Iron Surface: Electro-Galvanized(Zinc Plated) Size: From 3/16" to 3/4" Standard: Korean Type Brand:
53	Jaw and Jaw Turnbuckle DIN 1478 Rigging Screw Closed Type	Material: Cold-drawn Seamless Steel Tube Type: Jaw End, Eye End, Hook End Process: Drop Forged Surface: Hot Dipped Galva
54	Commercial Type Malleable Steel Turnbuckle	Material: Malleable Iron Type: Hook & Eye, Hook & Hook, Eye & Eye Process: Casting Surface: Electric Galvanized Size: 6m

Wire Rope Clips

No	Product	Published Specification Lines
1	Steel Cable Fasteners Wire Rope Clamp &Thimble; & Sleeve Set- Customizable Packaging	Material: Carbon steel or Stainless steel. Size: All Packing: Customized

No	Product	Published Specification Lines
2	Wire Rope Clamp And Thimble Set Customizable Packaging	Material: Carbon steel or Stainless steel. Size: All Packing: Customized
3	Fist Grip Clamp G-429 US Type Drop Forged Wire Rope Termination	Material : Carbon steel Size: from 3/16"-1/4" to 1 1/8" Processing: Drop Forged Finish : Hot dip galvanized Packing: Car
4	Wire Rope Fastener Cable Clamps Wire rope Clips	Material : Malleable Iron Size: from 1/8" to 1" Processing: Malleable Cast Body, Steel U Bolt Finish: Zinc Plated Packag
5	Steel Rope Clamp A Type Yellow Zinc Galvanzied	Material : Malleable Iron Size: from 6 to 50mm Processing: Malleable Cast Body, Steel U Bolt Finish: Zinc Plated Package
6	Rope Wire Clips A Type Yellow Zinc Galvanzied	Material : Malleable Iron Size: from 6 to 50mm Processing: Malleable Cast Body, Steel U Bolt Finish: Zinc Plated Package
7	1 8 Cable Clamp US Type Malleable Wire Rope Clip	Material : Malleable Iron Size: 1/8" Processing: Casting/Forged Finish: Electro-Galvanized. Package: Cartons then pack o
8	3 8 Cable Clamp US Type Malleable Wire Rope Clip	Material : Malleable Iron Size: 3/8" Processing: Casting/Forged Finish: Electro-Galvanized. Package: Cartons then pack o
9	US Type Drop Forged Wire Rope Clips G 450	Material : Forged Carbon Steel Size: from 1/8" to 3 1/2" Processing: Forged Finish: Hot Dip Galvanised Standard: ASME B3
10	Stainless Steel Cable Clamps DIN 741	Material : Stainless Steel 304/316 Size: from 3mm to 50mm Processing: Malleable Cast Body, Steel U Bolt Finish: Zinc Pla
11	U Clamp For Wire Rope	Material : Malleable Iron Size: from 3mm to 50mm Processing: Malleable Cast Body, Steel U Bolt Finish: Zinc Plated Packa
12	DIN741 Wire Rope Clips Malleable Steel	Material : Malleable Iron Size: from 3mm to 50mm Processing: Malleable Cast Body, Steel U Bolt Finish: Zinc Plated Packa
13	DIN1142 Malleable Steel Rope Clamp	Material : Malleable Iron Size: from 3mm to 40mm Processing: Malleable Cast Body, Steel U Bolt Finish: Zinc Plated Packa
14	Wire Rope Clip DIN1142 Malleable Steel Glavanized	Material : Malleable Iron Size: from 3mm to 40mm Processing: Malleable Cast Body, Steel U Bolt Finish: Zinc Plated Packa
15	Fist Grip G-429 US Type Drop Forged Wire Rope Termination	Material : Carbon steel Size: from 3/16"-1/4" to 1 1/8" Processing: Drop Forged Finish : Hot dip galvanized Packing: Car
16	Wire Rope Grip Italian Type Forged Rope Clip	Material : Carbon steel Size: From 3 to 45mm Processing: Drop Forged Finish : Electric-galvanized, Hot dip galvanized Pa
17	Deka Wire Rope Clip	Material : Malleable Iron Size: from 6mm to 25mm Processing: Casting/Forged Finish: Hot Dip Galvanized, Electro-Galvaniz
18	Malleable Wire Rope Clip US Type	Material : Malleable Iron Size: from 1/8" to 1" Processing: Casting/Forged Finish: Hot Dip Galvanized, Electro-Galvanize
19	Crosby G 450 US Type Drop Forged Wire Rope Clip	Material : Forged Carbon Steel Size: from 1/8" to 3 1/2" Processing: Forged Finish: Hot Dip Galvanised Standard: ASME B3
20	Cable Clamps For Wire Rope Type B Malleable Steel	Material : Malleable Iron Size: from 1/8" to 1" Processing: Malleable Cast Body, Steel U Bolt Finish: Zinc Plated Packag
21	Wire Rope Clips Type A Malleable Steel	Material : Malleable Iron Size: from 6 to 50mm Processing: Malleable Cast Body, Steel U Bolt Finish: Zinc Plated Package
22	Simplex Wire Rope Grip/Single Wire Rope Clip	Material : Carbon Steel Size: from 2 to 10mm Processing: Forged Finish: Zinc Plated Package: Cartons then pack on pallet
23	Duplex Wire Rope Clamp Double Wire Rope Clip	Size: From 2mm to 10mm Cardon steel, Stainless Steel 304 or 316 Surface: Electrical galvanized. Process: Cast & Forged P
24	DIN 741 Wire Rope Clip Malleable Iron	Material : Malleable Iron Size: from 3mm to 50mm Processing: Malleable Cast Body, Steel U Bolt Finish: Zinc Plated Packa
25	DIN 1142 Wire Rope Clip Malleable	Material : Malleable Iron Size: from 3mm to 40mm Processing: Malleable Cast Body, Steel U Bolt Finish: Zinc Plated Packa

Wire Rope Sleeves

No	Product	Published Specification Lines
1	Aluminum Sleeve-Duplex Hourglass Ferrules	Materials: Superior Aluminium Material Processing: Machining + Extruded Size: From 3/64" to 5/8" Application: Eye wire r
2	S505 Steel Swaging Sleeves	For flemish eye wire rope splicing. Designed for low temperature toughness. Resists cracking when swaged (equals or exce
3	Copper Ferrules Oval Type DIN 3093	Material: Copper. Sizes: Available in a range of sizes from 1mm to 20mm wire rope diameters. Finish: Natural copper fini
4	Copper Hourglass Sleeve/ Cooper Wire Rope Sleeve	Material: High-grade copper for corrosion resistance and durability. Size Range: Available for wire ropes ranging from 3
5	Copper Cable Sleeves Round Type, Copper Button Stop	Materials: Superior Copper Processing: Machining + Extruded Size: From 3/64" to 5/16" Application: Eye wire rope splicin
6	DIN 3093 Wire Rope Ferrule/Steel Oval Sleeves	Material: Aluminum / Copper / Stainless Steel, depending on the application and environment. Size Range: Available for w
7	Steel Cable Stops Buttons Sleeves	Materials: Stainless steel 316 or 304 Processing: Machining + Extruded Size: From 1/8" to 1 1/4" Application: Eye wire r
8	Aluminum Stop Buttons/Steel Cable Stops Round Ferrule	Materials: Superior Aluminium Material Processing: Machining + Extruded Size: From 3/64" to 3/8" Application: Eye wire r
9	Aluminium Ferrules DIN3093 / Oval Wire Rope Sleeves	Material: Aluminum Standard: DIN3093 Sizes: Available in a range of sizes to fit different wire rope diameters Applicati
10	Aluminum Crimping Sleeves Duplex 8 Hourglass Ferrules	Materials: Superior Aluminium Material Processing: Machining + Extruded Size: From 3/64" to 5/8" Application: Eye wire r

Wire Rope Thimbles

No	Product	Published Specification Lines
1	Synthetic Rope Thimbles	Material Options: Galvanized Steel, Stainless Steel, Mild Steel Standard: DIN, ASTM, or custom specifications as require
2	Tube Thimble Tube Wire Rope Thimble Without Gusset	Material Options: Galvanized Steel, Stainless Steel, Mild Steel Standard: DIN, ASTM, or custom specifications as require
3	Tubular Thimble With Gusset	Material Options: Galvanized Steel, Stainless Steel, Mild Steel Standard: DIN, ASTM, or custom specifications as require
4	Round Rope Thimbles, Manila Rope Thimble	Material Options: Galvanized Steel, Stainless Steel, Mild Steel Standard: DIN, BS 302. Size Range: From 8mm to 40mm (cus
5	Heavy Duty Thimble G414 US Type	Material Options: Galvanized Steel, Stainless Steel, Mild Steel Standard: US Type G414. Size Range: From 1/8" to 2 1/2"
6	G411 US Type Light Duty Wire Thimble	Material Options: Galvanized Steel, Stainless Steel, Mild Steel Standard: US Type G411. Size Range: From 1/8" to 2 1/2"
7	Wire Rope Thimble European Type	Materials: Galvanized Steel, Stainless Steel. Standard: European. Size Range: Available for wire rope diameters from 3mm
8	Tubular Thimble With Gusset	Material: Carbon steel or Stainless steel. Finish: Galvanized,,Hot dip galvanzied, Powder coated Size: From 10mm to 42mm
9	Tube Wire Rope Thimble Tube wire rope thimble without gusset	Material: Carbon steel or Stainless steel. Finish: Galvanized,,Hot dip galvanzied, Powder coated Size: From 10mm to 140m
10	Synthetic Rope Thimble	Material: Carbon steel or Stainless steel. Finish: Galvanized,,Hot dip galvanzied, Powder coated Size: From Ø 16 to Ø 11
11	Round Rope Thimble	Material: Carbon steel or Stainless steel. Finish: Galvanized,,Hot dip galvanzied, Powder coated Size: From 8mm to 40mm
12	European Type Wire Rope Thimble	Material: Carbon steel or Stainless steel. Finish: Galvanized / HDG / SS304 / SS316 Size: From 4mm to 32mm

No	Product	Published Specification Lines
13	G414 US type heavy duty thimble	Material: Carbon steel or Stainless steel. Finish: Galvanized Size: From 1/8" to 2 1/2"
14	G411 US type light duty thimble	Material: Carbon steel or Stainless steel. Finish: Galvanized Size: From 1/8" to 2 1/2"
15	Din 6899B Wire Rope Thimble	Material: Carbon steel or Stainless steel. Finish: Galvanized Size: From 3mm to 30mm
16	DIN 6899A Wire Rope Thimble	Material: Galvanized steel, stainless steel, or alloy steel. Standard: DIN 6899 Size: Suitable for wire ropes ranging fr

Chains

61 catalogued items. Full page: qd-kailipu.com/categories/chains.html

Chain Assemblies

No	Product	Published Specification Lines
1	Tow Chain V Bridle with Large Shank J Hooks and Grab Hooks WLL 4700 lbs	Grade 70- 4,700 Pound Safe Woking Load Flatbed Truck Trailer Safety Tow Chain
2	Towing Chain Bridle With Forged 4 Inch Mini J Hooks	Grade 70-36 Inch - 4,700 Pound Safe Woking Load
3	V Towing Chain Bridle with 15 Inch and 4 Inch J Hooks, T Hooks - Grade 70 Chain - 47 Inches Long - 4,700 Pound Safe Working Load	Vehicle Service Type ■Truck Load Capacity ■4700 Pounds Fastener Material ■Alloy Steel Fastener Type ■J-Hook Number of Pi

Hardware Chains

No	Product	Published Specification Lines
1	Trailer Safety Chains with S-Hooks	Material Carbon Steel Chain Grade G30 / G43 (Optional) Size 1/4", 3/16", 3/8", 5/16" Length 0.5m - 2m (Customizable) End
2	Custom Grade 30 Safety Chain Assembly: Long Link Galvanized Chain with Bracket (Production per Drawing/Sample)	Material: Carbon Steel, Alloy Steel. Surface Treatment: Hot Dipped Galvanized, Electro-Galvanized, Black Oxide. Standard
3	Gradw 30 Proof Coil Chain NACM2010	Material Options: Carbon Steel, Stainless Steel, Mild Steel Standard: NACM, or custom specifications as required Size Ra
4	GRADE 43 HIGH TEST CHAIN NACM2010	Material: Heat-treated carbon steel Standard: NACM, or custom specifications as required Size Range: From 1/4" to 7/8" (
5	GRADE 30 PROOF COIL CHAIN ASTM80	Technical Notes: ASTM A413 specifications Material: Carbon steel Processing: Welded Surface Finish: Self-color, zinc pla
6	GRADE43 HIGH TEST CHAIN ASTM80	Technical Notes: ASTM A413 specifications Material: Carbon steel Processing: Welded Surface Finish: Self-color, zinc pla
7	DIN5685A/C SHORT LINK / LONG LINK CHAIN	Material: Carbon steel Processing: Welded Straight link and twist link are both available Design factor 2.5 : 1 Surface
8	TWIST LINK CHAIN-NACM2010 MACHINE CHAIN	Material: Carbon steel Processing: Welded Design factor 4 : 1 Surface Finish: Self-color, zinc plated, hot dip galvanize
9	STRAIGHT LINK COIL CHAIN - NACM2010	Material: Carbon steel Processing: Welded Design factor 4 : 1 Surface Finish: Self-color, zinc plated, hot dip galvanize
10	ORDINARY MILD STEEL CHAIN SHORT LINK	Material: Carbon steel Processing: Welded Surface Finish: Self-color, zinc plated, hot dip galvanized. Application: manu
11	ORDINARY MILD STEEL CHAIN MEDIUM LINK	Material: Carbon steel Processing: Welded Surface Finish: Self-color, zinc plated, hot dip galvanized. Application: manu

No	Product	Published Specification Lines
12	ORDINARY MILD STEEL CHAIN LONG LINK	Material: Carbon steel Processing: Welded Surface Finish: Self-color, zinc plated, hot dip galvanized. Application: manu
13	AUSTRALIAN STANDARD SHORT LINK CHAIN	Technical Notes: Conform To Australian Standard Material: Carbon steel Processing: Welded Surface Finish: Self-color fin
14	AUSTRALIAN STANDARD REGULAR LINK CHAIN	Technical Notes: Conform To Australian Standard Material: Carbon steel Processing: Welded Surface Finish: Self-color fin
15	AUSTRALIAN STANDARD LONG LINK CHAIN	Technical Notes: Conform To Australian Standard Material: Carbon steel Processing: Welded Surface Finish: Self-color fin
16	Japanese Standard Chain	Material : Stainless steel 304-A2,316-A4 Size: From 2mm to 12mm Processing: Casting/Forged Surface Treatment: Electro po

Lifting Chains

No	Product	Published Specification Lines
1	EN818-2 LIFTING CHAIN, GRADE 80 SHORT LINK CHAIN	Technical Notes: Conform To EN818-2 Material: The highest quality alloy steel Processing: Welded Surface Finish: Black/H
2	GRADE T (80) HOIST CHAIN TYPE T EN818-7	Technical Notes: Conform To EN818-7 Material: The highest quality alloy steel Processing: Welded Surface Finish: Electro
3	GRADE T (80) SHORT LINK CHAIN AS2321	Technical Notes: Conform To AS2321 Material: The highest quality alloy steel Processing: Welded Surface Finish: Electrop
4	GRADE V SHORT LINK CHAIN AS2321	Technical Notes: Conform To AS 2321 Material: The highest quality alloy steel Processing: Welded Surface Finish: Electro
5	GRADE 100 ALLOY CHAIN ASTM973	Technical Notes: Conform To ASTM973 Material: The highest quality alloy steel Processing: Welded Surface Finish: Electro
6	GRADE 100 ALLOY CHAIN NACM2010	Technical Notes: Conform To NACM2010 Material: The highest quality alloy steel Processing: Welded Surface Finish: Electr
7	GRADE 80 ALLOY CHAIN NACM2010	Technical Notes: Conform To NACM2010 Material: The highest quality alloy steel Processing: Welded Surface Finish: Electr

Marine Chains

No	Product	Published Specification Lines
1	Lugless Joining Shackle - Kenter Link - End Shackle -Swivel Set	Grade: U2 or U3 Size: From 12.5mm to 162mm Color: Silver,Black,Steel color Process: Welded Surface: Hot dip galvanized,G
2	Kenter Link - Joining / End Shackle -Swivel Set	Grade: U2 or U3 Size: From 12.5mm to 162mm Color: Silver,Black,Steel color Process: Welded Surface: Hot dip galvanized,G
3	Kenter Shackle - Anchor Chain Fittings	Grade: U2 or U3 Size: From 12.5mm to 162mm Color: Silver,Black,Steel color Process: Welded Surface: Hot dip galvanized,G
4	STUDLESS ANCHOR CHAIN	Material: Hot-rolled anchor steel, CM490, CM690, stainless steel 316, 316L Grade: R3, R4, R5 Chain Diameter: 68mm to 205
5	STUD LINK ANCHOR CHAIN	Material: Hot-rolled anchor steel, CM490, CM690, stainless steel 316, 316L Grade: U2, U3 Chain Diameter: 13mm to 152mm F
6	DIN763 LONG LINK CHAIN	Material: Carbon steel Processing: Welded Surface Finish: hot dip galvanized, electro-galvanized or self-color Ultimate
7	DIN 764 LINK CHAIN	Material: Carbon steel Processing: Welded Surface Finish: hot dip galvanized, electro-galvanized or self-color Ultimate
8	DIN766 SHORT LINK CHAIN GRADE 3	Material: Carbon steel Processing: Welded Surface Finish: Painting, hot dip galvanized Ultimate load is at least 4 times
9	MOORING CHAIN HOT DIP GALVANIZED GRADE 43	Material: Carbon steel Processing: Welded Surface Finish: Painting, hot dip galvanized Ultimate load is at least 4 times

Mining Chains

No	Product	Published Specification Lines
1	Mining Flat Chain Link Chainlock DIN 22258	Application: Mine Cart Connection Material: High quality alloy steel Manufacturing standards: ISO, DIN, BS, MT, etc.
2	Mining Chain Connectors Flat Sawtooth Chainlock	Application: Mine Cart Connection Material: High quality alloy steel Manufacturing standards: ISO, DIN, BS, MT, etc.
3	Mining Chain Connector With Flat Arc Tooth CC Series Chainlock	Application: Mine Cart Connection Material: High quality alloy steel Manufacturing standards: ISO, DIN, BS, MT, etc.
4	Round Link Double Bolt Shackle	Application: Mine Cart Connection Material: High quality alloy steel Manufacturing standards: ISO, DIN, BS, MT, etc. Str
5	Twin Outboard Chain Shackle, Round Link Single Bolt Shackle	Application: Mine Cart Connection Material: High quality alloy steel Manufacturing standards: ISO, DIN, BS, MT, etc. Str
6	Coal Mine Car Three Ring Chain For Narrow Gauge Railway Vehicles	Application: Mine Cart Connection Material: High quality alloy steel Manufacturing standards: ISO, DIN, BS, MT, etc. Str
7	Mining Compact Chain High Strength Mining Flat Chains	High Tension Mining Compact Chain The mining compact chain is a mining chain that alternately consists of welded circula
8	High Tension Round Link Chain For Mining	Standard: GB/T12718-2009 Quality grade: C
9	High Tension Round Link Mining Chain	Standard: GB/T12718-2009 Quality grade: B

Tie Down Chains

No	Product	Published Specification Lines
1	GRADE 43 CHAIN ASTM SHORT LINK BINDER CHAIN	Technical Notes: Conform To ASTM specifications Material: Carbon steel Processing: Welded Surface Finish: Self-color fin
2	GRADE 43 CHAIN NACM	Technical Notes: Conform To NACM specifications Material: Carbon steel Processing: Welded Surface Finish: Self-color fin
3	GRADE 70 TRANSPORT CHAIN NACM2010	Technical Notes: Conform To NACM specifications Material: Alloy steel Processing: Welded Surface Finish: Yellow chromate
4	GRADE 70 SHORT LINK TRANSPORT CHAIN ASTM A413	Technical Notes: Conform To ASTM A413 specifications Material: Alloy steel Processing: Welded Surface Finish: Yellow chr
5	GRADE 70 TRANSPORT CHAIN AS4344	Technical Notes: Conform To Australian Standard 4344 Material: Alloy steel Processing: Welded Surface Finish: Yellow chr

Tire Chains

No	Product	Published Specification Lines
1	Double Loop Chain Style	Usage : Can be used as decorative fitting Size: 1.6mm to 4.9mm Surface: white or blue zinc Package: plastic reel,30m/ree

Towing and Recovery Chains

No	Product	Published Specification Lines
1	Grade 70 Towing Chain with 15 Inch J Hook, T-Hook & Grab Hook	Chain Grade: Grade 70 / G70 Transport Chain Size: 5/16 inch Chain Length: 2.4 m (Approx. 8 ft) End Hook 1: 15" Eye Style
2	Grade 43 Trailer Safety Chain with Clevis Slip Hook	Chain Grade: Grade 43 / High Test Chain Material: Carbon Steel Hook Type: Clevis Slip Hook Surface Finish: Zinc Plated /
3	Grade 70 Trailer Safety Chain with Clevis Slip Hook, Heavy Duty Transport Towing Chain	Size: 1/4" , 5/16" , 3/8". Chain Length: 35" Working Load Limit: 4,700 lbs, 6,250 lbs, 6,600 lbs. Breaking Strength: 18,8

No	Product	Published Specification Lines
4	Grade 70 Chain Extension with Pear Link & Eye Grab Hook Chain Anchor with Pear Link	Length: 18.5 inches Components: G70 Forged Grab Hook + Pear Link Working Load Limit (WLL): 5,400 lbs Breaking Strength:
5	G70 Chain Extension with Delta Ring and Eye Grab Hook - Car Hauler Tie-Down	Size: 3" 5/16", 4" 3/8". Length: 18" (For full assembly) Working Load Limit: 3667 / 6600 lbs Breaking Strength on 3/8" C

Weldless Chains

No	Product	Published Specification Lines
1	DECORATOR CHAIN	Material: Carbon steel Surface: Different finishes Application: A decorative chain for hanging plants, lamps, flower pot
2	SASH CHAIN	Material: Carbon steel Surface: zinc plated finish, Copper plated finish Type: US type NACM Standard Application: Used f
3	SINGLE JACK CHAIN	Material: Carbon steel Surface: zinc plated finish, Copper plated finish, Polycoated. Type: US type NACM Standard Applic
4	PLASTIC CHAIN	PLASTIC CHAIN TRADE SIZE INSIDE LENGTH OUTSIDE WIDTH mm mm mm 6 25 20 6 41 20 8 39 27 8 50 26 Plastic chain colors are a
5	DIN5686 KNOTTED CHAIN	Material: Carbon steel Processing: Weldless Surface Finish: Self-color finish, zinc plated finish, hot dip galvanized fi
6	DOUBLE LOOP CHAIN US TYPE NACM STANDARD	Material: Carbon Steel Surface: Zinc Plated, Galvanized Type: US type NACM Standard Application: Swing sets, animal chai

Webbing Slings

60 catalogued items. Full page: qd-kailipu.com/categories/webbing-sling.html

Endless Slings

No	Product	Published Specification Lines
1	1T Endless Webbing Sling/Endless Polyester lifting slings	◆ Material:100% High tenacity industrial polyester yarn ◆ Working Load Limit: 1000kg ◆ Colour: Violet ◆ Safety Factor av
2	2T Endless Webbing Sling/Endless Polyester lifting slings	◆ Material:100% High tenacity industrial polyester yarn ◆ Working Load Limit: 2000kg ◆ Colour: Green ◆ Safety Factor ava
3	3T Endless Webbing Sling/Endless Polyester lifting slings	◆ Material:100% High tenacity industrial polyester yarn ◆ Working Load Limit: 3000kg ◆ Colour: Yellow ◆ Safety Factor av
4	4T Endless Webbing Sling/Endless Polyester lifting slings	◆ Material:100% High tenacity industrial polyester yarn ◆ Working Load Limit: 4000kg ◆ Colour: Grey ◆ Safety Factor avai
5	5T Endless Webbing Sling/Endless Polyester lifting slings	◆ Material:100% High tenacity industrial polyester yarn ◆ Working Load Limit: 5000kg ◆ Colour: Red ◆ Safety Factor avail
6	6T Endless Webbing Sling/Endless Polyester lifting slings	◆ Material:100% High tenacity industrial polyester yarn ◆ Working Load Limit: 6000kg ◆ Colour: Brown ◆ Safety Factor ava
7	Single Layer Endless Webbing Sling	Material: 100% Polyester / Nylon Safety Factor: 5:1 6:1 7:1 8:1 Ply; one ply to four ply Length/Color: As required Stand

Eye and Eye Round Slings

No	Product	Published Specification Lines
1	Soft Slings Eye And Eye Flexible Round Type 10T-500T	Round slings are Specification ◆ Material:100% High tenacity industrial polyester yarn ◆ Inner core:made of 60000D twist

No	Product	Published Specification Lines
2	Lifting Webbing Sling Eye And Eye Flexible Round Type 8T, Blue	Round slings are Specification ♦ Material:100% High tenacity industrial polyester yarn ♦ Inner core:made of 60000D twiste
3	Web Slings For Lifting Eye And Eye Flexible Round Type 6T, Brown	Round slings are Specification ♦ Material:100% High tenacity industrial polyester yarn ♦ Inner core:made of 60000D twiste
4	Webbing Sling Eye And Eye 5T, Flexible Eye Round Sling Red	Round slings are Specification ♦ Material:100% High tenacity industrial polyester yarn ♦ Inner core:made of 60000D twiste
5	Eye And Eye Slings 4T, Flexible Round Sling Eye Grey Color	Round slings are Specification ♦ Material:100% High tenacity industrial polyester yarn ♦ Inner core:made of 60000D twiste
6	Eye To Eye Slings 3T, Flexible Round Sling Eye & Eye Yellow Color	Round slings are Specification ♦ Material:100% High tenacity industrial polyester yarn ♦ Inner core:made of 60000D twiste
7	Round Sling Eye & Eye 1T	Round slings are Specification ♦ Material:100% High tenacity industrial polyester yarn ♦ Inner core:made of 60000D twiste
8	Eye and Eye Round Sling 2T Polyester Green Color	Round slings are Specification ♦ Material:100% High tenacity industrial polyester yarn ♦ Inner core:made of 60000D twiste

Flat Webbing Slings

No	Product	Published Specification Lines
1	Webbing Sling 1 ton, Polyester Flat Eye, Violet	Specification ♦ Material:100% High tenacity industrial polyester yarn ♦ Color:Violet ♦ Working Load:1000 kg ♦ Ply: Double
2	Flat Woven Webbing Sling 2 ton, Green, Custom length	Specification ♦ Material:100% High tenacity industrial polyester yarn ♦ Color:Green ♦ Working Load:2000 kg ♦ Ply: Double
3	Webbing Sling 3 Ton Flat Woven Polyester Eye & Eye	Specification ♦ Material:100% High tenacity industrial polyester yarn ♦ Color:Yellow ♦ Working Load:3000 kg ♦ Ply: Double
4	Webbing Sling 4 Ton Flat Woven Eye & Eye Custom length	Specification ♦ Material:100% High tenacity industrial polyester yarn ♦ Color:Red ♦ Working Load:4000 kg ♦ Ply: Double ♦
5	Webbing Sling 5 Ton Flat Woven Polyester Eye & Eye	Specification ♦ Material:100% High tenacity industrial polyester yarn ♦ Color: Red ♦ Working Load: 5000 kg ♦ Ply: Double
6	Webbing Sling 6 Ton	♦ Material:100% High tenacity industrial polyester yarn ♦ Color: Brown ♦ Working Load:6000 kg ♦ Ply: Double ♦ With reinfo
7	8T Webbing Sling	♦ Material:100% High tenacity industrial polyester yarn ♦ Color: Blue ♦ Working Load: 8000 kg ♦ Ply: Double ♦ With reinfo
8	10T Webbing Sling	♦ Material:100% High tenacity industrial polyester yarn ♦ Color: Orange ♦ Working Load:10000 kg ♦ Ply: Double ♦ With rein
9	12T Webbing Sling	♦ Material:100% High tenacity industrial polyester yarn ♦ Color:Orange ♦ Working Load:12000 kg ♦ Ply: Double ♦ With reinf

Polyester Webbing Belt

No	Product	Published Specification Lines
1	1T Polyester Webbing For Web Sling	♦ Material:100% High tenacity industrial polyester yarn ♦ WLL: 1T ♦ Color: Violet ♦ Packing: 100m per roll, 3 rolls per
2	2T Polyester Webbing For Web Sling	♦ Material:100% High tenacity industrial polyester yarn ♦ WLL: 2T ♦ Color: Green ♦ Packing: 100m per roll, 2 rolls per c
3	3T Polyester Webbing For Web Sling	♦ Material:100% High tenacity industrial polyester yarn ♦ WLL: 3T ♦ Color: Yellow ♦ Packing: 100m per roll, 2 rolls per
4	4T Polyester Webbing For Web Sling	♦ Material:100% High tenacity industrial polyester yarn ♦ WLL: 4T ♦ Color: Grey ♦ Packing: 100m per roll, 1 roll per car
5	5T Polyester Webbing For Web Sling	♦ Material:100% High tenacity industrial polyester yarn ♦ WLL: 5T ♦ Color: Red ♦ Packing: 100m per roll, 1 roll per cart

No	Product	Published Specification Lines
6	6T Polyester Webbing For Web Sling	◆ Material:100% High tenacity industrial polyester yarn ◆ WLL: 6T ◆ Color: Brown ◆ Packing: 100m per roll, 1 roll per ca
7	8T Polyester Webbing For Web Sling	◆ Material:100% High tenacity industrial polyester yarn ◆ WLL: 8T ◆ Color: Blue ◆ Packing: Bulk in carton ◆ Safety Facto
8	10T Polyester Webbing For Web Sling	◆ Material:100% High tenacity industrial polyester yarn ◆ WLL: 10T ◆ Color: Orange ◆ Packing: Bulk in carton ◆ Safety Fa
9	Webbing For Ratchet Tie Down 25mm/1" B.S.800/1000/1500kg	◆ Material:100% High tenacity industrial polyester yarn ◆ Width:25mm/1" Color:Yellow/Blue/Orange/Green ◆ Packing: 100m p
10	Webbing For Ratchet Tie Down 35mm/1.5" B.S.2000Kg	◆ Material:100% High tenacity industrial polyester yarn ◆ Width:35mm Color:Yellow/Orange ◆ Packing: 100m per roll, 3 rol
11	Webbing For Ratchet Tie Down 38mm/1.5" B.S.3000Kg	◆ Material:100% High tenacity industrial polyester yarn ◆ Width:38mm/1.5" Color:Yellow/Orange ◆ Packing: 100m per roll,
12	Tie Down Webbing 50mm*6000LBS European Standard Lashing webbing	◆ Material:100% High tenacity industrial polyester yarn ◆ Width:50mm Color:Yellow/Orange/Red/Blue ◆ Packing: 100m per ro
13	Tie Down Webbing 50mm*7500LBS European Standard Lashing webbing	◆ Material:100% High tenacity industrial polyester yarn ◆ Width:50mm Color:Yellow/Orange/Red/Blue ◆ Packing: 100m per ro
14	Ratchet Tie Down Webbing For 50mm/2" 10000lbs	◆ Material:100% High tenacity industrial polyester yarn ◆ Width:50mm/2" Color: Yellow ◆ Packing: 100m per roll, 2 rolls
15	Ratchet Tie Down Webbing For 75mm/3" 16200lbs	◆ Material:100% High tenacity industrial polyester yarn ◆ Width:75mm/3" Color: Yellow ◆ Packing: 100m per roll, 2 rolls
16	Ratchet Tie Down Webbing For 100mm/4" 16200lbs/22000lbs	◆ Material:100% High tenacity industrial polyester yarn ◆ Width:100mm/4" Color: Yellow ◆ Packing: 100m per roll, 2 rolls
17	Lashing Webbing For 102mm/4" 20000lbs Tie Down USA Standard	◆ Material:100% High tenacity industrial polyester yarn ◆ Width:102mm/4" ◆ Webbing Breaking Strength: 20000lbs ◆ Color:
18	Lashing Webbing For 51mm/2" 12000lbs Tie Down USA Standard	◆ Material:100% High tenacity industrial polyester yarn ◆ Width:51mm/2" ◆ Webbing Breaking Strength: 12000lbs ◆ Color: Y
19	USA Standard Tie Down Webbing for 51mm/2" ratchet Lashing	Specification ◆ Material:100% High tenacity industrial polyester yarn ◆ Width:51mm/2" ◆ Webbing Breaking Strength: 6000l
20	Polyester Webbing Used for 50mm/2" Ratchet Tie Down	Specification ◆ Material:100% High tenacity industrial polyester yarn ◆ Width : 50mm/2" Color: Yellow ◆ Packing: 100m pe
21	Cargo Lashing Strap Webbing US Type	Specification ◆ Material:100% High tenacity industrial polyester yarn ◆ Width:100mm/4" Color: Yellow ◆ Packing: 100m per
22	European Standard Tie Down Webbing/Lashing webbing	Specification ◆ Material:100% High tenacity industrial polyester yarn ◆ Width:50mm Color:Yellow/Orange/Red/Blue ◆ Packin
23	USA Standard Tie Down Webbing/Lashing webbing	Specification Material:100% High tenacity industrial polyester yarn Width: From 25mm-100mm Color: Yellow Packing: 100yd
24	Polyester round sling sleeve/European Single Wall Sleeve	Specification ◆ Material:100% High tenacity industrial polyester yarn
25	Polyester round sling sleeve/European Double Wall Sleeve	Specification ◆ Material:100% High tenacity industrial polyester yarn
26	Lashing Webbing Material	Material: 100% Polyester / Nylon Safety Factor: 6:1 7:1 8:1 As you required Lengh/Color: As you required Standard: ISO4
27	Sling Webbing Material	Material: 100% Polyester / Nylon Safety Factor: 5:1 6:1 7:1 8:1 Length: 3000 meters continuous without disconnection for

Round Slings

No	Product	Published Specification Lines
1	Round Webbing Sling 1T Polyester Round Sling/Soft Flexible Lifting Sling	Specification ◆ Material:100% High tenacity industial polyester yarn ◆ Inner core:made of 60000D twisted polyester yarn

No	Product	Published Specification Lines
2	Endless Round Webbing Sling 2T Soft Flexible Lifting Sling	Specification ♦ Material:100% High tenacity industrial polyester yarn ♦ Inner core:made of 60000D twisted polyester yarn
3	Round Sling Rigging 3T	Specification ♦ Material:100% High tenacity industrial polyester yarn ♦ Inner core:made of 60000D twisted polyester yarn
4	Endless Roundslings 4T Round Lifting Sling	Specification ♦ Material:100% High tenacity industrial polyester yarn ♦ Inner core:made of 60000D twisted polyester yarn
5	Synthetic Round Sling 5T	Specification ♦ Material:100% High tenacity industrial polyester yarn ♦ Inner core:made of 60000D twisted polyester yarn
6	Polyester Round Sling 6T	Specification ♦ Material:100% High tenacity industrial polyester yarn ♦ Inner core:made of 60000D twisted polyester yarn
7	8T Synthetic Round slings	Specification ♦ Material:100% High tenacity industrial polyester yarn ♦ Inner core:made of 60000D twisted polyester yarn
8	Polyester Round Slings 10T	Specification ♦ Material:100% High tenacity industrial polyester yarn ♦ Inner core:made of 60000D twisted polyester yarn
9	EN1492 2 Round Lifting Sling, Flexible Round Slings	Material:100% High tenacity industrial polyester yarn Working Load: 1T-1000T Safety Factor: 5:1, 6:1, 7:1, 8:1 Outer sleeve

Ratchet Straps

67 catalogued items. Full page: qd-kailipu.com/categories/tie-down-strap.html

Ratchet Tie Downs

No	Product	Published Specification Lines
1	50mm 5000kgs Ratchet Tie Down with Alu. handle and Doube J Hook	♦ Width:50mm ♦ Webbing Breaking Strength:6400kg ♦ Working Load:2500 kg ♦ Assembly Breaking Strength:5000 kg ♦ Safety Fac
2	50mm 5000kg Ratchet Tie Down with Rubber Handle and Flat Hook	♦ Width:50mm ♦ Webbing Breaking Strength:6400kg ♦ Working Load:2500 kg ♦ Assembly Breaking Strength:5000 kg ♦ Safety Fac
3	50mm Ergo Ratchet Tie Down LC 2500KG	♦ Width:50mm ♦ Webbing Breaking Strength:6400kg ♦ Working Load:2500 kg ♦ Assembly Breaking Strength:5000 kg ♦ Safety Fac
4	75mm 7500kg Ratchet Tie Down with Flat Hook	♦ Width:75mm ♦ Webbing Breaking Strength:9600kg ♦ Working Load:3750kg ♦ Assembly Breaking Strength:7500kg ♦ Safety Facto
5	100mm 10000kg Ratchet Tie Down	♦ Width:100mm ♦ Webbing Breaking Strength:12800kg ♦ Working Load:5000kg ♦ Assembly Breaking Strength:10000kg ♦ Safety Fa
6	25mm 800kg Ratchet Tie Down European Type	♦ Width:25mm ♦ Webbing Breaking Strength:1000kg ♦ Working Load:400 kg ♦ Assembly Breaking Strength:800 kg ♦ Safety Facto
7	25mm 1000kg Ratchet Tie Down European Type	♦ Width:25mm ♦ Webbing Breaking Strength:1250kg ♦ Working Load:500 kg ♦ Assembly Breaking Strength:1000 kg ♦ Safety Fact
8	25mm 1000kg Ratchet Tie Down with Swan Hook and Keeper	♦ Width:25mm ♦ Webbing Breaking Strength:1800kg ♦ Working Load:750 kg ♦ Assembly Breaking Strength:1500 kg ♦ Safety Fact
9	25mm 1500kg Ratchet Tie Down European Type	♦ Width:25mm ♦ Assembly Breaking Strength:1500 kg ♦ Safety Factor:2:1 ♦ Webbing Color:Yellow/Orange/Blue/Green ♦ Ratchet
10	35mm 2000kg Ratchet Tie Down European Type	♦ Width:35mm ♦ Webbing Breaking Strength:2600kg ♦ Working Load:1000 kg ♦ Assembly Breaking Strength:2000 kg ♦ Safety Fac
11	38mm 3000kg Ratchet Tie Down European Type	♦ Width:38mm ♦ Webbing Breaking Strength:3900kg ♦ Working Load:1500 kg ♦ Assembly Breaking Strength:3000 kg ♦ Safety Fac
12	1" Ratchet Strap with S Hooks	♦ Width:1" ♦ Webbing Breaking Strength:2600 lbs ♦ Working Load:800 lbs ♦ Assembly Breaking Strength:2200 lbs ♦ Safety Fa

No	Product	Published Specification Lines
13	1"Thumb Ratchet Strap w/ Wire Hooks	◆ Width:1" ◆ Webbing Breaking Strength:2600 lbs ◆ Working Load:800 lbs ◆ Assembly Breaking Strength:2200 lbs ◆ Safety Fa
14	1" Endless Ratchet Strap	◆ Width:1" ◆ Webbing Breaking Strength:2600 lbs ◆ Working Load:800 lbs ◆ Assembly Breaking Strength:2200 lbs ◆ Safety Fa
15	1" Cam Buckle Strap with S-Hooks	◆ Width:1" ◆ Webbing Breaking Strength:2600 lbs ◆ Working Load:800 lbs ◆ Assembly Breaking Strength:2200 lbs ◆ Safety Fa
16	1" Ratchet Strap with Flat Snap Hooks	◆ Width:1" ◆ Webbing Breaking Strength:4000 lbs ◆ Working Load:1000 lbs ◆ Assembly Breaking Strength:3000 lbs ◆ Safety F
17	1" Ratchet Strap with Wire Hooks Light Duty	◆ Width:1" ◆ Webbing Breaking Strength:4000 lbs ◆ Working Load:1000 lbs ◆ Assembly Breaking Strength:3000 lbs ◆ Safety F
18	2" Ratchet Strap w/ Wire Hooks/Double J Hooks	◆ Width:2" (stenciled) ◆ Webbing Breaking Strength:12000 lbs ◆ Working Load:3300 lbs ◆ Assembly Breaking Strength:10000
19	2" Ratchet Strap with Black Flat Hook	◆ Width:2" (stenciled) ◆ Webbing Breaking Strength:12000 lbs ◆ Working Load:3300 lbs ◆ Assembly Breaking Strength:10000
20	2" Ratchet Strap with Chain Extension	Width:2" Webbing Breaking Strength:12000 lbs Working Load:3300 lbs Assembly Breaking Strength:10000 lbs Safety Factor:3:
21	2" Ratchet Strap with Twisted Flat Snap Hooks	◆ Width:2" ◆ Webbing Breaking Strength:12000 lbs ◆ Working Load:3300 lbs ◆ Assembly Breaking Strength:10000 lbs ◆ Safety
22	2" Endless Ratchet Strap	◆ Width:2" ◆ Webbing Breaking Strength:6000 lbs ◆ Working Load:1467 lbs ◆ Assembly Breaking Strength:4400 lbs ◆ Safety F
23	2" E Track Ratchet Straps w/ Spring E-Fittings	◆ Width:2" ◆ Webbing Breaking Strength:6000 lbs ◆ Working Load:1467 lbs ◆ Assembly Breaking Strength:4400 lbs ◆ Safety F
24	E-Track Tie Down Straps - Cam Buckle■E-Track Cam Straps	◆ Width:2" ◆ Webbing Breaking Strength:6000 lbs ◆ Working Load:1467 lbs ◆ Assembly Breaking Strength:4400 lbs ◆ Safety F
25	E Track Rope Tie Off 2"x6"	◆ Width:2" ◆ Webbing Breaking Strength:6000 lbs ◆ Working Load:1467 lbs ◆ Assembly Breaking Strength:4400 lbs ◆ Safety F
26	3" Ratchet Strap with Chain Extension	◆ Width:3" ◆ Webbing Breaking Strength:20000 lbs ◆ Working Load:5400 lbs ◆ Assembly Breaking Strength:16200 lbs ◆ Safety
27	4" Ratchet Straps with Flat Hooks	◆ Width:4" ◆ Webbing Breaking Strength:25000 lbs ◆ Working Load:7300 lbs ◆ Assembly Breaking Strength:22000 lbs ◆ Safety
28	Ratchet Strap	Strap Material: 100% Polyester Safety Factor: 2:1 or 3:1 Length/Color: As required Certificate: CE/GS Standard: EN 12195

Tie Down Hardware

No	Product	Published Specification Lines
1	DOUBLE J HOOK	Available Size: 4" DOUBLE J HOOK, BS:10000KG/22000LBS 3" DOUBLE J HOOK, BS:10000KG/22000LBS 2" DOUBLE J HOOK, BS:5000KG/
2	2 "DOUBLE J HOOK WITH TUBE	Available Size: 2" BS:5000KG/11000LBS
3	SINGLE J HOOK WITH TUBE	Available Size: 2"SINGLE J HOOK WITH TUBE BS:5000KG/11000LBS 2" SINGLE J HOOK BS:3000KG/6600LBS
4	SINGLE J HOOK	Available Size: 2" SINGLE J HOOK BS:3000KG/6600LBS 1.5" SINGLE J HOOK BS:3000KG/6600LBS 1"SINGLE JHOOK BS:800KG/1760LBS
5	2" DOUBLE J HOOK WITH LACTH	Available Size: 2" BS:5000KG/11000LBS
6	HOOK WITH KEEPER	Available Size: 3"HOOK WITH KEEPER BS:10000KG/22000LBS 1.5"HOOK WITH KEEPER BS:3000KG/6600LBS
7	WELDED J HOOK	Available Size: 2"WELDED J HOOK BS:5000KG/11000LBS 1.5"WELDED HOOK BS:3000KG/6600LBS
8	DOUBLE S HOOK	Available Size: BS:800KG/1760LBS

No	Product	Published Specification Lines
9	SWIVEL J HOOK	Available Size: 2" U HOOK BS:10000KG/22000LBS 2" U HOOK BS:5000KG/11000LBS 2" U HOOK BS:5000KG/11000LBS 3000KG/6600LBS
10	2" U HOOK	Available Size: 2" U HOOK BS:10000KG/22000LBS 2" U HOOK BS:5000KG/11000LBS 2" U HOOK BS:5000KG/11000LBS 3000KG/6600LBS
11	FLAT HOOK	Available Size: 4" FLAT HOOK, BS:8000KG/17600LBS 3" FLAT HOOK, BS:8000KG/17600LBS 2" FLAT HOOK, BS:5000KG/11000LBS 2" FL
12	S HOOK 1"	Available Size: BS:800KG/1760LBS 1500KG/3300LBS
13	S HOOK W/LATCH 1"	Available Size: 1" S HOOK BS:800KG/1760LBS 1500KG/3300LBS
14	2" E HOOK	Available Size: 2" 1500Kg
15	Sider Hook 2"	Available Size: 2" 3000Kg
16	2" STEEL DELTA RING	Available Size: 2" 5000Kg 2" 3000Kg
17	Welded Strap D-Ring	Available Size: 2" 5000Kg 2" 3000Kg 1.5" 1500Kg 1" 750Kg
18	FORGED BUCKLE 50MM	-High strength steel -Zinc coated surface -Forged -Compatible to 50mm lashing webbing or strap -BS:5000KG/11000LBS
19	WELDED BUCKLE 40mm/50mm	-High strength steel -Zinc coated surface -Welded join -Compatible to 40mm and 50mm lashing webbing or strap -Weight: 36
20	1/2" CAM BUCKLE 001	1/2" CAM BUCKLE BS:110KG/220LBS A=13 B=12 C=25
21	1" CAM BUCKLE 002	1" CAM BUCKLE BS:200KG/440LBS A=26 B=17 C=44
22	1" CAM BUCKLE 003	1" CAM BUCKLE BS:250KG/550LBS A=26 B=12 C=45
23	1" CAM BUCKLE 004	1" CAM BUCKLE BS:350KG/770LBS A=26 B=15 C=50
24	1" CAM BUCKLE 005	1" CAM BUCKLE BS:400KG/880LBS A=26 B=15 C=50
25	1" CAM BUCKLE 006	1" CAM BUCKLE BS:400KG/880LBS A=26 B=15 C=50
26	1" CAM BUCKLE 007	1" /25mm CAM BUCKLE BS:500KG/1100LBS A=26 B=16 C=50
27	1" CAM BUCKLE 008	1" CAM BUCKLE BS:600KG/1320LBS A=28 B=25 C=65
28	2" CAM BUCKLE 009	2" CAM BUCKLE BS:900KG/1980LBS A=52 B=28 C=75
29	1" CAM BUCKLE 010	1" CAM BUCKLE BS:700KG/1540LBS A=26 B=28 C=57
30	1.5" CAM BUCKLE 011	1.5" CAM BUCKLE BS:900KG/1980LBS 700KG/1540LBS A=38 B=25 C=70
31	2" CAM BUCKLE 012	2" CAM BUCKLE BS:1100KG/2420LBS A=52 B=28 C=75
32	Double J Hooks	Double J hook DJH-- -10Tx10mm DJH-- -10Tx75mm DJH-- -5Tx50mm DJH-- -5Tx50mm with Hook Keeper DJH-- -4Tx50mm DJH-- -3Tx50
33	Ratchet buckle	10101 --10Tx100mm 75101 --10Tx75mm 50501 --5Tx50mm,plastic handle 50502 --5Tx50mm.Aluminum handle 50512 --5Tx50mm, Ergo

Winch and Tow Straps

No	Product	Published Specification Lines
1	Lasso Strap with O Ring 2" x 10'	◆ Width:2" ◆ Webbing Breaking Strength:12000 lbs ◆ Working Load:3333lbs ◆ Assembly Breaking Strength:10000 lbs ◆ Webbing
2	4" Winch Strap with Chain Extension	◆ Width:4" ◆ Webbing Breaking Strength:25000 lbs ◆ Working Load:7300 lbs ◆ Assembly Breaking Strength:22000 lbs ◆ Safety
3	4" Flat Hook Winch Straps	◆ Width:4" ◆ Webbing Breaking Strength:25000 lbs ◆ Working Load:7300 lbs ◆ Assembly Breaking Strength:22000 lbs ◆ Safety

No	Product	Published Specification Lines
4	4" Winch Strap w/ Double J hook	◆ Width:4" ◆ Webbing Breaking Strength:25000 lbs ◆ Working Load:7300 lbs ◆ Assembly Breaking Strength:22000 lbs ◆ Safety
5	4" Winch Strap with Delta Ring	◆ Width:4" ◆ Webbing Breaking Strength:25000 lbs ◆ Working Load:7300 lbs ◆ Assembly Breaking Strength:22000 lbs ◆ Safety
6	4" Winch Strap with Twisted Loop	◆ Width:4" ◆ Webbing Breaking Strength:25000 lbs ◆ Working Load:7300 lbs ◆ Assembly Breaking Strength:22000 lbs ◆ Safety

Trailer Winches

8 catalogued items. Full page: qd-kailipu.com/categories/truck-winches.html

Bolt-On Winches

No	Product	Published Specification Lines
1	Bolt on Winch Flatbed Trailer Truck Winches	Size: Bracket Height 140mm, Plate Thickness 8mm Bracket Height 160mm, Plate Thickness 8mm Bracket Height 110mm, Plate Th

Manual Winches

No	Product	Published Specification Lines
1	Manual Winch■Hand Operated Winches For Boat Trailer	Heavy Duty Hand Winch Fit for Trucks, Trailers With Rope/Strap, Hook. Size: From 600 to 3000 lbs. Finish: Color painted,

Other Winches

No	Product	Published Specification Lines
1	Combination Winches Low Profile Leg Bracket Combo Winch	Size: Height 94mm,Plate Thickness 10mm Material: Carbon Steel Color: Black painted Packing: Carton +Pallets

Slide Winches

No	Product	Published Specification Lines
1	Low Profile Sliding Winch (Bottom Mount)	Size: Bracket Height 170mm,Plate Thickness 8mm Bracket Height 190mm,Plate Thickness 8mm Bracket Height 140mm,Plate Thick

Weld-On Winches

No	Product	Published Specification Lines
1	Weld On Winch for Flatbed Truck Trailer, Double Cap	Double Cap, Bracket Height 140mm, Plate Thickness 8mm Material: Carbon Steel Color: Black painted Packing: Carton +Palle
2	Weld-On Winch, Deep Strap Flatbed Truck Trailer Tie Down Winches	Bracket Height 140mm, Plate Thickness 8mm Bracket Height 110mm, Plate Thickness 8mm Material: Carbon Steel Color: Black
3	Side Mount Weld-On Winch	Bracket Height 140mm, Plate Thickness 9mm Bracket Height 110mm, Plate Thickness 9mm Material: Carbon Steel Color: Black
4	Low Profile Weld-On Truck Tie Down Winch	Size: Bracket Height 140mm, Plate Thickness 8mm Bracket Height 160mm, Plate Thickness 8mm Bracket Height 110mm, Plate Th

Wire Rope

20 catalogued items. Full page: qd-kailipu.com/categories/wire-rope.html

Coated Wire Rope

No	Product	Published Specification Lines
1	PVC/PA/PE coated steel wire rope 6X7+FC	Construction Diameter(mm) ApproximateWeight Nominal Tensile Strength 1670 1770 1960 Minimun Breaking Load FC IWRC/WSC FC
2	PVC/PA/PE coated steel wire rope 7X7	Construction Diameter(mm) ApproximateWeight Nominal Tensile Strength 1670 1770 1960 Minimun Breaking Load FC IWRC/WSC FC
3	PVC/PA/PE coated steel wire rope 6X19+FC	Construction Diameter(mm) ApproximateWeight Nominal Tensile Strength 1670 1770 1960 Minimun Breaking Load FC IWRC/WSC FC
4	PVC/PA/PE coated steel wire rope 7X19	Construction Diameter(mm) ApproximateWeight Nominal Tensile Strength 1670 1770 1960 Minimun Breaking Load FC IWRC/WSC FC

Stainless Steel Wire Rope

No	Product	Published Specification Lines
1	STAINLESS STEEL WIRE ROPE 6x19S+IWR	Material: Stainless steel Grade: AISI 304, AISI 304L,AISI 316,AISI 316L Construction: 6x19s+IWR ■Lay direction: RHRL, LH
2	STAINLESS STEEL WIRE ROPE 6x19W+IWR	Material: Stainless steel Grade: AISI 304, AISI 304L,AISI 316,AISI 316L Construction: 6x19W+IWR ■Lay direction: RHRL, LH
3	STAINLESS STEEL WIRE ROPE 6X36WS+IWRC	Material: Stainless steel Grade: AISI 304, AISI 304L,AISI 316,AISI 316L Construction: 6x36WS+IWRC ■Lay direction: RHRL,

Steel Wire Rope

No	Product	Published Specification Lines
1	8x36WS+IWRC Wire Rope	Material: Steel Surface: Galvanized Or Ungalvanized Core: IWR Diameter: 14mm-42mm Packing: Wooden Reel
2	Wire rope 6X24+7FC	Ungalv./Galv./Stainless Steel wire rope 6 strands, 24 main wire per strand
3	Wire Rope 6X19+FC	Ungalv./Galv./Stainless Steel wire rope
4	Wire Rope 6X19+IWRC	Ungalv./Galv./Stainless Steel wire rope
5	Wire Rope 6X19+FC	Ungalv./Galv./Stainless Steel
6	Wire Rope 6X37+FC	Ungalv./Galv./Stainless Steel
7	Wire Rope 6X25Fi+FC	Ungalv./Galv./Stainless Steel
8	Wire Rope 6X37+IWRC	Ungalv./Galv./Stainless Steel
9	Wre Rope 6X19+IWS	Ungalv./Galv./Stainless Steel
10	Wire rope 6X19+IWRC	Ungalv./Galv./Stainless Steel
11	Wire Rope 6X19W+FC	Ungalv./Galv./Stainless Steel 6 strands, nominally 19 main wire per strand
12	Wire rope 6X19W+IWRC	Ungalv./Galv./Stainless Steel

Wire Rope Slings

No	Product	Published Specification Lines
1	Endless Wire Rope Sling Braid Type Grommet Slings	It is made of high-quality steel wire ropes, and the production process is strictly controlled to ensure that the joint-

Pulley Blocks

29 catalogued items. Full page: qd-kailipu.com/categories/pulley.html

Pulley Blocks

No	Product	Published Specification Lines
1	Die casting double pulley	ZINC ALLOY,NICKEL PLATED

Cast Iron Pulleys

No	Product	Published Specification Lines
1	Single Wheel Awning Pulley Fixed Eye, Cast Iron Steel	Availabe Size: 20mm - 70mm
2	Double Wheel Awning Pulley Fixed Eye, Cast Iron Steel	Availabe Size: 20mm - 70mm
3	Cast Iron Pulley Block, Black Cast Iron Wire Pulley With Forged Hook	Availabe Size: 80mm - 200mm
4	Cast Iron Rope Block, Hand Wheel Rope Pulley, Black Cast Iron Wire Pulley With Rebar Hook	Availabe Size: 80mm - 180mm

Snatch Blocks

No	Product	Published Specification Lines
1	Trawl Block With Eye Single Wheel	Load capacity: 0.5t-1t Rope diameter: 8mm -10 mm
2	Mounting Block With Hook, Single HQGK	Load capacity: 0.5t-20t Rope diameter: 7.7mm -35 mm Block Model: HQG(L)
3	Mounting Block With Eye, Single With A Hinged Lid	Load capacity: 0.5t-20t Rope diameter: 7.7mm -35 mm Block Model: HQG(L)
4	Snatch Block with Shackle HDG/ RED Lifting Marine Pulleys	Availabe Size: 3" 1.5T 4" 3T 5" 4.5T 6" 6T 8" 8T
5	Heavy Duty Snatch Block With Shackle HDG/ RED Lifting Marine Pulleys	Availabe Size: 3" 1.5T 4" 3T 5" 4.5T 6" 6T 8" 8T
6	Snatch Block With Hook Single Oval Eye Marine Pulleys	Availabe Size: 5" 3T 6" 5T
7	Single Sheave Pulley Block With Swivel Oval Eye	Availabe Size: 5" 3T 6" 5T
8	Pulley Block Double With Oval Eye B Type	Availabe Size: 3" 0.5T 4" 1T 5" 1.5T 6" 2T 7" 3T 8" 4T 10" 5T
9	Snatch Pulley Block Triple With Hook B Type	Size: 4" Capacity: 1T For wire rope dia(mm) 10mm Weight: 3.5KG Size: 5" Capacity: 1.5T For wire rope dia(mm) 13mm Weig
10	Pulley Block Double With Hook Open Type	Availabe Size: 3" 0.5T 4" 1T 5" 1.5T 6" 2T 7" 3T 8" 4T 10" 5T 12" 6T
11	Sheave Pulley Block Single With Hook B Type	Availabe Size: 3" 0.5T, 4" 1T, 5" 1.5T, 6" 2T. 7" 3T 8" 4T 10" 5T
12	Pulley Block Single With Hook K Type	Availabe Size: 3" 0.5T, 4" 1T, 5" 1.5T, 6" 2T. 7" 3T 8" 4T 10" 5T 12" 6T
13	Triple Pulley Block Snatch K-Type With Hook	Size: 4" Capacity: 1T For wire rope dia(mm) 10mm Weight: 3.5KG Size: 5" Capacity: 1.5T For wire rope dia(mm) 13mm Weig
14	Double Snatch Block With Hook	Availabe Size: 2" 0.25T, 3" 0.5T, 4" 0.8T, 5" 1.5T, 6" 2T. 7" 3T
15	Snatch Block Manufactuers in China-Single With Hook	Availabe Size: 2" 0.25T, 3" 0.5T, 4" 0.8T, 5" 1.5T, 6" 2T.

No	Product	Published Specification Lines
16	H408 LIGHT TYPE CHAMPION SNATCH BLOCK DOUBLE SHEAVE WITH HOOK	H408 LIGHT TYPE CHAMPION SNATCH BLOCK DOUBLE SHEAVE WITH HOOK Size S.W.L. Dia of Rope N.W. (in) (ton) (in) (kg) 4 1/2 4
17	Shackle Type Snatch Block / H419 Light Type Champion Snatch Block With Shackle	CHAMPION SNATCH BLOCK CABLE PULLEY SWIVEL SHACKLE BLOCK
18	H418 SNATCH BLOCK LIGHT TYPE CHAMPION WITH HOOK	CHAMPION SNATCH BLOCK CABLE PULLEY SWIVEL HOOK BLOCK

Zinc Alloy Pulleys

No	Product	Published Specification Lines
1	Die Cast Fixed Double Pulley Metal Wheel	Material (Body): Die Cast Zinc Alloy Wheel Material: Steel / Galvanized Metal Eye Type: Fixed Eye Number of Wheels: 2 (D)
2	Die Cast Fixed Eye Pulley Single Metal Wheel	Material (Body): Die Cast Zinc Alloy Wheel Material: Steel / Galvanized Metal Eye Type: Fixed Eye Number of Wheels: 1 (S)
3	Swivel Eye Single Pulley Block Die Casting Metal Wheel	Type: Swivel Eye Single Pulley Block Material: Die-Cast Zinc Alloy / Metal Wheel Wheel: Single wheel design Finish: Zinc
4	Swivel Eye Pulley Block Die Casting Double Metal Wheel	Type: Swivel Eye Double Pulley Block Material: Die-Cast Zinc Alloy / Metal Wheel Wheel: Single wheel design Finish: Zinc
5	Single Wheel Nylon Fixed Pulley	Type: Single Wheel Fixed Pulley Wheel Material: Nylon Frame Material: Steel / Zinc Alloy (optional) Wheel Quantity: 1 (s)
6	Double Wheel Nylon Fixed Pulley	Type: Fixed Eye Double Wheel Pulley Wheel Material: Nylon Frame Material: Steel / Zinc Alloy (optional) Wheel Quantity:

How To Order

- Send the item names or our page links plus the sizes and quantities you need.
- Tell us the finish you want: zinc plated, hot dip galvanised, powder coated, electrophoretic black or self colour.
- Say whether you need a Material Test Certificate to EN 10204 3.1 with the batch.
- Tell us the destination port and whether you want the goods held in our Qingdao warehouse to consolidate with other items.
- For custom parts send a drawing on WhatsApp or by email. CAD files for our standard range are supplied on request rather than published for download.

Qingdao Kailipu Electromechanical Co., Ltd
No.66 Changcheng Road, Chengyang District, Qingdao, China
sales@qd-kailipu.com
WhatsApp +86-18660236941
qd-kailipu.com