

Ratchet Straps Catalogue

67 catalogued ratchet straps supplied from Qingdao China with Material Test Certificates on request.

Ratchet Tie Downs

Tie Down Hardware

Winch and Tow Straps

All figures in this document are the specification lines published in the Kailipu catalogue. Where a value is not stated it is available on request. Send a drawing or a bill of materials on WhatsApp +86-18660236941 or to sales@qd-kailipu.com and we will confirm sizes, finish and lead time.

Ratchet Straps

67 catalogued items. Full page: qd-kailipu.com/categories/tie-down-strap.html

Ratchet Tie Downs

No	Product	Published Specification Lines
1	50mm 5000kgs Ratchet Tie Down with Alu. handle and Doube J Hook	◆ Width:50mm ◆ Webbing Breaking Strength:6400kg ◆ Working Load:2500 kg ◆ Assembly Breaking Strength:5000 kg ◆ Safety Fac
2	50mm 5000kg Ratchet Tie Down with Rubber Handle and Flat Hook	◆ Width:50mm ◆ Webbing Breaking Strength:6400kg ◆ Working Load:2500 kg ◆ Assembly Breaking Strength:5000 kg ◆ Safety Fac
3	50mm Ergo Ratchet Tie Down LC 2500KG	◆ Width:50mm ◆ Webbing Breaking Strength:6400kg ◆ Working Load:2500 kg ◆ Assembly Breaking Strength:5000 kg ◆ Safety Fac
4	75mm 7500kg Ratchet Tie Down with Flat Hook	◆ Width:75mm ◆ Webbing Breaking Strength:9600kg ◆ Working Load:3750kg ◆ Assembly Breaking Strength:7500kg ◆ Safety Facto
5	100mm 10000kg Ratchet Tie Down	◆ Width:100mm ◆ Webbing Breaking Strength:12800kg ◆ Working Load:5000kg ◆ Assembly Breaking Strength:10000kg ◆ Safety Fa
6	25mm 800kg Ratchet Tie Down European Type	◆ Width:25mm ◆ Webbing Breaking Strength:1000kg ◆ Working Load:400 kg ◆ Assembly Breaking Strength:800 kg ◆ Safety Facto
7	25mm 1000kg Ratchet Tie Down European Type	◆ Width:25mm ◆ Webbing Breaking Strength:1250kg ◆ Working Load:500 kg ◆ Assembly Breaking Strength:1000 kg ◆ Safety Fact
8	25mm 1000kg Ratchet Tie Down with Swan Hook and Keeper	◆ Width:25mm ◆ Webbing Breaking Strength:1800kg ◆ Working Load:750 kg ◆ Assembly Breaking Strength:1500 kg ◆ Safety Fact
9	25mm 1500kg Ratchet Tie Down European Type	◆ Width:25mm ◆ Assembly Breaking Strength:1500 kg ◆ Safety Factor:2:1 ◆ Webbing Color:Yellow/Orange/Blue/Green ◆ Ratchet
10	35mm 2000kg Ratchet Tie Down European Type	◆ Width:35mm ◆ Webbing Breaking Strength:2600kg ◆ Working Load:1000 kg ◆ Assembly Breaking Strength:2000 kg ◆ Safety Fac
11	38mm 3000kg Ratchet Tie Down European Type	◆ Width:38mm ◆ Webbing Breaking Strength:3900kg ◆ Working Load:1500 kg ◆ Assembly Breaking Strength:3000 kg ◆ Safety Fac
12	1" Ratchet Strap with S Hooks	◆ Width:1" ◆ Webbing Breaking Strength:2600 lbs ◆ Working Load:800 lbs ◆ Assembly Breaking Strength:2200 lbs ◆ Safety Fa
13	1"Thumb Ratchet Strap w/ Wire Hooks	◆ Width:1" ◆ Webbing Breaking Strength:2600 lbs ◆ Working Load:800 lbs ◆ Assembly Breaking Strength:2200 lbs ◆ Safety Fa
14	1" Endless Ratchet Strap	◆ Width:1" ◆ Webbing Breaking Strength:2600 lbs ◆ Working Load:800 lbs ◆ Assembly Breaking Strength:2200 lbs ◆ Safety Fa
15	1" Cam Buckle Strap with S-Hooks	◆ Width:1" ◆ Webbing Breaking Strength:2600 lbs ◆ Working Load:800 lbs ◆ Assembly Breaking Strength:2200 lbs ◆ Safety Fa
16	1" Ratchet Strap with Flat Snap Hooks	◆ Width:1" ◆ Webbing Breaking Strength:4000 lbs ◆ Working Load:1000 lbs ◆ Assembly Breaking Strength:3000 lbs ◆ Safety F
17	1" Ratchet Strap with Wire Hooks Light Duty	◆ Width:1" ◆ Webbing Breaking Strength:4000 lbs ◆ Working Load:1000 lbs ◆ Assembly Breaking Strength:3000 lbs ◆ Safety F
18	2" Ratchet Strap w/ Wire Hooks/Double J Hooks	◆ Width:2" (stenciled) ◆ Webbing Breaking Strength:12000 lbs ◆ Working Load:3300 lbs ◆ Assembly Breaking Strength:10000
19	2" Ratchet Strap with Black Flat Hook	◆ Width:2" (stenciled) ◆ Webbing Breaking Strength:12000 lbs ◆ Working Load:3300 lbs ◆ Assembly Breaking Strength:10000
20	2" Ratchet Strap with Chain Extension	Width:2" Webbing Breaking Strength:12000 lbs Working Load:3300 lbs Assembly Breaking Strength:10000 lbs Safety Factor:3:
21	2" Ratchet Strap with Twisted Flat Snap Hooks	◆ Width:2" ◆ Webbing Breaking Strength:12000 lbs ◆ Working Load:3300 lbs ◆ Assembly Breaking Strength:10000 lbs ◆ Safety
22	2" Endless Ratchet Strap	◆ Width:2" ◆ Webbing Breaking Strength:6000 lbs ◆ Working Load:1467 lbs ◆ Assembly Breaking Strength:4400 lbs ◆ Safety F

No	Product	Published Specification Lines
23	2" E Track Ratchet Straps w/ Spring E-Fittings	◆ Width:2" ◆ Webbing Breaking Strength:6000 lbs ◆ Working Load:1467 lbs ◆ Assembly Breaking Strength:4400 lbs ◆ Safety F
24	E-Track Tie Down Straps - Cam Buckle E-Track Cam Straps	◆ Width:2" ◆ Webbing Breaking Strength:6000 lbs ◆ Working Load:1467 lbs ◆ Assembly Breaking Strength:4400 lbs ◆ Safety F
25	E Track Rope Tie Off 2"x6"	◆ Width:2" ◆ Webbing Breaking Strength:6000 lbs ◆ Working Load:1467 lbs ◆ Assembly Breaking Strength:4400 lbs ◆ Safety F
26	3" Ratchet Strap with Chain Extension	◆ Width:3" ◆ Webbing Breaking Strength:20000 lbs ◆ Working Load:5400 lbs ◆ Assembly Breaking Strength:16200 lbs ◆ Safety
27	4" Ratchet Straps with Flat Hooks	◆ Width:4" ◆ Webbing Breaking Strength:25000 lbs ◆ Working Load:7300 lbs ◆ Assembly Breaking Strength:22000 lbs ◆ Safety
28	Ratchet Strap	Strap Material: 100% Polyester Safety Factor: 2:1 or 3:1 Length/Color: As required Certificate: CE/GS Standard: EN 12195

Tie Down Hardware

No	Product	Published Specification Lines
1	DOUBLE J HOOK	Available Size: 4" DOUBLE J HOOK, BS:10000KG/22000LBS 3" DOUBLE J HOOK, BS:10000KG/22000LBS 2" DOUBLE J HOOK, BS:5000KG/
2	2 "DOUBLE J HOOK WITH TUBE	Available Size: 2" BS:5000KG/11000LBS
3	SINGLE J HOOK WITH TUBE	Available Size: 2"SINGLE J HOOK WITH TUBE BS:5000KG/11000LBS 2" SINGLE J HOOK BS:3000KG/6600LBS
4	SINGLE J HOOK	Available Size: 2" SINGLE J HOOK BS:3000KG/6600LBS 1.5" SINGLE J HOOK BS:3000KG/6600LBS 1"SINGLE JHOOK BS:800KG/1760LBS
5	2" DOUBLE J HOOK WITH LATCH	Available Size: 2" BS:5000KG/11000LBS
6	HOOK WITH KEEPER	Available Size: 3"HOOK WITH KEEPER BS:10000KG/22000LBS 1.5"HOOK WITH KEEPER BS:3000KG/6600LBS
7	WELDED J HOOK	Available Size: 2"WELDED J HOOK BS:5000KG/11000LBS 1.5"WELDED HOOK BS:3000KG/6600LBS
8	DOUBLE S HOOK	Available Size: BS:800KG/1760LBS
9	SWIVEL J HOOK	Available Size: 2" U HOOK BS:10000KG/22000LBS 2" U HOOK BS:5000KG/11000LBS 2" U HOOK BS:5000KG/11000LBS 3000KG/6600LBS
10	2" U HOOK	Available Size: 2" U HOOK BS:10000KG/22000LBS 2" U HOOK BS:5000KG/11000LBS 2" U HOOK BS:5000KG/11000LBS 3000KG/6600LBS
11	FLAT HOOK	Available Size: 4" FLAT HOOK, BS:8000KG/17600LBS 3" FLAT HOOK, BS:8000KG/17600LBS 2" FLAT HOOK, BS:5000KG/11000LBS 2" FL
12	S HOOK 1"	Available Size: BS:800KG/1760LBS 1500KG/3300LBS
13	S HOOK W/LATCH 1"	Available Size: 1" S HOOK BS:800KG/1760LBS 1500KG/3300LBS
14	2" E HOOK	Available Size: 2" 1500Kg
15	Sider Hook 2"	Available Size: 2" 3000Kg
16	2" STEEL DELTA RING	Available Size: 2" 5000Kg 2" 3000Kg
17	Welded Strap D-Ring	Available Size: 2" 5000Kg 2" 3000Kg 1.5" 1500Kg 1" 750Kg
18	FORGED BUCKLE 50MM	-High strength steel -Zinc coated surface -Forged -Compatible to 50mm lashing webbing or strap -BS:5000KG/11000LBS
19	WELDED BUCKLE 40mm/50mm	-High strength steel -Zinc coated surface -Welded join -Compatible to 40mm and 50mm lashing webbing or strap -Weight: 36
20	1/2" CAM BUCKLE 001	1/2" CAM BUCKLE BS:110KG/220LBS A=13 B=12 C=25

No	Product	Published Specification Lines
21	1" CAM BUCKLE 002	1" CAM BUCKLE BS:200KG/440LBS A=26 B=17 C=44
22	1" CAM BUCKLE 003	1" CAM BUCKLE BS:250KG/550LBS A=26 B=12 C=45
23	1" CAM BUCKLE 004	1" CAM BUCKLE BS:350KG/770LBS A=26 B=15 C=50
24	1" CAM BUCKLE 005	1" CAM BUCKLE BS:400KG/880LBS A=26 B=15 C=50
25	1" CAM BUCKLE 006	1" CAM BUCKLE BS:400KG/880LBS A=26 B=15 C=50
26	1" CAM BUCKLE 007	1" /25mm CAM BUCKLE BS:500KG/1100LBS A=26 B=16 C=50
27	1" CAM BUCKLE 008	1" CAM BUCKLE BS:600KG/1320LBS A=28 B=25 C=65
28	2" CAM BUCKLE 009	2" CAM BUCKLE BS:900KG/1980LBS A=52 B=28 C=75
29	1" CAM BUCKLE 010	1" CAM BUCKLE BS:700KG/1540LBS A=26 B=28 C=57
30	1.5" CAM BUCKLE 011	1.5" CAM BUCKLE BS:900KG/1980LBS 700KG/1540LBS A=38 B=25 C=70
31	2" CAM BUCKLE 012	2" CAM BUCKLE BS:1100KG/2420LBS A=52 B=28 C=75
32	Double J Hooks	Double J hook DJH-- -10Tx10mm DJH-- -10Tx75mm DJH-- -5Tx50mm DJH-- -5Tx50mm with Hook Keeper DJH-- -4Tx50mm DJH-- -3Tx50
33	Ratchet buckle	10101 --10Tx100mm 75101 --10Tx75mm 50501 --5Tx50mm,plastic handle 50502 --5Tx50mm.Aluminum handle 50512 --5Tx50mm, Ergo

Winch and Tow Straps

No	Product	Published Specification Lines
1	Lasso Strap with O Ring 2" x 10'	◆ Width:2" ◆ Webbing Breaking Strength:12000 lbs ◆ Working Load:3333lbs ◆ Assembly Breaking Strength:10000 lbs ◆ Webbing
2	4" Winch Strap with Chain Extension	◆ Width:4" ◆ Webbing Breaking Strength:25000 lbs ◆ Working Load:7300 lbs ◆ Assembly Breaking Strength:22000 lbs ◆ Safety
3	4" Flat Hook Winch Straps	◆ Width:4" ◆ Webbing Breaking Strength:25000 lbs ◆ Working Load:7300 lbs ◆ Assembly Breaking Strength:22000 lbs ◆ Safety
4	4" Winch Strap w/ Double J hook	◆ Width:4" ◆ Webbing Breaking Strength:25000 lbs ◆ Working Load:7300 lbs ◆ Assembly Breaking Strength:22000 lbs ◆ Safety
5	4" Winch Strap with Delta Ring	◆ Width:4" ◆ Webbing Breaking Strength:25000 lbs ◆ Working Load:7300 lbs ◆ Assembly Breaking Strength:22000 lbs ◆ Safety
6	4" Winch Strap with Twisted Loop	◆ Width:4" ◆ Webbing Breaking Strength:25000 lbs ◆ Working Load:7300 lbs ◆ Assembly Breaking Strength:22000 lbs ◆ Safety

How To Order

- Send the item names or our page links plus the sizes and quantities you need.
- Tell us the finish you want: zinc plated, hot dip galvanised, powder coated, electrophoretic black or self colour.
- Say whether you need a Material Test Certificate to EN 10204 3.1 with the batch.
- Tell us the destination port and whether you want the goods held in our Qingdao warehouse to consolidate with other items.
- For custom parts send a drawing on WhatsApp or by email. CAD files for our standard range are supplied on request rather than published for download.

Qingdao Kailipu Electromechanical Co., Ltd
No.66 Changcheng Road, Chengyang District, Qingdao, China
sales@qd-kailipu.com
WhatsApp +86-18660236941
qd-kailipu.com