

Truck Wheel and Rim Specifications

Resunyou Co., Limited · Qingdao, Shandong Province, China · sales@resunyou.com · +86 186 6979 3873

Figures below are the published data for each pattern. Where a value is not listed it is confirmed in writing before an order. Approval marking depends on the destination market.

Model	Rated Load	PCD	Bolt Hole	Centre Hole	Offset	Hand Hole	Valve
8.50-24	4500kg	φ335	10-φ26	φ281	180	10-57×32	-
6.00G-16	1450kg	φ222.25	6-φ24	φ164	120	6-30×80	-
17.5X6.75	3000kg	ø225	ø26	ø176	-	120	141
22.5x11.75 Dual Polished	4750kg	ø285.75	ø26.75	ø220	-	120	-
22.5x11.75 Coated	5000kg	ø335	ø26	ø281.2	-	119.5	144.5
22.5x8.25 Gloss Black	3650kg	ø335	ø26	ø281.2	-	145	168
22.5x8.25 Machined Face	3650kg	ø335	ø32	ø281.2	-	145	168
22.5×11.75	4250kg	φ335	10-φ26	φ281	0	18-φ36	V3-20-5
19.50×14.00	5000kg	φ335	10-φ26	φ281	0	10-57×32	TR575
24.5×8.25	3250kg	φ285.75	10-φ32	φ222	169	2-116×86	V3-20-4
22.5×8.25	3000kg	φ335	10-φ26	φ281	165	10-φ70	V3-20-4
22.5×9.0	3750kg	φ285.75	10-φ26	φ220	175	10-φ64	V3-20-6
17.5×6.75	2000kg	φ225	10-φ26	φ176	V3-20-4	142	5-φ55/Oval
22.5×11.75 10 Hand Holes	4250kg	φ335	10-φ26	φ281	120	10-φ70	TR572C
22.5×11.75 20 Hand Holes	4250kg	φ335	10-φ26	φ281	120	20-φ36	V3-20-5
22.5X14.00	5600kg	φ335	10-φ26	φ281	0	20-φ36	TR572C

Wheels without a published specification table are quoted on request.