



LED downlight - surface mounted

Product Features & Advantage	1, surface mounted/pendent light. Hole-free surface mounting, easy and quick to install without complex ceiling renovation.
	2, Sleek & compact design, fits various interior styles (residential/commercial).
	3, die-casting aluminum housing, stable performance and extended product life.
	4, Mercury-free & eco-friendly, no UV/IR radiation, safe for daily use.
	5, Anti-glare optical design, comfortable lighting without eye strain.
	6. Conform CE, RoHS, FCC, SAA, PSF certifications.

General data	General	Material	die-casting aluminum	
		Finish	white; black	
	Electrical	Light efficacy	95 lm/w	
		Input voltage	AC100-240V	
		Power factor (PF)	>0.9	
	Optical	CCT	2700K/3000K/4000K/6000K	
		Led type	CREE COB	
		CRI	>80/90	
		Beam angle	24°/45°	
		SDCM	<3	
	Function	Control	Non-dim./ Triac Dim. / DALI dim./ 0-10V dim	
		Tilting angle	/	
		Rotating angle	/	
	Durability	IP grade	IP20/IP65	
		Operating Temperature	-20°C ~ +40°C	
		Lifespan	>50,000H(L90,Tc=55°C)	
		Warranty	3 years	

Model	Power	Size(mm)	Model	Power	Size(mm)
WK-DL-S-10W	10W	φ90*90mm	WK-DL-S-15W	15W	φ110*120mm
WK-DL-S-20W	20W	φ130*135mm	WK-DL-S-30W	30W	φ170*185mm
WK-DL-S-40W	40W	φ195*195mm			

Notes & Warnings:	NOTES 1, Match rated voltage with mains 2, Mount on flat, firm surface only 3, No housing covering during use 4, Use dedicated dimmer if dimming WARNINGS 1, Power off for installation/maintenance 2, No unauthorized disassembly/modification 3, Keep away from heat, fire, water splash 4, Keep out of children/pets' reach 5, No overload/incompatible accessories 6, Do not touch hot lamp body after use
Applications:	1, Residential areas: Living room, bedroom, kitchen, study, hallway 2, Commercial spaces: Office, retail store, exhibition hall, shopping mall 3, Public areas: Corridor, stairwell, waiting area, lobby 4, Service venues: Hotel, restaurant, café, clinic 5, Industrial & utility: Workshop, storage room, garage

Updated on: 202601