



Silicone flexible led strip light - side view

Product Features:	1, Side-Facing Light Emission: The LED chips are arranged to perpendicularly to the strips surface (side-oriented), ensuring concentrated lateral illumination. 2, Silicone Encapsulation Advantages: Made of food-grade, high-transparency, IP67 waterproof protection, corrosion resistance, and UV resistance . 3, Structural Design: Flexible FR-4 is fully wrapped in silicone, resulting in a slim profile that balances flexibility and sturdiness. Minimum bending radius $\geq 10\text{mm}$ (single direction) allows adaptation to mild curves. 4, Optical Performance: Available in warm white, natural white , cool white , and RGB/RGBW variants. High CRI (Ra $\geq 80/90$) . Beam angle: 120°–150°. high brightness and no dark spots. 5, Electrical Stability: Low voltage 12V/24V DC, effective power consumption , and high luminous flux . 6, Flicker-free : No video / mobile phone flicker. dimming (PWM $\geq 20\text{kHz}$) supports brightness adjustment from 10% to 100%.
--------------------------	--

Advantages:	1, Targeted & Lateral Illumination: Side-view design directs light horizontally (not upward/downward), making it perfect for wall washing, edge lighting, or illuminating vertical surfaces. Silicone diffusion ensures no pixelated spots—creating a high-end, uniform aesthetic for indirect lighting. 2, All-Round Protection: Silicone housing shields internal LEDs from moisture, dust, oil, and physical impact—suitable for both indoor humid environments and outdoor protected areas. 3, Durability & Longevity: Silicone's weather resistance and the PCB's efficient heat dissipation extend the service life to $\geq 50,000$ hours (L70). The strip resists yellowing, cracking, and corrosion even under long-term use. 4, Space-Saving & Concealable: Slim, low-profile design (thickness $\leq 8\text{mm}$) allows hidden installation in narrow gaps (e.g., wall recesses, cabinet edges, or ceiling cornices). It stays out of sight while delivering impactful light. 5, Safety & Versatility: Low working voltage (12V/24V) eliminates electric shock risks. Compatible with dimmers, controllers (for RGB models), and smart home systems. Food-grade silicone options are safe for use in food contact areas (e.g., restaurant kitchens).
--------------------	--

Product details:	LED type	2835 / 5050/ 3528/ 2216 smd; COB	
	Model number	WK-SPxx-xx	
	Housing material	silicone	
	Size	see [sideview size list]	
	Input voltage	DC 12V/24V	
	LED qty	customizable	
	Power Consumption	based on led qty	
	Color temperature	R/G/B / 1800-7000K/ RGB/ RGBW...	
	CRI (Ra)	> 80/90/95	
	Beam angle	120°	
	Lumens per watt	>90 lm/w	
	IP grade	IP 67/68	

Packaging details:	Meters per roll	5M/ 8M / 10M...customizable	Anti-static bag + foam buffer + carton box
	Rolls per carton	100 rolls / 50 rolls	
	Carton dimension		

Commitment:	1. Brand chip: Samsung, Osram, Philips, Epistar 2. Double PCB, reduce the voltage drop. 3. Comply with international standard: CE,ROHS, UL,PSE etc. 4. Quality guarantee : 2/3 years. (Warranty does not cover damage caused by improper use, installation, or modification.)
--------------------	--

	Feature	Side View	Top View
Key Difference (side view VS top view)	Light Direction	Lateral (horizontal)	Upward (vertical)
	Ideal For	Wall washing, edge lighting	Ceiling coves, overhead ambient
	Glare Risk	Lower (light directed away from eyes)	Higher (direct upward glow)
	Installation Position	Wall recesses, cabinet sides	Ceiling gaps, under-cabinet tops

Notes & Warnings:	1, Use a dedicated LED driver with matching voltage and current rating to avoid overloading. 2, For 12V strips longer than 5m or 24V strips longer than 10m, dual-end power supply is recommended to prevent voltage drop. 3, Cutting must be performed at designated cutting marks (if applicable); avoid damaging the PCB or silicone housing. 4, Do not immerse non-waterproof (IP20) models in water or expose to heavy moisture. 5, Avoid bending the strip beyond the minimum bending radius to prevent LED chip or PCB damage. 6, During installation, ensure proper heat dissipation; do not cover the strip with heat-insulating materials for long-term use. 7, Static-sensitive: Wear anti-static gloves when handling the strip to avoid electrostatic damage to LED chips.
------------------------------	---

Applicatons:	1, Wall Washing & Architectural Lighting: Installed in wall recesses, ceiling cornices, or floor skirting to cast soft lateral light across vertical surfaces;Outdoor building facades, columns, or balcony edges to outline architectural contours at night without glare. 2, Indoor Decorative & Task Lighting: Cabinet & Shelf Lighting; TV/Monitor Backlighting. 3, Commercial & Retail Lighting: Retail Displays; Restaurant & Café Ambiance. 4, Outdoor Protected Areas: Patio & Pergola Lighting;Garden Edging. 5, Furniture & Custom Lighting: Bed Frame Lighting;Desk & Workspace Lighting.
---------------------	---

Updated on: 202511