



Silicone flexible wall washing strip - 16*16mm 48pcs led

Product Features:	1, Dedicated Wall-Washing Optics: Narrow beam angle (15°–45°) for uniform, glare-free light coverage on vertical surfaces. 2, Integrated Silicone Encapsulation: IP67/IP68 waterproof rating, resistant to dust, moisture and UV rays for indoor/outdoor use. 3, High Flexibility: Bendable to fit curved walls or architectural contours without light leakage. 4, Low-Voltage Safe Operation: DC 24V input, suitable for long-distance installation with stable brightness. 5, Cuttable & Spliceable: Pre-marked cutting points for custom lengths, compatible with standard connectors for easy extension.
--------------------------	---

Advantages:	1, Precise Wall-Washing Effect: Narrow 15°–45° beam angle delivers even, shadow-free illumination on vertical surfaces. 2, Weatherproof Durability: Integrated silicone housing with IP67/IP68 rating resists dust, moisture and UV damage for indoor/outdoor use. 3, Curved Surface Adaptability: Ultra-flexible design fits irregular architectural contours without light leakage or damage. 4, Easy Customization: Cuttable at pre-marked points and spliceable, suitable for projects of any length.
--------------------	---

Product details:	LED type	2835 smd	
	Model number	WK-SP2835-48 wall wash	
	Housing material	silicone	
	Size	16x16 mm (PCB width: 22 mm)	
	Input voltage	DC 24V	
	LED qty	48 pcs	
	Power Consumption	16w-18w/m	
	Color temperature	R/G/B / 1800-7000K	
	CRI (Ra)	> 80/90	
	Beam angle	30°	
	Lumens per watt	>90 lm/w	
	IP grade	IP 67/68	

Packaging details:	Meters per roll	5M/ 8M / 10M...customizable	Anti-static bag + foam buffer + carton box
	Rolls per carton	50 rolls	
	Carton dimension		

Commitment:	1. Brand chip: Samsung 2. Double PCB, reduce the voltage drop. 3. Comply with international standard: CE,ROHS, UL,PSE etc. 4. Quality guarantee : 2/3 years. (Warranty does not cover damage caused by improper use, installation, or modification.)
--------------------	--

Notes & Warnings:	1, Use only DC 12V/24V compatible power supplies; avoid AC voltage connection. 2, Seal cutting/splicing joints with waterproof silicone glue before outdoor installation. 3, Do not bend the strip beyond its flexibility limit to prevent circuit damage. 4, Mount the strip with dedicated clips; avoid direct pulling or stretching during installation. 5, Disconnect power completely before maintenance, cleaning, or replacement. 6, Keep away from high-temperature sources and corrosive environments.
Applications:	1, Architectural Facades: Highlight building contours, columns and exterior wall textures for commercial and residential buildings. 2, Indoor Commercial Spaces: Create ambient lighting for hotel lobbies, restaurant feature walls and retail store backdrops. 3, Cultural & Exhibition Venues: Illuminate museum exhibit walls, art gallery displays and exhibition hall booths. 4, Outdoor Landscapes: Decorate park pavilions, villa garden walls and scenic spot viewing platforms. 5, Entertainment Venues: Enhance ambiance for KTV private rooms, bar walls and theater lobbies.

Updated on: 202511